
PREFERRED 45° ACCEPTABLE
COIN EDGES TO ELIMINATE BURRS
BLADE THICKNESS AND WIDTH MUST BE MAINTAINED FOR A MINIMUM OF 0.9 MM FROM THE COINED END
END OF TERMINAL MUST BE FREE OF BURRS
0.6 MAX COIN
MATERIAL SPECIFICATIONS
RECOMMENDED
BASE METAL - COPPER ALLOY, EITHER BRASS OR PHOSPHOR BRONZE
PLATING - 0.0050 ± 0.0025 MM THK TIN
MINIMUMS
ELECTRICAL CONDUCTIVITY - > 0.300 IACS AT 20°C. USE OF A MATERIAL WITH LESS THAN THIS VALUE MUST BE APPROVED BY DELPHI PACKARD ELECTRIC MATERIALS ENGINEERING.
TENSILE STRENGTH - 407 MPa
PLATING - FOR LOW CURRENT (< 5A) AND NON-PASSENGER COMPARTMENT POWER CIRCUITS, 0.0050 ±0.0025 MM THICK TIN. FOR MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.0050 ±0.0025 MM THICK IS REQUIRED.
BLADE THICKNESS
UNPLATED = 0.813 ± 0.025
TIN PLATED = 0.823 ± 0.030
MATING BLADE INFORMATION
SCALE 10:1
SECTION G-G
SECTION F-F
MATING SHROUD REQUIREMENTS
REQUEST THE LATEST INFORMATION FOR THE MATING SHROUD FROM DELPHI PACKARD ELECTRIC SEE NOTE 1
SECTION E-E
SECTION C-C
DETAIL "X"
SCALE 5:1
SECTION B-B
SECTION A-A
DETAIL "Y" (CRUSH POINT)
SCALE 10:1
DETAIL "Z"
SCALE 10:1
MATING DEVICE REQUIREMENTS
(RELAY APPLICATIONS)
REQUEST THE LATEST INFORMATION FOR THE MATING DEVICES FROM DELPHI PACKARD ELECTRIC SEE NOTE 1
NOTES:
1. ALL RADII 0.4 UNLESS OTHERWISE SPECIFIED
2. DIMENSIONS ARE TO FACE OF VIEW SHOWN UNLESS OTHERWISE INDICATED
3. 3° DRAFT ON ALL OUTSIDE SURFACES UNLESS OTHERWISE INDICATED
4. RECOMMENDED MATERIAL - GLASS FILLED NYLON OR POLYESTER.
5. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST COPY OF THIS PRINT FROM DELPHI PACKARD ELECTRIC
280 SEALED RELAY ASSEMBLED DIMENSIONS
ALL DIMENSIONS ARE REFERENCE, EXCEPT AS NOTED SCALE 1:1
NOTES:
1. MATING COMPONENT DIMENSIONS SHOWN ARE REFERENCE ONLY. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST MATING INFORMATION FROM DELPHI PACKARD ELECTRIC. SEE NOTE 1 ON MATING SHROUD & DEVICE COMPONENT PRINTS FOR ACTUAL DIMENSIONS.
2. WHEN PARTS ARE SHIPPED, THEY MUST BE PACKED IN EITHER PLASTIC BAGS OR SHIPPING CONTAINERS LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER.
3. FOR LOAD LENGTH CALCULATIONS, DISTANCE FROM CAVITY FACE OF CONNECTOR TO FRONT OF CABLE CORE IS 14.5+0.7/-0.0.
4. SEALING CODE 2 - DESIGN WILL PASS SALT-FOG TEST AFTER CONDITIONING AS SPECIFIED IN EIA-364-26A CONDITION A, EXCEPT DURATION IS 96 HOURS. EIA-364 (HANDBOOK MICRO-PACK) - 2 ROW (WORLD CONNECTOR), ETC WHEN MATED TO MATING PART OR EQUIVALENT.
5. UNLESS OTHERWISE SPECIFIED, AND/OR INDICATED ON DRAWING, ALL DIMENSIONS ARE NOMINAL AND ARE FOR REFERENCE ONLY. NOT REQUIRED FOR INSPECTION. USED MATH MODEL FOR PRECISE DIMENSION.
6. NO PROCESSING OIL ALLOWED TO BE ADDED TO AID IN THE APPLICATION OF THE SEAL TO THE CONNECTOR
7. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.
2 MAX GAP ALLOWABLE
CONN BODY - (SEE CHART)
CONN SEAL - (SEE CHART)
4.1 NEWTONS MINIMUM RETENTION
DS-ECLIPSE
SYMBOL DEFINITION
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWINGS.
MISSING SYMBOLS
1-2 5-8 10 13-14
TOTAL NO OF INSPECTIONS REQUIRED 5
LOC NO. 1625 14
REVISION HISTORY
ECR/ECO | REVISION DESCRIPTION | DATE | BY | APVD