

TYPICAL BLADE DETAIL



SECTION B-B



SECTION A-A
SCALE 5:1









DETAIL C
SCALE 5:1

MATING PART DETAIL





SECTION F-F

NOTES
1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED, DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION USING MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. SEALING CODE 3 - DESIGN WILL PASS SALT FOG AND IMMERSION PER GMW3172 (CYCLIC CORROSION TEST), GM9508P (ESU-LAM UNDERHOOD MICRO-PACK), ESA-M2P (UNDERHOOD MICRO-PACK), ESA-650 (UNDERHOOD MICRO-PACK), D-4006 (UNDERHOOD MICRO-PACK) WHEN MATED TO MATING PART OR EQUIVALENT.
3. THIS PART IS CONTROLLED FOR AUTOMATIC FEEDING AS DENOTED ON DRAWING WITH ▲.
4. REFERENCE MATING COMPONENTS OR EQUIVALENT: CONNECTOR 12034160
5. THIS PART ACCEPTS THE FOLLOWING COMPONENTS OR EQUIVALENT: TERMINAL 12034150
6. BOLT TO BE RETAINED TO A MIN. 400 N FORCE.
7. "*" INDICATES BOLT IS INTERNALLY DRIVEN WITH A 4* (1.0MM) RECESS.
8. CONNECTOR TO BE ASSEMBLED TO MATING PART WITH M8 N-M (70 IN-LBS) TORQUE.
9. RETENTION TO BE MEASURED AT A TORQUE OF 1.5 N-M (13.3 IN-POUNDS) AFTER RETAINER IS ASSEMBLED.
10. FOR LEAD LENGTH CALCULATIONS, DISTANCE FROM MATING END OF CONNECTOR TO FRONT OF CABLE SEAL IS 10.15-17.05
11. WHEN PARTS ARE STORED OR SHIPPED THEY MUST BE PACKED IN PLASTIC BAGS OR TRAYS/TRAY DIVIDERS THAT ARE LINED WITH ANTISTATIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER.

SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (XX) DOES NOT REQUIRE INSPECTION, IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 18	NO MISSING SYMBOL NUMBER
	LAST NO. USED: 65	

ENG STATUS				DR	REVISION HISTORY	APV	DR RELEASED
DATE	SHEET	SHEET	ZONE				
07MAY08	M	04	-	-	12034161 - RESTRICTED) 12034151 - RELEASED	31JUL07	31JUL07
10MAR08	B	05	-	-	12034161 - OBSOLETE	27JAN06	20FEB08

PART NO	REV	STATUS	NO. OF FEMALE TERMINALS	RETAINER	BOLT HEAD SIZE	PART NO	BLOCKAGE CAVITIES	COLOR	SEAL NO. 1 PART NO	BLOCKAGE CAVITIES	COLOR
15492931	B1	RELEASED	14	15492934	1/4 IN - HEX	12034161	NONE	GREEN	12034161	NONE	GREEN
15492687	A1	OBSOLETE	14	15492934	7MM - HEX	15492688	NONE	GRAY	15492688	1,4,5,8,9	PURPLE
12089909	A1	OBSOLETE	14	12034235	1/4 IN - HEX	12089908	NONE	GRAY	12089908	NONE	GRAY
12040350	A3	OBSOLETE	12	12034235	7MM - HEX	12034161	NONE	GREEN	12040349	10,11 & 12	BLUE
15492682	A2	OBSOLETE	12	15492934	7MM - HEX	15492683	NONE	GREEN	15492683	NONE	GREEN
12084968	C1	OBSOLETE	14	12034236	12084774	TIN +	12034161	NONE	GREEN	12034161	NONE	GREEN
12057279	A1	OBSOLETE	11	12034236	12057276	7MM - HEX	12034161	NONE	GREEN	12041359	1,11 & 14	TAN
12041370	B1	OBSOLETE	11	12034236	12034235	1/4 IN - HEX	12034161	NONE	GREEN	12041359	1,11 & 14	TAN
12034161	E6	OBSOLETE	14	12034235	12034235	1/4 IN - HEX	12034161	NONE	GREEN	12034161	NONE	GREEN

PART NO	BOLT	MATERIAL
12034161	1/4 IN - HEX	NYLON 66 REINFORCED

PART NO	COLOR
12034160	BLACK

PART NO	COLOR
12034162	BLACK

PART NO	COLOR
12034163	BLACK

PART NO	BLADE NO. WHICH MAY BE OMITTED
12034169	NONE
12034170	2,4,6,8,10,12,14
12034171	1,3,5,7,9,11,13
12034172	NONE
12034168	NONE
12057279	1,4,11 & 14
12041370	1,4,11 & 14
12041362	NONE

DRAWING NUMBER: 12066368
SIZE: A3 | SHEET: 01 | SHEETS OF SHEET: 01 | MATING PART NO: 12034160 | MATING PART NO: 12034161

DRAWING TYPE: PART DRAWING
STYLE:
NAME OF: SHEET ZONE: D
UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN MILLIMETERS
INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994
MATERIAL
FINISH
DELPHI
DELPHI PACKARD ELECTRIC SYSTEMS
WARREN, OH
DATE
APV
CHK
DR
TAXI CONN W/P 150
SIZE: A3 | SHEET NO: 01 | SHEETS OF: 01 | DRAWING NO: 12066368 | REV: A

THIS DRAWING OR SPECIFICATION IS THE PROPERTY OF DELPHI PACKARD ELECTRIC SYSTEMS AND IS LOANED SUBJECT TO AGREEMENT TO RETURN IT UPON DEMAND AND NOT TO REPRODUCE OR COPY IT IN WHOLE OR IN PART. IT IS SUBMITTED IN CONFIDENCE AND MUST NOT BE DISCLOSED TO ANY THIRD PARTY WITHOUT WRITTEN CONSENT OF DELPHI PACKARD ELECTRIC SYSTEMS.

THIRD ANGLE PROJECTION

TOLERANCES UNLESS OTHERWISE SPECIFIED: ANGLES ±1° | 2 PLACE DECIMALS ±0.25 | 3 PLACE DECIMALS ±0.127

ISO 9283