

SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL [] DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	25
	LAST NO. USED	24

MISSING SYMBOLS
NO MISSING SYMBOL NUMBER

DWG STATUS DATE	STS	REC'N/P	CHB	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2
02NOV06	R	01	-	-	13597075 WAS PE15180; 13597076 WAS PE13267; 13597077 WAS PE13268; ALL PARTS RELEASED	283233	MM	MM	SCH
12DEC07	R	02	-	-	ALL PARTS: REVISED MAT'L SIZE: 0.23 X (28) WAS 0.23 X (29)	492629	MM	MM	SCH
24SEP09	R	03	-	-	ALL PARTS - REVISED MATERIAL CODE	499629	PSC	PSC	PSC
04JAN11	R	04	-	-	ALL PARTS - 0.64 +0.07/-0.04 FOR FIRST 5 MM MIN OF BLADE WAS 0.64 ±0.04 FOR FIRST 5 MM MIN OF BLADE	512960	JRL	JRL	CR
06OCT11	R	05			ALL PARTS 0.64 +/- 0.085 WAS 0.64 +/- 0.075	515235	MYP	MYP	MMC






NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. "PXX" INDICATES "P" PLUS LAST TWO DIGITS OF MAKE DIE SERIES NUMBER (P01, P02, P03, ETC).
3. RECOMMENDED MAXIMUM CURRENT CAPACITY IS 7 AMPS.
4. RECOMMENDED MATING FEMALE TERMINAL IS 13543114.
5. CRIMP DIMENSION FROM THE BACK OF THE CORE WING (INCLUDES THE FLARE OUT FROM THE CORE WING) TO THE END OF THE INSULATION WING.

 FOR CABLE O.D. FROM 1.47 MM TO 1.9 MM (INCLUDING 0.8 MM² SPECIAL CABLE INSULATION)
 MAX INSULATION CRIMP WIDTH IS 2.05 MM
 MAX INSULATION CRIMP HEIGHT IS 2.15 MM

 FOR CABLE O.D. FROM 1.86 MM TO 2.25 MM
 MAX INSULATION CRIMP WIDTH IS 2.4 MM
 MAX INSULATION CRIMP HEIGHT IS 2.55 MM
6. "*" DENOTES DIMENSIONS MADE AT CUT-OFF AND CRIMP DIE.
7. MATING COMPONENTS OR EQUIVALENT : CONNECTOR - TBD



PART NO	REV	N/P	STATUS	MAT'L SIZE	MATERIAL SPEC	SIZE (MM²)	GAUGE SIZE	ID	CABLE O.D.	TYPE	$B_{\pm 0.05}$	$B_{\pm 0.05}$	(H_1)	(H_2)	T MAX
13597075	01	AD		0.23 X (28)	SN PLATED COPPER ALLOY	0.13 - 0.22	26 - 24	25	1.05 - 0.81	103	1.6	1.9	1.62	1.89	1.4
13597076	01	AD		0.23 X (28)	SN PLATED COPPER ALLOY	0.35 - 0.5	22 - 20	21	1.82 - 1.47	102	2.1	2.5	2.1	2.7	1.4
13597077	01	AD		0.23 X (28)	SN PLATED COPPER ALLOY	0.75 - 1.0	18 - 16	17	2.25 - 1.7	101	2.6	3.1	2.8	3.5	1.6

DWG TYPE: PART DRAWING
STYLE:
RELEASE DWG: SCRIPT DWG:

UNLESS OTHERWISE SPECIFIED
DATA ASSOCIATED IS TO ACCOMPANY WITH USAGE (SEE NOTE 1) AND IS NOT TO BE USED FOR INSPECTION OR FABRICATION PURPOSES. DIMENSIONS OR FEATURES OF RESTRICTED KEY OR WHERE IMPROPERLY REPRESENTED BY DATUM REFERENCES.

ALL DIMENSIONS ARE IN MILLIMETERS

REFERENCE

PROCESS INSPECTION DIMENSION
DIMENSIONS INCLUDED IN 2 (INSPECT) ARE TO BE INSPECTED AT 2 NO SAMPLE UNITS ARE REPLENISHED

DIMENSIONAL RANGE (MM) | DECIMAL PLACES
FROM 0 | >2
TO 2 |
TOLERANCE USED FOR DIMENSIONS SPECIFIED ONLY | ±0.2
ANGULAR TOLERANCE ±2°

THIRD ANGLE PROJECTION | DO NOT SCALE | USE MATH DATA

DELPHI
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE
WARREN, OH

	DATE
DR APVD1: M. McCALL	02NOV06
APVD2: M. McCALL	02NOV06
APVD3: S.C. HSIEH	02NOV06
APVD4	
APVD5	

SUBSTANCES OF CONCERN ARE RESTRICTED EXCEPT PER DELPHI SPEC(S)

SEE CHART

DRAWING NAME: TAXI TERM M MICRO HVT 064

DRAWING NUMBER: 13597074

SIZE	SCALE	TRANS NO	SHEET NO	STS	REV	N/P
AD	10:1	1	1 OF 1	R	05	-