SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL [ ] DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 77	NO MISSING SYMBOL NUMBER
	LAST NO. USED: 64	

CHG STATUS DATE	STS	REC	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2
310CT2	R	01	-	-		CLEANED REVISION COLUMN, REDRAWN TO PD & 13452173 - RELEASED.	232331	EDS	JWM	DRS
060011	R	02	-	-		ALL PARTS - CREATED APPLICATION DATA	415663	CBD	CBD	DEM
03JA14	R	03	-	-		ALL PARTS - ADDED LUBEWELL LUBRICANT NOTE	424997	JAR	JWM	WRM



MATING TERMINAL INFORMATION
SCALE 10:1

RECOMMENDED MATERIAL:
P-1546 (CA210) EXTRA SPRING TEMPER-TIN PLATED BRASS

PLATING THICKNESS: 0.005-0.003 MM

TENSILE STRENGTH: 480-430 MPa

INSPECTION SYMBOLS SHOWN IN THESE VIEWS ARE FOR REFERENCE ONLY





SECTION A-A



SECTION B-B

MATING CONNECTOR INFORMATION

RECOMMENDED MATERIAL: GLASS-FILLED POLYESTER M-2192-001-NATURAL

INSPECTION SYMBOLS SHOWN IN THESE VIEWS ARE FOR REFERENCE ONLY







TYPE 101





TYPE 102
SAME AS TYPE 101 EXCEPT AS SHOWN

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. WHEN PARTS ARE SHIPPED THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER.
3. SEALING CODE 3 - DESIGN WILL PASS SALT FOG AND IMMERSION TEST AFTER CONDITIONING AS SPECIFIED IN ESA-644 (WEATHER-PACK),ESA-710 (METRI-PACK), ESA-650 (UNDERHOOD MICRO-PACK), C-4006 (WORLD CONNECTOR), ETC WHEN MATED TO MATING PART OR EQUIVALENT
4. THIS PART ACCEPTS THE FOLLOWING COMPONENTS OR EQUIVALENT: CAVITIES TO ACCEPT 12047680 TERMINAL.
5. FOR LEAD LENGTH CALCULATIONS, DISTANCE FROM MATING END OF CONNECTOR TO FRONT END OF CABLE CORE IS 10.15/7.05.
6. FOR PART NUMBERS WITH ADHESIVE, USE M3510001 OR ADHESIVE APPROVED BY MATERIALS ENGINEERING TO GLUE CONNECTOR SEAL TO CONNECTOR.
7. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.
8. 5-60-T LUBEWELL LUBRICANT CAN BE USED AS AN AUXILIARY SUPPORT ON THE CABLE INSTALLATION PROCESS.

			PART NO. WITH ADHESIVE	REV	N/P	PART NO. WITHOUT ADHESIVE	REV	N/P	TYPE	CONNECTOR	CONNECTOR SEAL	CABLE SEAL & COLOR
		-	15452173	01	AB	-	102	12065286		15439078	12065295 - RED	
12186689	B3	-	12186827	A3	-	-	101	12065286		12186821	12110072 - TAN	
		-	12162926	C3	-	-	101	12162925		12052893	12078089 - PURPLE	
		-	12110192	B3	-	-	101	12065286		12052893	12110072 - TAN	
		-	12078090	C3	-	-	101	12065286		12052893	12078089 - PURPLE	
		-	12065287	B3	-	-	101	12065286		12052893	12065295 - RED	

THE DRAWN TERMINAL PART NUMBER OBTAINED THAT PHYSICAL PARTS ARE NOT AVAILABLE FOR ORDERING.

PART NUMBERS THAT OR NOT HAVE A LINE PREFIX INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT DELPHI SALES TO ASSURE AVAILABILITY OF PARTS.

SEE TYPE

PART DRAWING

STYLE

RELEASE DATE | DESIGN OWN

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN MILLIMETERS AND ANGLES ARE IN DEGREES. TOLERANCES PER ASME Y14.5M-1994. GEOMETRIC TOLERANCING PER ASME Y14.5M-1994. SURFACE TEXTURE PER ASME B46.1-1995. DRAWING INTERPRETATION PER ISO 10578-1992. DELPHI ENGINEERING STANDARD CS-0003 MAY BE USED AS A GUIDE TO INTERPRET ISO STANDARDS.

ALL DIMENSIONS ARE IN MILLIMETERS

REFERENCE

(N/A) PROCESS INSPECTION DISPOSITION

DIMENSIONS AND ANGLES APPLY AFTER PLATING. DIMENSIONS APPLY BEFORE PAINTING UNLESS OTHERWISE SPECIFIED.

| ATMOSPHERIC PRESS. (MM) | | |