



NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED DIMENSIONS ARE TO FACE OF VIEW SHOWN AND ARE AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION USE. (SEE MATH MODEL FOR PRECISION DIMENSIONS). FOR OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. FLUG ANGLE IS WIND BOTTOM SURFACE ROTATED COUNTERCLOCKWISE AGAINST THE BOX BOTTOM SURFACE.
3. MAXIMUM INSULATION CRIMP WIDTH OF 4.4mm AND HEIGHT 4.4mm FOR CABLE SIZE UP TO 3.0mm O.D.; MAXIMUM CORE CRIMP WIDTH OF 4.2mm
4. PLATING TYPE

SS	PLATING TYPE (SEE NOTE 4)	PLAT (SEE
Production Number		
33214501		
DATE AUG	SINCE 1021	FROM SET 2 OF 11
		SHEET NO. OF 3 R

ITEM	1					2					ITEM	QTY	UOM
	QTY	UNIT	REV	DATE	DESC	QTY	UNIT	REV	DATE	DESC			
3321442	R	81	-	-	ALL PARTS - OPERATED PART DRAWING	432175	206	05	01	432175	206	05	01
3321442	R	82	-	-	332144402 - UPDATED PART NAME, REV. L1	4321818	408	05	01	4321818	408	05	01
3321442	R	83	-	-	332144514 & 33214460 - UPDATED PART NAME, REV. L1	432271	408	05	01	432271	408	05	01

[illegible]