SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL (□) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	18
	LAST NO. USED	17

MISSING SYMBOLS
16

DWG STATUS DATE	STS	REV	N/P	DIR	ZONE	REVISION HISTORY	AUTH	DR	APVD/APVD 1	2
09JN03	R	31	-	-	-	ALL PARTS - RELEASED	241567	AMD	AMD	RF
24OCT03	R	32	-	-	-	ADDED P/N 15326426, 15326427, & 15326427 TO CHART, OBSOLETED FOR P/N 15473367, 15471368, & 15473369. UPDATED BLANK VIEW	246088	AMD	AMD	RF
30MAR04	R	33	-	-	-	15326426 - UPDATED PDM ATTRIBUTES	253827	MJM	MJM	LN
16AUG04	R	34	-	-	-	ADDED TERMINAL I.D. NOTE; REMOVED "PXX" FROM GRAPHICS	258116	TSH	TSH	RF
11APR05	R	35	-	-	-	ALL ACTIVE PARTS - ADDED CABLE ID COLUMN TO CHART, ADDED NOTE #4	265764	DAD	DAD	RAF
16MAY05	R	36	-	-	-	ALL ACTIVE PARTS - ADDED 2 COLUMNS TO CHART AND REVISED MATING COMPONENTS NOTE: 15326426 - TYP CABLE SEAL WAS 12159226; 15326427 - TYP CABLE SEAL WAS 12162227; 15326428 - TYP CABLE SEAL WAS 12162229	268254	RH	RH	LN
21MAY06	R	37	-	-	-	15326428 - UPDATED PDM ATTRIBUTES	278780	JBD	AJG	EJH
30MAY06	R	38	-	-	-	ALL ACTIVE PARTS-UPDATED PDM ATTRIBUTES	281035	TLD	TLD	MJC
07AUG07	R	39	-	-	-	ALL PARTS - MATT'L SIZE COLUMN REMOVED FROM CHART. 13666125 - RELEASED	402847	EAJ	JAM	JAY
03DEC07	R	40	-	-	-	13666125 - MATERIAL SPEC WAS W3666CH7	403315	RH	RH	RWK
07DEC08	R	41	-	-	-	13722266 - WAS ON SHT "1"	406319	AGP	FXV	EJB
26DEC08	R	42	-	-	-	13722264 & 13722266 - UPDATED MAT'L SPEC	406468	VRP	FXV	EJB
06MAR09	R	43	-	-	-	ALL ACTIVE PARTS - UPDATED MAT'L CALL OUT	414685	PHS	JAP	PHS
25FEB09	R	44	-	-	-	13722264 & 13722266 - WERE TYPE 501 AND REVISED TERMINAL FRONT BOX LABEL	407450	EFS	FXV	GER
17NOV09	R	45	-	-	-	13794882 AND 13794883 - RELEASED	419486	JAP	JAP	GER
25FEB10	R	46	-	-	-	13794882 & 13794883 - UPDATED MAT'L CALL OUT	410882	MAL	WAL	PSO
19APR10	R	47	-	-	-	ALL ACTIVE PARTS - UPDATED PDM ATTRIBUTES	410249	THE	PTE	AKP
24APR10	R	48	-	-	-	ALL ACTIVE PARTS - ADDED TYP CABLE SEAL & TYP SEALING CAVITY TO CHART AND 13666125 - UPDATED MAT'L CALL OUT	410431	MRS	MRS	AKP
16AUG10	R	49	-	-	-	ALL ACTIVE PARTS - UPDATED MAT'L DESC, ADDED "CONTACT TYPE" COLUMN, "CRIMP TYPE" COLUMN & "PLATING TYPE" NOTE	411627	MRS	MRS	AKP
24AUG10	R	50	-	-	-	ALL ACTIVE PARTS - UPDATED PDM ATTRIBUTES	411755	MRS	MRS	AKP
30SEP10	R	51	-	-	-	ALL ACTIVE PARTS - UPDATED PLATING NOTE	412114	KJP	JAM	AKP
23MAY11	R	52	-	-	-	ALL ACTIVE PARTS - ADDED "MAT'L SIZE" COLUMNS	414345	JAP	JAP	AKP
15OCT14	R	53	-	-	-	13722264, 13722266 & 13794882-01 - REVISED NOTE 7 ABOUT "TARNISH INFO" IN PLATING TYPE NOTE	427927	ABH	JAM	JSH
16JUN15	R	54	-	-	-	15471370, 15326426-2B - ADDED CONTACT PLATING STAMP	429886	ABH	JAM	LES
05MAY16	R	55	-	-	-	13666125, 15471370, 15326426-2B - REMOVED BARE COPPER NOTE	432987	LES	AKP	AKP
10MAY16	R	56	-	-	-	15471370, 15326426-2B - UPDATED PLATING STAMP NOTE	433053	LES	AKP	AKP





TWO RIB SEAL POSITION
AND TERMINAL/CABLE ALIGNMENT
SCALE 5:1



THREE RIB SEAL POSITION
SCALE 5:1



NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. MATING TERMINAL MUST HAVE A PRECIOUS METAL (GOLD OR SILVER) CONTACT INTERFACE.

3. * DENOTES DIMENSIONS MADE AT CUT-OFF AND CRIMP DIE.

4. DO NOT PROBE, TEST OR OTHERWISE CONTACT THE INTERIOR REGION (THE SPRING OR ANY MOVING PART) OF THIS TERMINAL. SEVERE DAMAGE CAN OCCUR, COMPROMISING THE PERFORMANCE OF THE ELECTRICAL INTERFACE.

5. PLATING TYPE:

   I. MATE TIN ELECTROPLATE 1.9 - 7.0 MICROMETERS THICK WITH A NICKEL UNDERPLATE 0.13 - 0.25 MICROMETERS THICK.

   II. REFLOW TIN 1.9 - 3.3 MICROMETER THICK WITH A COPPER UNDERPLATE 0.5 MICROMETER TO 1.0 MICROMETER THICK.

   III. MATE TIN ELECTROPLATE 1.9 - 7.0 MICROMETERS THICK.

   IV. 1.27 MICROMETERS DIFFUSED GOLD PALLADIUM/SILVER ALLOY INLAY OVER 1.27 MICROMETERS THICK NICKEL UNDERLAY.

   V. SILVER 3.5 - 6.0 MICROMETERS THICK OVER 0.13 - 0.25 MICROMETERS THICK NICKEL UNDERPLATE.

   FOR TERMINALS PACKAGED & STORED IN THE APPROVED MANNER, TARNISH ON SILVER PLATED SURFACES WILL NOT AFFECT THE PERFORMANCE OF THE PART.

   PLATING TYPE INFORMATION SHOWN ABOVE IS REFERENCE ONLY. PLATING REQUIREMENTS ARE CONTAINED IN APPLICABLE MATERIAL SPECIFICATION.

PART NO	REV	N/P	PREFERRED MAT'L SIZE	ALTERNATIVE MAT'L SIZE	MAT'L DESCRIPTION	SIZE (MM²)	TYPICAL CABLE AWG	ID	DIA	TYPE	B_{plate}	APPLICATION	TYPICAL CABLE SEAL OR EQUIVALENT	TYPICAL SEALING CAVITY CONFIG.	CONTACT AREA PLATING TYPE (SEE NOTE 5)	CRIMP AREA PLATING TYPE (SEE NOTE 5)
13794883	01	AH	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.75 - 0.8	18	18	2.02 - 1.7	502	2.65	SEALED (MINI)	15305351	3.2 X 4 OVAL	V	I
13794882	01	AH	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.25 - 0.5	20 OR 22	21	1.85 - 1.2	502	2.1	SEALED (MINI)	15366022	3.2 X 4 OVAL	V	I
13722266	01	AK	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.35 - 0.5	20 OR 22	21	1.85 - 1.2	502	2.1	SEALED (GT)	15366021	Ø4 ROUND	V	I
13722264	01	AK	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.75 - 1	16 OR 18	17	2.25 - 1.7	502	2.65	SEALED (GT)	15366060	Ø4 ROUND	V	I
13666125	01	AJ	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.75 - 0.8	18	18	2.02 - 1.7	501	2.65	SEALED (MINI)	15305351	3.2 X 4 OVAL	II	II
15326428	05	AB	0.3 X 26.7	0.3 X 27.38	GOLD PLATED BERYLLIUM COPPER ALLOY	0.25 - 0.5	20 OR 22	21	1.85 - 1.2	501	2.1	SEALED (MINI)	15366022	3.2 X 4 OVAL	IV	III
15326427	05	AB	0.3 X 26.7	0.3 X 27.38	GOLD PLATED BERYLLIUM COPPER ALLOY	0.75 - 1	16 OR 18	17	2.25 - 1.7	501	2.65	SEALED (GT)	15366060	Ø4 ROUND	IV	III
15326426	05	AB	0.3 X 26.7	0.3 X 27.38	GOLD PLATED BERYLLIUM COPPER ALLOY	0.35 - 0.5	20 OR 22	21	1.85 - 1.2	501	2.1	SEALED (GT)	15366021	Ø4 ROUND	IV	III
15471369	01	-	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.75 - 1	16 OR 18	17	2.25	1.7	501	2.65	SEALED (GT)	12191227	Ø4 ROUND	-
15472369	01	-	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.35 - 0.5	20 OR 22	21	1.85 - 1.2	501	2.1	SEALED (GT)	12191226	Ø4 ROUND	-	-
15471370	03	AB	0.3 X 26.7	0.3 X 27.38	GOLD PLATED BERYLLIUM COPPER ALLOY	0.75 - 0.8	18	18	2.02 - 1.7	501	2.65	SEALED (MINI)	15305351	3.2 X 4 OVAL	IV	III
15471369	01	-	0.3 X 26.7	0.3 X 27.38	BERYLLIUM COPPER ALLOY	0.35 - 0.5	20 OR 22	21	1.85 - 1.2	501	2.1	SEALED (MINI)	12191229	3.2 X 4 OVAL	-	-

THE DRAWN TERMINAL FORM SHOWN AND CUTOUT MAY PHYSICAL PARTS ARE NOT AVAILABLE FOR ORDERING.

PART NUMBERS THAT OR NOT HAVE A LINE PRESENT INDICATE THAT PHYSICAL PARTS ARE AVAILABLE FOR ORDERING.

CONTACT DELPHI SALES TO VERIFY AVAILABILITY OF PARTS.

PART DRAWING

DRAWING TYPE: STYLE

RELEASE DATE: DESIGN OWN:

UNLESS OTHERWISE SPECIFIED

THIS DRAWING IS TO BE INTERPRETED WITH ASME Y14.5M-1994 AND ASME Y14.5.1M-1994 GEOMETRIC DIMENSIONING AND TOLERANCING PRINCIPLES AT MAXIMUM MATERIAL CONDITION (MMC) UNLESS OTHERWISE SPECIFIED. FEATURES SIZE BY THREE DIMENSIONAL MEASUREMENTS OF SURFACE REFERENCES.

ALL DIMENSIONS ARE IN MILLIMETERS

(12) PROCESS SENSITIVE DIMENSION

DIMENSIONS ENCLOSED IN ( ) INDICATE REFERENCE DIMENSIONS AND ARE NOT TOLERANCED UNLESS OTHERWISE SPECIFIED.

DIMENSIONAL RANGE (MM)	CHART C
FROM: 0	>12
TO: 12	

TOLERANCE VALUES OTHERWISE SPECIFIED ON DRAWING: ±0.2

ANGULAR TOLERANCE ±2°

THIRD ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE

COPYRIGHT 2016 DELPHI AUTOMOTIVE SYSTEMS LLC
ALL RIGHTS RESERVED.
PRINTED IN U.S.A.
THIS DRAWING IS THE PROPRIETARY PROPERTY OF DELPHI AUTOMOTIVE SYSTEMS LLC AND IS NOT TO BE REPRODUCED OR USED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF DELPHI AUTOMOTIVE SYSTEMS LLC. ANY REPRODUCTION OF ANY KIND WITHOUT SUCH CONSENT IS PROHIBITED.

DR	DATE
APVD1 ANDRES MENDEZ	09JN03
APVD2 ANDRES MENDEZ	09JN03
APVD3 RICK FETCENKO	10JN03
APVD4	
APVD5	

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI SPEC(S):

MATERIAL: SEE CHART.

DRAWING NAME: TAXI TERM F GT 150

DRAWING NUMBER: 12191815

SIZE	SCALE	TRANS NO	SHEET NO	STS	REV	N/P
A0	10:1	1 OF 1	5 OF	R	26	-