

TYPE 102
USCAR TYPE B
SAME AS TYPE 101
EXCEPT AS SHOWN



TYPE 103
USCAR TYPE C
SAME AS TYPE 101
EXCEPT AS SHOWN







TYPE 104
USCAR TYPE D
SAME AS TYPE 101
EXCEPT AS SHOWN



TYPE 105
USCAR TYPE E
SAME AS TYPE 101
EXCEPT AS SHOWN



TYPE 101
USCAR TYPE A





TYPE 106
USCAR TYPE F
SAME AS TYPE 101
EXCEPT AS SHOWN

SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE TRDITIONAL COMPONENT DRWTNG.	TOTAL NO OF INSPECTIONS REQUIRED: 79	NO MISSING SYMBOL NUMBER
	LOC NO. 1625: 24	

ENG STATUS				REVISION HISTORY	DATE	BY	APVD
RLM06	B	01	-	-	28SEP95	BH	RH
RTM06	B	02	-	-	28SEP95	BH	RH
RPD01	B	03	-	-	10FEB97	MT	MT
RMK01	B	04	-	-	11JUN97	MW	MW

REVISION HISTORY	DATE	BY	APVD
- (RW09) W/S REVISION. - (RW09) W/S REVISION. (RW11) AND REVISING (RW12) AND REVISING ALL PARTS. - (RW13) AND REVISING ALL PARTS. - (RW14) MODELS	28SEP95	BH	RH
ALL PARTS. - REVISED CHAMFER. (RLE MD NOTHING) ADD TEXTURE	28SEP95	BH	RH
ADDED NOTES 12, 13 AND 14	10FEB97	MT	MT
- (RW23) - GENERIC MATL CALLOUT	11JUN97	MW	MW

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND
   TO BE MEASURED AT THE CENTER OF PART
   USE MATH MODEL FOR PRECISE DIMENSIONS FOR ALL
   OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL
   BUILD. SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. MATERIAL RECYCLING CODE PER ISO 11469, (11)X(12,13) RAISED CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE. OPTIONAL CONSTRUCTION TO BE NO MATERIAL RECYCLING CODE.

3. CONNECTOR VALIDATED PER SAE/USCAR-2 MAY 2004! TEMPERATURE CLASS 1, VIBRATION FOR COMPONENTS NOT COUPLED TO ENGINE.

4. (11)X(12,13) DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE. OPTIONAL CONSTRUCTION TO BE NO BRAND. OPTIONAL CONSTRUCTION FOR EXISTING TOOLING MAY BE "PRE1".

5. MATING BLADE REQUIREMENTS ARE FOUND ON USCAR/EWCAP DRAWING: #(EWCAP-001 REV C SECTION "CBA-TOOL"

6. PART TO BE USED WITH APPROPRIATE DELPHI PACKARD HOLDER DESIGN.

7. PART TO BE PROCESSED USING DELPHI-PACKARD ELECTRIC SYSTEMS AND APPLICABLE CONNECTOR ASSEMBLY INSTRUCTIONS AND APPLICABLE CRIMPING PROCEDURES.

8. PRIMARY LOCK DISENGAGE MAY BE BELOW 10N.

9. CONNECTOR TO CONNECTOR UNMATING FORCE MAY EXCEED 70N IF IT DR WIRE CIRCUITS ARE USED.

10. POLARIZATION FEATURE EFFECTIVENESS MAY BE BELOW 200N. WHEN MATING TO A DIFFERENT USCAR 20 WAY INSRT.

11. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

12. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR THICKNESS CHANGES INCLUDING, BUT NOT LIMITED TO, FLOW MARKS, COLOR SHADING, GLOSS VARIATIONS, AND SURFACE TEXTURE MAY NOT AFFECT FIT, FORM, OR FUNCTION OF THE PART AND ARE ACCEPTABLE PER GMW# 4.7-CS-01.

PART NO	REV	V/P	STATUS	MATERIAL SPECIFICATION AND COLOR	TYPE	USCAR TYPE	VOLUME CAV	MATING CONNECTOR OR EQUIVALENT
13592212	02	AA		POLYESTER COMPOUND NATURAL	101	F	1.745	
13592210	04	AA		POLYESTER COMPOUND BLUE	101	C	1.745	
13592401	04	AA		POLYESTER COMPOUND GRAY	101	D	1.745	
13592731	02	AA		POLYESTER COMPOUND BROWN	103	C	1.745	
13592804	02	AA		POLYESTER COMPOUND GRAY	102	B	1.745	
13592209	02	AA		POLYESTER COMPOUND BLACK	101	A	1.745	12405164

PART DRAWING

PART NO. 13592212

TAB SIZE 2.8 X 0.8 MM

TYCO MINI-FIT JUNIOR

DELPHI

MINI-FIT JUNIOR 6UCTRUS/6UCTRWS HEADERS

PART NUMBER (SURF): 13-2506
PART NUMBER (DUAL): 13-2506
MATE RETENTION: 13-2506

DRAWING NUMBER: 13592212

TAB SIZE 2.8 X 0.8 MM

I 32SSIS