




TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN







NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF WIRE SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION TOOL MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. RECOMMENDED MATING BLADE WIDTH 2.8 ±0.08 THICKNESS 0.635 ±0.05
3. "***" DENOTES DIMENSION IS MADE AT CUT OFF AND CRIMP DIE
4. VISIBLE CRACKS ARE NOT PERMISSIBLE
5. "PXX" INDICATES "P" PLUS LAST TWO DIGITS OF WAKE DIE SERIES NUMBER (P01, P02, P03, ETC).
6. DO NOT PROBE. TEST OF CRIMP/SE CONTACT THE INTERIOR WIDTH (THE CONTACT AREA) OF THE WIRE BARREL CRIMP SHALL BE UNDISTURBED CAN OCCUR, COMPROMISING THE PERFORMANCE OF THE ELECTRICAL INTERFACE.

SYMBOL DEFINITION		MISSING NUMBERS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL DOES NOT REQUIRE INSPECTION. TOLERANCES MAY BE SHOWN ON AN INDIVIDUAL COMPONENT DRAWING.	TYP. NO. SYMBOLS ON DRAWING: 6 LAST NO. USED: 8	

ECR/ECO	DIV	SECTION	ITEM	REVISION HISTORY	AUTH	DR APPROVED
0549191	R	05	-	-	ALL PARTS - ADDED SEPARATE DWG	9900289	JJH	9900289
0549191	R	02	-	-	SHT. 1 OF 2 ADDED	9900289	JJH	9900289
0576001	R	03	-	-	12129424 & 25 - UPDATED PCM ATTRIBUTES	2135940	MPL	MPL
0549191	R	04	-	-	ALL ACTIVE PARTS - REVISED DRAWINGS	2139706	JJH	JJH
1190261	R	05	-	-	ALL ACTIVE PARTS - ADDED TERMINAL ID NOTE	2661188	BPS	JJH
0580285	R	06	-	-	12129429, 12129430 & 12129431 - MATERIAL AND FINISHES 1190188 RELEASED	2778985	CJP	LJF
2969285	R	07	-	-	12129426, 12129428 & 12129431 - CREATED NISSAN CUSTOMER PART DRAWING	2667491	JTI	KAT
1769186	R	08	-	-	12129428 - REINSTATED	2778610	PCP	PCP
1850186	R	09	-	-	ALL ACTIVE PARTS - METAL SPEC WAS 4515 ALSTAMP	2969471	MAT	MPL
0769197	T	10	-	-	12129429 AND 12129430 MATERIAL SPEC 4515 ALSTAMP	4515787	MM	MPL

PART NO	REV/N/P	STATUS	PART NO	REV/N/P	STATUS	MAT'L SIZE	MAT'L SPEC	SIZE (AWG)	DIA	(IDT) TYPE
UNPLATED STRIP FORM		LOOSE PIECE								
PLATED STRIP FORM		LOOSE PIECE								
CABLE										

				0.406 X 32.54	12129429	03	AC		MDM-DDDET-DTM10 1/2 HD	1-2	2.48-3.97 (15-102)	3.74G.4	6490.4
				0.406 X 32.54	12129430	03	AC		MDM-DDDET-DTM20 1/2 HD	1-2	2.48-3.97 (15-102)	3.74G.4	7.6360.4
				0.406 X 32.54	12129431	03	AC		MDM-DDDET-DTM40 1/2 HD	1-2	2.48-3.97 (15-102)	3.74G.4	7.6360.4
				0.406 X 32.54	12129425	04	AC	1.543188	01 AA	MX574DDT CAPPED EX HD	1-2	2.48-3.94 (15-102)	3.74G.4	6490.4
				0.406 X 32.54	12129426	03	AC			MX574DDT CAPPED EX HD	1-2	2.48-3.97 (15-102)	3.74G.4	6490.4
				0.406 X 32.54	12129427	02	AC			MX574DDT CAPPED EX HD	1-2	2.48-3.97 (15-102)	3.74G.4	6490.4
			INACTIVE	0.406 X 32.54	12129422	02				AS15822-4G TIN BRS EX HD GR ALTV	0.5-0.96	2.07-3.16 (19-10)	2.26G.4	3926.4
				0.406 X 32.54	12129423	04				MX574DDT CAPPED EX HD	0.75-0.5	1.84-2.51 (21-16)	2.44G.2	5.840.2
				0.406 X 32.54	12129420	04								

| | | | | | | | | | | |