

E	OPEN	OPEN	OPEN	OPEN
D	OPEN	CLOSED	CLOSED	OPEN
C	CLOSED	OPEN	OPEN	CLOSED
B	CLOSED	CLOSED	OPEN	OPEN
A	OPEN	OPEN	CLOSED	CLOSED
KEY DESIGN	1	2	3	4

KEY LOCATION

54 POCKET - RIGHT HAND LEVER

KEYING CONFIGUATION



THROUGH HOLE



MOUNTING SPACE



PLR CLOSED POSITION



PLR PRE-LOCKED POSITION









SECTION A-A

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (TREE MATHEMATICAL DATA). DIMENSIONED TO BE USED WITH TOLERANCES OF TOOL BUILD. SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.
3. REFERENCE DRESS COVER ASM PN: 13934566
4. CONNECTOR CAVITY ACCEPT BELOW TERMINAL OR EQUIVALENT.

0-1452908-1	TYCO	0.64 SQ TIMF	SELVEB	1.2-1.0MM
0-1452908-4	TYCO	0.7TIMF	SILVER	1.7-1.0MM
PART NO	SUPPLIER	CABLE SIZE	PLATING	CABLE O.D.

5. CABLE SEAL PLUG P/N J5310164
6. MATING INTERFACE INFORMATION: DELPHI PN: 13862951 BM PN: 13589822
7. 0.75MM2 IN 2 CIRCUITS MAXIMUM WITH WIRE INSULATION OUTER DIAMETER 1.77 TO 1.79 MM
8. KEY "E" CONFIGURATION FOR SERVICE ONLY
9. HARNESS APPLICATION SEE CONNECTOR MANUAL 13951030-CUS72-501

27	28	29	30	31	X	33	34	35	X	X	X
X	X	X	X	X	X	X	X	X	X	X	X

13287593 OPEN CAVITY AVAILABLE, X PLUGGING HOLE

PART NO	DIRECTION	CODE	HOUSING	LEVER	PLR	CONN SEAL	BLOCK SEAL	SEAL RETAINER	OPEN CAVITY PATTERN
13287593	RIGHT HAND	B	13951870	13938310	13938314	13938311	13938312	13938313	ALL
13955865	RIGHT HAND	E	13951877	13938310	13938314	13938311	13938312	13938313	ALL
13955416	RIGHT HAND	D	13950876	13938310	13938314	13938311	13938312	13938313	ALL
13955415	RIGHT HAND	B	13950870	13938310	13938314	13938311	13938312	13938313	ALL
13938307	RIGHT HAND	A	13938309	13938310	13938314	13938311	13938312	13938313	ALL

| REVISIONS | | | | | | | | | | |