

SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE TRDITIONAL COMPONENT DRWTNG.	TOTAL NO OF INSPECTIONS REQUIRED: 69	NO MISSING SYMBOL NUMBER
	LSEC NO. 1625: 24	

ENG STATUS					REVISION HISTORY	DATE	BY	APVD
1349061	B	01	-	-	ALL PARTS - CHANGED PKG RELEASING AGENCY AND ULTEMA TRADENAME PER ECR/ECO: 4086-96 ALL PARTS - MOLDING CHAMFER (PLC AND MOTHER) ADDED	27SEP96	RDPOPP	RJL
1374004	B	02	-	-	ALL PARTS - MOLDING CHAMFER (PLC AND MOTHER) ADDED TITANIUM	03DEC96	RH	RJL
1387007	B	03	-	-	ADDED NOTES 12 AND 13	16FEB97	RMT	RMT
2106011	B	04	-	-	ALL PARTS - ADDED APPLICATION DATA NOTE, UPDATED LOCK & HOUSING DRAWING CALLOUTS, CHANGED TYP COMPONENTS - MATERIAL CALLOUT & MOTHER TERM. CR. SHEET NO INCLUDED MATL CHANGE, PLATING NOTE	16DEC97	STEVEV	JRS
1430008	B	05	-	-	CHANGE - UPDATED MATL CALLOUT	19JUL99	LWD	LWD
1534404	B	06	-	-	ALL PARTS - GLOBAL POLARIZATION FEATURE EFFECTIVENESS NOTE	19DEC01	SWD	RWD

PART NO	REV	A/P	STATUS	MATERIAL SPECIFICATION AND COLOR	TYPE	USCAR TYPE	VOLUME
15486791	02	AC	-	PBT GLASS REINFORCED NATURAL	101	F	3,921
15486792	02	AC	-	POLYESTER COMPOUND BLUE	101	A	3,921
15486793	02	AC	-	POLYESTER COMPOUND GREEN	104	D	3,921
15486794	02	AC	-	POLYESTER COMPOUND BROWN	103	C	3,921
15486795	02	AC	-	POLYESTER COMPOUND GRAY	102	B	3,921
15486702	02	AC	-	POLYESTER COMPOUND BLACK	101	A	3,921

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATIC INSPECTION BOUNDARY DOES NOT CONSTITUTE INSPECTION. ANGULAR DIMENSIONS ARE 0 OR 90 DEGREES. CORNER RADII AND CHAMFERS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. MATERIAL RECYCLING CODE PER ISO 11469,)(XX)(-)(RAISED CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE.
3. CONNECTOR VALIDATED PER SAE/USCAR-2 MAY 2006+ TEMPERATURE CLASS 1, VIBRATION FOR COMPONENTS NOT COUPLED TO ENGINE. - 5, X.Z CONNECTOR-CONNECTOR MATING FORCE: 75N MAX.
4.)(XX)(-)(RAISED DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE, FREE OF MOLD LISTING AT FINAL ASSEMBLY. OPTIONAL CONSTRUCTION TO BE "PED" OR NO LOGO.
5. MATING BLADE REQUIREMENTS ARE FOUND ON USCAR/EWCAP DRAWING: #EWCAP-001 REV C SECTION "06-TOOLS".
6. PART TO BE USED WITH APPROPRIATE DELPHI PACKARD HOLDER DESIGN.
7. PART TO BE PROCESSED USING DELPHI PACKARD ELECTRIC SYSTEMS BEST PRACTICE METHODS AND/OR CONNECTOR ASSEMBLY INSTRUCTIONS AND APPLICABLE MANUFACTURING PROCEDURES.
8. PRIMARY LOCK DISENGAGE MAY BE BELOW 10N.
9. POLARIZATION FEATURE EFFECTIVENESS MAY BE BELOW 220N. WHEN MATING TO A DIFFERENT USCAR 16 WAY INDEX.
10. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR IMPERFECTIONS INCLUDING, BUT NOT LIMITED TO, FLOW MARKS, COLOR VARIATION, SHRINKAGE, AND EJECTOR PIN MARKS ARE ACCEPTABLE AS LONG AS THEY DO NOT AFFECTION OF THE PART ARE POSSIBLE (REF DRWG. 15-05-01.
11. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.
12. POLARIZATION FEATURE EFFECTIVENESS TO A 2ND INDEX IS 100N MINIMUM WHEN MATING TO A DIFFERENT USCAR 16 WAY INDEX.

DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC PRODUCTS

DRAWN	PHIL E. PHILLIPPS	12NOV96
CHECKED	PHIL E. PHILLIPPS	12NOV96
APPV MANUAL LITTLE		12NOV96

PART DRAWING

TAB SAVER

TAB SAVER

TAB SAVER 16 F MICRO MIT

15486791

SIZE A(+3) | SHT 1 OF 2 | REV 06

THIRD ANGLE PROJECTION

SCALE 4/1

DO NOT SCALE DRAWING

THIS DRAWING AND THE INFORMATION CONTAINED HEREIN IS THE EXCLUSIVE PROPERTY OF DELPHI PACKARD ELECTRIC SYSTEMS AND IS NOT TO BE REPRODUCED OR COPIED IN WHOLE OR IN PART WITHOUT THE WRITTEN PERMISSION OF DELPHI PACKARD ELECTRIC SYSTEMS.

15486791