APEX[®] 2.8 SensoMate[™]



APEX® 2.8 SensoMate™ 4W Female

BENEFITS

- Heavy-duty performance
- Highest current rating
- · Ergonomic design

FEATURES

- Compliant with USCAR design guidelines and performance standards
- Industry standard footprint
- Superior single-piece housing construction
- Primary Lock Reinforcement (PLR) to detect partially installed terminals

AVAILABLE CONFIGURATIONS


Cavity Count (ways)	2, 3, 4
Cavity Configurations (mm)	2.8
Genders	Female
Sealing Type	Cable Sealed
Centerline Spacing (mm)	5.0



APPLICATIONS

On-engine sensors

See back page for representative part numbers and packaging dimensions.







About Aptiv

Aptiv is a global technology company that develops safer, greener and more connected solutions enabling a more sustainable future of mobility.

Visit aptiv.com



Cavity count	Blade size (mm)	Gender	Dimensions W x H x D (mm)	Part number	Index	Color	Other indexes offered
2	2.8	F	21.6 x 21.2 x 31.0	13821046	А	Black	В
3	2.8	F	26.6 x 21.2 x 31.0	13791661	А	Black	В
4	2.8	F	31.6 x 23.2 x 31.0	33513154	А	Black	В


Please, contact an Aptiv representative for the full part number list.

COMPATIBLE SEALS

Туре	Applicable Wire Size (mm²)	Color	Restraint Ring	Part Number
Cable Seal	0.35 - 1.0	Pink	Yes	35296484
Cable Seal	1.0 - 2.0	Black	Yes	15518641
Cable Seal	2.5 - 4.0	Brown	Yes	15458498
Cavity Plug	N/A	Blue	Yes	35478080
Cavity Plug	N/A	White	No	15305170


DIMENSION MEASUREMENT SAMPLE





APEX® 2.8 SensoMate™ 2W Female pre-assemly

APEX® 2.8 SensoMate™ 2W Female assemly



APEX® 2.8 SensoMate™ 2W Female

COMPATIBLE WITH



Part numbers, specifications, dimensions and performance data in this document are for general references only and are subject to change without notice. To verify product information, please contact an Aptiv representative.



