

MATERIAL SPECIFICATIONS

RECOMMENDED

BASE METAL - CDA-210, EXTRA SPRING TEMPER

- TIN PLATING (WHERE APPLICABLE TO 125°C MAX CONTINUOUS USAGE): 0.0005MM-0.0025 MM (20-100 µIN) ELECTROPLATED TIN.
- USAGE OF PLATING TYPES OTHER THAN RECOMMENDED MUST BE APPROVED BY DELPHI PACKARD ELECTRIC SYSTEMS ENGINEERING.

MINIMUMS

ELECTRICAL CONDUCTIVITY - ≥28% IACS AT 20 °C. USE OF A MATERIAL WITH CONDUCTIVITY <28% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 430 - 480 MPa

UNDERPLATING FOR TIN PLATING - FOR BASE MATERIALS CONTAINING 10% OR MORE ZINC, AN UNDERPLATE OF COPPER 0.0025 MM (100 µIN) MINIMUM THICK IS REQUIRED.

PROCESSING LUBRICANT - ANY PROCESSING LUBRICANT REMAINING ON TERMINALS MUST NOT VARNISH OR DEGRADE THE ELECTRICAL PERFORMANCE OF THE CONNECTION UP TO A MAXIMUM TEMPERATURE OF 150° C). PROCESSING LUBRICANTS MUST BE APPROVED BY DELPHI PACKARD ELECTRIC SYSTEMS ENGINEERING.

MATING BLADE INFORMATION





NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
   ALL RADII 0.4
   DRAFT IS 1° ON ALL OUTSIDE SURFACES
2. TERMINAL MUST WHITSTAND A MINIMUM PUSHOUT FORCE OF 67 NEWTONS.
3. WHEN USING THIS INFORMATION FOR A NEW DESIGN, REQUEST THE LATEST COPY OF THIS PRINT FORM PACKARD ELECTRIC DITC(SIS)

RECOMMENDED MATERIAL —— GLASS REINFORCED NYLON OR POLYESTER.

MATING CONNECTOR INFORMATION



STACK ANALYSIS VIEW





OPTIONAL CONSTRUCTION



NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:
   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. MATERIAL RECYCLING CODE PER ISO 11469, (>)1X(<)1) CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE.
3. (>)1X(<)1) DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE (INTERNALLY VISIBLE AT FINAL ASSEMBLY). OPTIONAL CONSTRUCTION TO BE "PCB" OR NO LOGO.
4. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM. MINOR COSMETIC IMPERFECTIONS (INCLUDING, BUT NOT LIMITED TO, SCRATCHES, DENTS, PARTICLES OR INCLUSIONS) WHICH DO NOT AFFECT FORM, FIT, FUNCTION OR FUNCTION OF THE PART ARE PERMISSIBLE PER DPUM-4,T-CS-01.
5. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE TRADITIONAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 17	16
	LSEC NO. 1625: 16	

DELTA STATUS					REVISION HISTORY	DATE	BY	APVD
RELEASE	R	01	-	-	FEATURES - RELEASED	24JUN96	LTD	KTOOMEY
CHANGE	R	02	-	-	ALL PARTS - ADDED STACK ANALYSIS VIEW	25JUN96	KJM	JEMERSON
CHANGE	R	03	-	-	FEATURES - ADDED MATERIAL RECYCLING CODE AND SPLICE MATING BLADE INFORMATION	27SEP96	JPM	MA1000
CHANGE	R	04	-	-	FEATURES - ADDED MPA STATION DATA NOTE; REVISED PART NUMBER IN TITLE BLOCK; REVISED PART ADAPTER DATA AND REVISED MATL CALLOUT TO REMOVE CALLOUT	4DEC96	KDEWEY	JMS
STATUS	R	05	-	-	UPDATED MATING CONFIGURATION INFO	11JAN99	DMC	DMCOOK

PART NO	REV	N/M	STATUS	MATERIAL SPECIFICATION AND COLOR	TYPE	VOL CM3
15473845	01	AB		POLYAMIDE COMPOUND BLUE	101	0.865

| DRAWING NUMBER | | | | |