SYMBOL DEFINITION		MISSING SYMBOLS
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL ( ) DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED: 30	3-10
	LAST NO. USED: 18	

DWG STATUS DATE	STS	REV	N/P	CHG	ZONE	REVISION HISTORY	AUTH	DR	APVD I.E.	APVD
06SEP02	R	01	-	-		ALL PARTS - REDRAWN TO PD	224144	RCH	RCH	GG
06SEP02	R	02	-	-		ALL PARTS - ADDED NOTES (2 PLCS)	220031	RCH	RCH	GG
20JUN04	M	02	-	-		ALL PARTS - ADDED BASIC DIMS & MACH TOLERANCES	290436	STR	STR	MB
31MY05	R	04	-	-		12047813 - MAT'L SPEC WAS M46950J1	269583	GPS	JAA	MB



MOUNTING HOLE
(VIEWED FROM OUTSIDE OF CASE)





TYPE 101



TYPE 103



TYPE 102









SECTION A - A



NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED:

   DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION (SEE MATH MODEL FOR PRECISE DIMENSIONS). FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.

2. REFERENCE MATING COMPONENTS OR EQUIVALENT:

   CONNECTOR SEE CHART

3. THIS PART ACCEPTS THE FOLLOWING COMPONENTS OR EQUIVALENT:

   CAVITIES TO ACCEPT 12040902 TERMINAL.
   MAX INSULATION CRIMP MUST BE LESS THAN 2.65 HIGH AND 2.3 WIDE.
   MAX CABLE O.D. 2.4
   REFER TO ESA-60M FOR CRIMP DIMENSIONS.

4. BUTTON LOCKS MUST BE CLOSED (LOCKED) UPON COMPLETION OF HARNESS BUILD, SINCE THESE FUNCTION AS THE TPA FOR THE PARTS.

5. MATERIAL RECYCLING CODE PER ISO 11469. 11X10.21 CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE. OPTIONAL CONSTRUCTION TO BE NO MATERIAL RECYCLING CODE

6. 11X10.21 RAISED DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE, PREFERABLY VISIBLE AT FINAL ASSEMBLY. OPTIONAL CONSTRUCTION TO BE "PED" OR NO LOGO.

PART NO	REV	N/P	STATUS	MATERIAL SPECIFICATION AND COLOR	TYPE	MATING CONNECTOR	VOL CM³
12065671	A3	-	-	M46950O3 PBT-GRA	103	12065672	4.241
12047813	D4	-	-	M46950O1 PBT NAT	101	12066130	4.243
12040905	G3	-	-	M46950O2 PBT-REPELLENT,ZED-BLK	102	12064980	4.233

(13) PROCESS SENSITIVE DIMENSION

REFERENCE

DIMENSIONS ARE IN MILLIMETERS

DIMENSIONAL RANGE (MM)										
FROM	0.5	3.15	6.31	10	18	30	50	120	250	400
TO	3.15	6.3	10	18	30	50	120	250	400	630
ANGULAR TOLERANCE (DEG)										
	±0.75	±0.5	±0.25	±0.17	±0.12	±0.08	±0.06	±0.04	±0.03	±0.02

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS IN ACCORDANCE WITH ASME Y14.5M-1994
DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994
TOLERANCING PER ISO 1101. ALL DIMENSIONAL TOLERANCES AND GEOMETRIC CONTROLS APPLY AT 20°C. MEAS. PT. CONTACT POINT IS THE INTERSECTION OF THE TERMINAL AXIS AND THE CONTACT SURFACE. ALL DATUMS USED TO ORIENTATION OR LOCATION TOLERANCES SEPARATE POSITION TOLERANCES MAY BE CHAIRED INDIVIDUALLY. DIMENSIONS APPLY PRIOR TO PLATING.
ALL DIMENSIONS ARE IN MILLIMETERS

THIRD ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

NAME/TYPE	PART DRAWING
STYLE	
VOLUME (CUBIC)	SEE CHART
DELTA CODE	D

DELPHI
DELPHI PACKARD ELECTRIC SYSTEMS
WARREN, OH

	DATE
DR MFVD R. CHACON	06SEP02
MFVDE RL. CHACON	06SEP02
MFVDI G. CRANTES	06SEP02
MFVDA	
MFVDS	

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI 10PM1001

MATERIAL: SEE CHART

DRAWING NAME: TAX| CONN 9 M MIC/P 100

DRAWING NUMBER: 12048250

SIZE	SCALE	FRAME NO	SHEET NO	STS	REV	WT
A0	4:1	1 OF 1	1 OF 1	R	04	-