

MATERIAL SPECIFICATIONS

RECOMMENDED

BASE METAL - CDA-210, GILDING, EXTRA SPRING TEMPER

PLATING - 0.005±0.0025 MM THICK TIN

MINIMUMS

ELECTRICAL CONDUCTIVITY - ≥ 20% IACS AT 20°C. USE OF A MATERIAL WITH CONDUCTIVITY < 20% IACS MUST BE APPROVED BY PACKARD ELECTRIC MATERIALS ENGINEERING.

TENSILE STRENGTH - 407 MPa

PLATING - FOR LOW ENERGY (≤5v) AND NON-PASSENGER COMPARTMENT POWER CIRCUITS, 0.005±0.0025 MM THICK TIN. FOR MATERIALS CONTAINING 10% OR MORE ZINC, AND UNDERPLATE OF COPPER 0.005±0.0025 MM THICK IS REQUIRED

MATING BLADE INFORMATION

SCALE 8:1



TYPE 102
SAME AS TYPE 101
EXCEPT AS SHOWN

SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL [ ] DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	17
	LAST NO. USED	16

MISSING SYMBOLS
NO MISSING SYMBOL NUMBER

ENG STATUS					ZONE	REVISION HISTORY	AUTH	DR	AP/APVD 1	AP/APVD 2
DATE	STG	REV	N/P	ECN						
26JN03	R	01	-	-		ALL PARTS - RELEASED	242936	EGR	EGR	SM
30SE03	R	02	-	-		ALL PARTS - UPDATED PDM ATTRIBUTES	246108	EGR	EGR	BS
25AU04	-	03	-	-		ALL PARTS - ADDED STACK ANALYSIS VIEW	257899	AK	AK	BSD
05OCO7	R	04				ALL PARTS - REMOVED RECYCLING CODE	402554	MEC	MEC	BDB





SECTION B-B



SECTION A-A

NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA. ALL RADII 0.4
2. RECOMENDED MATERIAL GLASS REINFORCED NYLON OR POLYESTER.
3. WHEN USING THIS INFORMATION FOR A NEW DESIGN REQUEST THE LATEST COPY OF THIS PRINT FROM PACKARD ELECTRIC DIVISION.

MATING CONNECTOR INFORMATION



TERMINAL OVER TRAVEL 0.85 ± 0.65

SECTION C-C

STACK ANALYSIS VIEW





TYPE 101



NOTES

1. UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
2. MAXIMUM CABLE DIAMETER 2.72 MM.
3. WHEN PARTS ARE TO BE SHIPPED THEY MUST BE PACKED IN PLASTIC BAGS OR SHIPPING CONTAINERS MUST BE LINED WITH PLASTIC LINERS. BAGS OR LINERS MUST BE SEALED TO AVOID ENTRY OF FOREIGN MATTER.
4. 11.5X10.1 DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE, PREFERABLY VISIBLE AT FINAL ASSEMBLY. OPTIONAL CONSTRUCTION TO BE "NO LOGO".
5. THIS PRODUCT IS NOT CATEGORIZED AS AN APPEARANCE ITEM, MINOR IMPERFECTIONS INCLUDING, BUT NOT LIMITED TO, FLOW MARKS, COLOR BLEMISHES, GATE VESTIGE, AND SOFT FLASH THAT DO NOT AFFECT THE FIT, FORM, OR FUNCTION OF THE PART ARE PERMISSIBLE PER NAP 4.10-18.
6. FOR APPLICATION DATA SEE THE INDIVIDUAL APPLICATION DRAWINGS.

PART NO	REV	N/P	STATUS	TYPE	MATERIAL SPECIFICATION AND COLOR	VOL CM³
15467085	01	AC		101	POLYAMIDE COMPOUND GRAY	0.753
15466861	01	AC		102	POLYAMIDE COMPOUND GRAY	0.806

DRAWING TYPE	PART DRAWING
TITLE	
VOLUME (CM³)	SYSTEM UNIT
SEE CHART	D

UNLESS OTHERWISE SPECIFIED

ALL DIMENSIONS ARE IN MILLIMETERS

RETURNED

THIRD ANGLE PROJECTION

DO NOT SCALE

USE MATH DATA

DELPHI

DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE

	NAME	DATE
DR		
APVD1	E. GARCIA	26JN03
APVD2	E. GARCIA	26JN03
APVD3	G. MACIAS	26JN03
APVD4		
APVD5		

SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI (GM9501)

MATERIAL	SEE CHART
CREATED NAME	TAXI CONN F W/P 150.2
CREATED NUMBER	15473840
SIZE	A0
SCALE	5:1
SHEET NO	1 OF 1
SHEET NO	1 OF 1
STG	R
REV	04
N/P	-