1075-Nettoyant Ligne d'Eau

Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 1 of 13 Print date: 21/11/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:	Nettoyant Ligne d'Eau
Product Code:	1075
UFI:	6YN0-D0PT-W00P-7WC9

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Cleaner

Uses advised against: Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	FLUIDRA COMMERCIAL FRANCE
Address:	Avenue Maurice Bellonte,
City:	66 000 PERPIGNAN
Province:	FRANCE
Telephone:	Tel: 04 11 300 200
Fax:	+34 93 713 41 11
E-mail:	fds@inquide.com
Web:	www.ctxprofessional.com

1.4 Emergency telephone number: (Available 24 hours)

Anti poisoning centre: ITALY (Rome): 06/305 43 43 ITALY (Milan): 02/66 10 10 29 SPAIN: +34 91 562 04 20 FRANCE (Paris): 01 40 05 48 48 FRANCE (Tolousse): 05 61 77 74 47 FRANCE (Marseille): 04 91 75 25 25 PORTUGAL: 808 250 143 BELGIQUE (Brussel): (+32) 070 245 245 Sweden: 112 - Begär Giftinformation (ask for Poisons Information) Denmark (Giftlinjen): +45 8212 1212 Finland: 0800 147 111 Norway: +47 22 59 13 00 Cyprus: 1401 Greece: (0030) 2107793777 Netherlands (NVIC): +31 (0)88 755 8000 Romania: +4021 318 360 6 Biroul RSI Si Informare Toxicologica Apelabil de luni pâna vineri, între orele 8.00-15.00 CAV accreditati: Roma +39 06 68 59 3726; Foggia +39 800 18 34 59; Napoli +39 081 54 53 333; Roma +39 06 49 97 80 00; Roma +39 06 30 54 343; Firenze +39 055 79 47 819; Pavia +39 0382 24 444; Milano +39 02 66 10 10 29; Bergamo +39 800 88 33 00; Verona +39 800 01 18 58.

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008: Skin Corr. 1 : Causes severe skin burns and eye damage.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 2 of 13 Print date: 21/11/2024

Pictograms:



Signal Word: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

Precautionary statements:

 P101
 If medical advice is needed, have product container or label at hand.

 P102
 Keep out of reach of children.

 P280
 Wear protective gloves/protective clothing/eye protection.

 P301+P330+P331
 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

 P303+P361+P353
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

 P305+P351+P338
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 011-002- 00-6 CAS No: 1310-73-2 EC No: 215-185-5 Registration No: 01- 2119457892-27-XXXX	sodium hydroxide	2 - 4 %	Skin Corr. 1A, H314	Skin Corr. 1A, H314: $C \ge 5 \%$ Skin Corr. 1B, H314: 2 % $\le C$ < 5 % Skin Irrit. 2, H315: 0,5 % \le C < 2 % Eye Irrit. 2, H319: 0,5 % \le C < 2 %

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 3 of 13 Print date: 21/11/2024

CAS No: 126-92-1 EC No: 204-812-8 Registration No: 01- 2119971586-23-XXXX	sodium etasulfate	1 - 10 %	Eye Dam. 1, H318 - Skin Irrit. 2, H315	-
Index No: 603-014- 00-0 CAS No: 111-76-2 EC No: 203-905-0 Registration No: 01- 2119475108-36-XXXX	[1] 2-butoxyethanol	1 - 3 %	Acute Tox. 4, H312 - Acute Tox. 4, H302 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315	Oral: ETA = 1200 mg/kg pc (Armonizada ATP15)
CAS No: 127036-24-2	Poly(oxy-1,2-ethanediyl), .alphaundecyl- .omegahydroxy-, branched and linear	1 - 3 %	Acute Tox. 4, H302 - Eye Dam. 1, H318	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet. [1] Substance with a European Union exposure limit in the workplace (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eve contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

(in accordance with Regulation (EU) 2020/878)

1075-Nettoyant Ligne d'Eau



Version 1 Date of compilation: 20/01/2020 Version 3 (replaces version 2) Revision date: 08/03/2022 Page 4 of 13 Print date: 21/11/2024

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture. <u>Special risks.</u>

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

None in particular.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 5 of 13 Print date: 21/11/2024

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
		United	Eight hours		
		Kingdom [1]	Short term		2
		Éire [2]	Eight hours		
		Life [2]	Short term		2
		Italia [3]	Eight hours		
sodium hydroxide	1310-73-2		Short term		2
Sociality invalorial	1510-75-2	United States	Eight hours	(Ceiling) 2	
		[4] (Cal/OSHA)	Short term		
		United States	Eight hours		(Ceiling) 2
		[5] (NIOSH)	Short term		
		United States	Eight hours		2
		[6] (OSHA)	Short term		
		European	Eight hours	20 (skin)	98 (skin)
		Union [7]	Short term	50 (skin)	246 (skin)
		United	Eight hours	25	123
		Kingdom [1]	Short term	50	246
		Éire [2]	Eight hours	20	98
			Short term	50	246
2-butoxyethanol	111-76-2	Italia [3]	Eight hours	20	98
	111 /0 2		Short term	50	246
		United States	Eight hours	20	
		[4] (Cal/OSHA)	Short term		
		United States	Eight hours	5	
		[5] (NIOSH)	Short term		
		United States	Eight hours	50	240
[1] A /		[6] (OSHA)	Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. [2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[3] Secondo il Decreto Legislativo del Governo n.277, 15/08/1991, il Decreto Legislativo n.66 ed il Decreto Ministeriale 26/02/2004.

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health,

Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.

[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs),

California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[7] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
sodium hydroxide	DNEL	Inhalation, Chronic, Local effects	1 (mg/m ³)
CAS No: 1310-73-2	(Workers)		
EC No: 215-185-5	DNEL	Inhalation, Chronic, Local effects	1 (mg/m ³)
LC NO. 215-185-5	(Consumers)		
2-butoxyethanol	DNEL	Inhalation, Chronic, Systemic effects	98
CAS No: 111-76-2	(Workers)		(mg/m ³)
EC No: 203-905-0			

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 6 of 13 Print date: 21/11/2024

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum. CAS: 111-76-2

TLV TWA - 20 ppm, A3 - 96,66 mg/m3, A3 TLV STEL - A3 VLE 8h - 98 mg/m3 - 20 ppm VLE short - 246 mg/m3 - 50 ppm **8.2 Exposure controls.**

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %				
Uses:	Cleaner				
Breathing protect					
PPE: Characteristics:	Filter mask for protection against gases and particles. «CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.				
CEN standards:	EN 136, EN 140, EN 405				
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach				
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Filter Type needed:	A2				
Hand protection:					
PPE:	Non-disposable protective gloves against chemicals.				
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.				
CEN standards:	EN 374-1, EN 374-2, EN 374-3, EN 420				
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.				
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.				
Material:	PVC (polyvinyl chloride) Breakthrough time > 480 Material thickness (mm): 0,35				
Eye protection:					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.				
Skin protection:					
PPE:	Chemical protective clothing «CE» marking, category III. Clothing should fit properly. The level of protection				
Characteristics:	must be set according to a test parameter called BT (Breakthrough Time), which				
CEN standards:	indicates how long it takes for the chemical to pass through the material. EN 464,EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.				

1075-Nettoyant Ligne d'Eau



Version 1 Date of compilation: 20/01/2020 Version 3 (replaces version 2) Revision date: 08/03/2022

PPE:	Anti-static safety footwear against chemicals.
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Amber Odour: Not applicable/Not available due to the nature/properties of the product Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product Boiling point or initial boiling point and boiling range: Descompone °C Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product Flash point: 126 °C (Estimation based on the indication of the Regulation (CE) Nº1272/2008.) Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product pH: 13-14 (20°C) Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product Solubility: Not applicable/Not available due to the nature/properties of the product Hydrosolubility: 100 % Liposolubility: Alcohol y glicerol Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product Vapour pressure: 22,9 (Estimation based on the indication of the Regulation (CE) Nº1272/2008.) Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: 1.02 - 1.13 (20 °C) Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Viscosity: Not applicable/Not available due to the nature/properties of the product Explosive properties: Not applicable/Not available due to the nature/properties of the product Oxidizing properties: No aplicable Dropping point: Not applicable/Not available due to the nature/properties of the product

Blink: Not applicable/Not available due to the nature/properties of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with: - Acids.

10.3 Possibility of hazardous reactions.

Page 7 of 13

Print date: 21/11/2024

(in accordance with Regulation (EU) 2020/878)

1075-Nettoyant Ligne d'Eau



Version 1 Date of compilation: 20/01/2020 Version 3 (replaces version 2) Revision date: 08/03/2022

Page 8 of 13 Print date: 21/11/2024

Neutralization can occur on contact with acids.

10.4 Conditions to avoid.

- Avoid contact with acids.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

Corrosive vapors or gases.

SECTION 11: TOXICOLOGICAL INFORMATION.

2-butoxyethanol and its acetate are easily absorbed by the skin and can cause noxious effects to the kidneys.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

Name		Acute toxicity				
	Name	Туре	Test	t Kind	Value	
sodium hydroxide		Oral	experin	Rabbit Naunyn-Schmiedel nentielle Pathologie ny), 184, 587-604		
		Dermal		<u>1777 10 17 10 17 10 17 10 17</u>		
CAS No: 1310-73-2	EC No: 215-185-5	Inhalation				
2-butoxyethanol		Oral	LD50 LD50 [1] OCI [2] OCI		1300 mg/kg [1] 1300 mg/kg [2]	
		Dermal	LD50	Rat	> 2000 mg/kg [1]	
CAS No: 111-76-2	EC No: 203-905-0	Inhalation	LC50	Rat	450 ppm (4 h) [1]	
Poly(oxy-1,2-ethanediyl), .alphaundecyl- .omegahydroxy-, branched and linear		Oral	LD50	Rat	2000 mg/kg	
		Dermal	LD50	Rat	>2000 mg/kg	
CAS No: 127036-24-2	EC No:	Inhalation				

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Product classified:

Skin Corrosive, Category 1: Causes severe skin burns and eye damage.

(in accordance with Regulation (EU) 2020/878)

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 9 of 13 Print date: 21/11/2024

c) serious eye damage/irritation; Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure; Not conclusive data for classification.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity					
Name	Туре	Test	Kind	Value		
	Fish	LC50	Fish	35-189 mg/kg (96 h)		
sodium hydroxide	Aquatic	EC50	Ceriodaphnia sp.	40.4 mg/L (48 h) [1]		
	invertebrates	ates [1] Warne MSJ (1999), Ecotoxicology and Environmental Safety, 14, 196-206				
CAS No: 1310-73-2 EC No: 215-185-5	Aquatic plants					
	Fish	LC50 LC50	Fish Fish	1250 ppm (96 h) 1250 ppm (96 h)		
2-butoxyethanol	Aquatic invertebrates	EC50 EC50	Daphnia Daphnia	1550 ppm (48 h) 1550 ppm (48 h)		
CAS No: 111-76-2 EC No: 203-905-0	Aquatic plants	EC50 NOEC	Algae Algae	911 mg/l (72 h) 88 mg/l (72 h)		
Poly(oxy-1,2-ethanediyl), .alphaundecyl-	Fish	LC50	Cyprinus carpio	1-10 mg/l [1]		

1075-Nettoyant Ligne d'Eau



Version 1 Date of compilation: 20/01/2020 Version 3 (replaces version 2) Revision date: 08/03/2022

Page 10 of 13 Print date: 21/11/2024

	[1] OECD TG 20)6	
Aquatic invertebrates		5	1-10 mg/l [1]
Aquatic plants	EC50 subs	spicatus	1-10 mg/l [1]
	Aquatic invertebrates	Aquatic [1] OECD TG 20 invertebrates [1] OECD TG 20 Aquatic plants EC50	Aquatic invertebrates [1] OECD TG 202 EC50 Subspiratus

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
2-butoxyethanol		0,8	_	_	Very low
CAS No: 111-76-2	EC No: 203-905-0	0,0			Very IOW

12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 11 of 13 Print date: 21/11/2024

Sea: Transport by ship: IMDG. Transport documentation: Bill of lading **<u>Air</u>:** Transport by plane: ICAO/IATA. Transport document: Airway bill.

14.1 UN number or ID number. UN No: UN1760

14.2 UN proper shipping name.

Description: ADR/RID: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE), 8, PG III, (E) IMDG: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE), 8, PG III ICAO/IATA: UN 1760, CORROSIVE LIQUID, N.O.S. (CONTAINS SODIUM HYDROXIDE), 8, PG III

14.3 Transport hazard class(es).

Class(es): 8

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-B

14.6 Special precautions for user.

Labels: 8



Hazard number: 80 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 1 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 3,115 % VOC content: 31,777 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

1075-Nettoyant Ligne d'Eau



Version 1	Date of compilation:	20/01/2020
Version 3 (re	eplaces version 2)	Revision date: 08/03/2022

Page 12 of 13 Print date: 21/11/2024

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4 Eye Dam. 1 : Serious eye damage, Category 1 Eye Irrit. 2 : Eye irritation, Category 2 Skin Corr. 1 : Skin Corrosive, Category 1 Skin Corr. 1A : Skin Corrosive, Category 1A Skin Irrit. 2 : Skin irritant, Category 2

Changes regarding to the previous version:

- Modification of specific hazards (SECTION 2.3).
- Changes in the composition of the product (SECTION 3.2).
- Modification in the firefighting measures (SECTION 5.2).
- Modifications in the accidental release measures (SECTION 6.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

(in accordance with Regulation (EU) 2020/878)

1075-Nettoyant Ligne d'Eau



Version 1Date of compilation: 20/01/2020Version 3 (replaces version 2)Revision date: 08/03/2022

Page 13 of 13 Print date: 21/11/2024

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.

- AwSV: Facility Regulations for handling substances that are hazardous for the water.
- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.
- LC50: Lethal concentration, 50%.
- LD50: Lethal dose, 50%.
- NOEC: No observed effect concentration.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.
- WGK: Water hazard classes.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.