

AUTOMATIC COMMERCIAL POOL CLEANERS



TRX 8500 IQ - VORTRAX

Specifically designed for intensive use in small or medium-sized public pools (hotels, campings, apartments, etc.) with rigid walls up to 20 m length tough, smart and ultra-efficient.

- + High performance brushless electronic motor.
- + Easy-to-clean brush system.
- + Sensor Nav Sytem TM: intelligent and personalised cleaningwith anti-tangle compass system without the need of swivel.
- + Heavy-duty materials and traction system for intensive use.
- + Ultra-powerful and long-lasting suction with easy-to-clean filters.

Code

WR000597



Units / pallet

AquaLini

TRACKS TRACTION

PATENTED

Accessories

Standard Model

Trolley Control box Dual-Stage filter 150 + 60µ (with possibility to use 150µ alone) Contact Brushes Free app

FOR WHICH TYPE OF POOLS?		
Types of pools	Small to medium public pools (hotels, campings, apartments) with rigid walls, up to 20m length	
Pool shapes	Rectangular, oval, freeshape	
All Floors	Flat, gentle slope, composite slope, diamond shape	
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete	

DESCRIPTION			
Cleaning areas	Floor /walls/ waterline		
Number / Length of cleaning cycles	Multiple from 0h30 to 6h00 with preset cycles: -Quick: floor only 1h15 -Smart: floor / walls / waterline (calculated time) -Ultra: floor / walls / waterline (2h45)		
Timer / Delayed start	7-days timer / Up to 3h delayed start		
Power supply	Autonomous, connected to 230V main supply before the transformer		
Steering	Pre-programmed		
Drive system	Tracks system drive - 2 brushless motors		
Transmission	Gear transmission with reinforced components		
Pressure sensor	Yes		
Brushes	Yes (Contact + ZZ Brushes)		
Lift System	Yes		
Full filter indicator	Yes		
Remote control	Remote control mode (with app)		
Water temperature measure- ment	Yes		
Pressure depth sensor	Yes		
Safety	Deck system, out of water safety, diagnostic, electronic motor protector		
Filtration system / access	Rigid Filter canister with access over the cleaner		

12

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60Hz
Power supply	30 VDC
Operating power	150 W
Cable length / Hose length	25m
Cleaner size (L x W x h)	47 x 51 x 29 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	11 kg
Packaging weight	21 kg
Filtering surface and level	1180 cm ³
Filtering capacity	5L
Inlet suction size / /Cleaned width	24.5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)		
Fine filter canister 100µ	Fine filter canister 200µ	
R0863600	R0863700	