

ctx600 ANTICAL



Prevents limescale deposits

- Eliminates and prevents lime scale buildup.
- Helps prevent filters from clogging and metal parts of the circulation and filtration system from corroding.

LIQUID	EFFICACY	ALL TYPES OF POOLS	DOSAGE
	WEEKLY	 	50ml /10m ³

PROPERTIES

Appearance	Liquid
Colour	Colourless
pH (0,1%)	>12,5
Density	1,33 - 1,37 g /cm ³

CHARACTERISTICS

Dispersing and inhibiting product, by means of which incrustations are eliminated and avoided, it also helps to prevent the obstruction of filters and the corrosion of the metallic parts of the recirculation and filtration system.

INSTRUCTIONS FOR USE

Those pools that are not emptied during the winter period should be treated with an initial dose of product at the end of the bathing season.

Dilute the necessary amount of product in a container with water and spread it evenly over the entire surface of the pool, keeping the filtration equipment running.

DOSAGE

Initial Treatment: Add 2.5 lts. of product per 100 m³ of water.

Maintenance Treatment: Add 0.5 lts. of product per 100 m³ of water once a week.

These doses are indicative and can be modified depending on the hardness and salt content of the water.

ctx
pro

The caring formula
ctxprofessional.com