



ASTRALPOOL 

Evo

Air/Water heat pump

**Heat your pool
in the cheapest
possible way**



- ▶ Private pools of up to 90m³
- ▶ Silent
- ▶ Robust ABS casing
- ▶ Titanium exchanger
- ▶ Easy-to-use control panel



Evo

Air/Water heat pump



www.astralpool.com

Performance

- Wide range of power settings for all types of pools (see table for technical specifications).
- Silent.
- Robust and light ABS casing resistant to sunlight.
- Easy-friendly digital panel
- R-407C refrigerant gas (environmentally friendly).
- Protected electrical box
- Improvements in quality cabling (hose, . . .)
- Titanium exchanger ready to be used for all kind of chemical treatments (UV, ozone, chlore, salt chlorinator. . .)
- Forced draught defrosting cycle



Daily consumption

(8 m x 4 m pool).
80% of its power comes from the atmosphere.



For all kinds of pools and treatments

(chlorine, bromine, ozone, UV, electrochemical, salt, etc.).



Easy-to-Use
Digital Control Panel.



2-year warranty



AstralPool heat pumps enable pool temperatures to be raised so that the swimming season can be lengthened cheaply and swimmers can use the pool in comfort.

Technical specifications

		BLPAM200	BLPAM400	BLPAM600	BLPAM700 BLPAT700	BLPAM800 BLPAT800	BLPAT900
Power	kW	4,2	8,5	13,5	17	21	25
Voltage	V/Ph/Hz	230/2/50	230/2/50	230/2/50	230/2/50 - 400/3/50	230/2/50 - 400/3/50	400/3/50
Pool	MAX.	m ³	14,5	29,0	46,0	58,0	72,0
Volume	MIN.	m ³	9,0	18,0	29,0	36,0	45,0
Sound level	dB(A)	≤47	≤51	≤58	≤58	≤58	≤60

27°C T. Air	INLET	kW	0,87	1,75	2,66	3,57	4,59	5,61
24°C T. Water	OUTLET	kW	4,70	9,50	14,50	19,20	24,30	29,70
	COP		5,40	5,43	5,45	5,38	5,29	5,29
15°C T. Air	INLET	kW	0,85	1,70	2,60	3,50	5,50	5,50
24°C T. Water	OUTLET	kW	4,20	8,50	13,50	17,00	21,00	25,00
	COP		4,94	5,00	5,19	4,88	4,67	4,56
5°C T. Air	INLET	kW	0,75	1,50	2,29	3,08	3,96	4,84
24°C T. Water	OUTLET	kW	2,60	5,20	8,00	10,40	13,00	18,80
	COP		3,47	3,47	3,49	3,38	3,28	3,88

