

# ASTER TN



### FEATURES

- ✓ Filters manufactured from polyester resin and fiberglass.
- ✓ Excellent finish.
- ✓ Filter color: grey.
- ✓ Fast opening top lid.
- ✓ Fitted with 1" collector arms and easy-to-remove threaded diffuser.
- ✓ Manometer, manual and automatic air drain and manual water drain.
- ✓ Connections to six positions multiport valve with filter, backwash, rinse, recirculate, waste and closed operations.
- ✓ Maximum pressure 2.5 bar.

### CARACTERÍSTICAS

- ✓ Filtros fabricados con proyección simultánea de resina de poliéster y fibra de vidrio.
- ✓ Excelente acabado.
- ✓ Color del filtro: gris.
- ✓ Tapa superior de apertura rápida.
- ✓ Montado con colectores de 1" y difusor roscado de fácil manipulación.
- ✓ Manómetro y purga de agua manual y aire automática y manual.
- ✓ Conexiones para válvula selectora de seis vías, con operaciones de filtración, lavado, enjuague, recirculación, vaciado y cerrado.
- ✓ Presión máxima 2.5 bar.

## FILTER DETAILS



▪ Cone diffuser



▪ Fitted with 1" collector arms



▪ Fast opening top lid

### TECHNICAL DATA

### PACKAGING

Code	Model (mm)	Connections (mm/inch)		Filtering velocity (m <sup>3</sup> /h/m <sup>2</sup> )	Filtration Area (m <sup>2</sup> )	Flow (m <sup>3</sup> /h)	Maximum pressure (bar)	Sand (0.4-0.8mm) (kg)	Net weight (kg)	D (mm)	H (mm)	M (mm)	N (mm)	Units per pallet	Box dimension (cm)
		mm	inch												
00497-0100	350	50	1 ½"	50	0.096	5	2.5	50	9	375	655	400	275	15	39x39x76
00498-0100	450	50	1 ½"	50	0.16	8	2.5	70	15	455	730	415	290	10	52x52x76
19781-0100	500	50	1 ½"	50	0.19	10	2.5	95	15	525	725	419	294	8	56x56x85
32706-0100	550	50	1 ½"	50	0.24	12	2.5	110	20	575	775	450	325	8	65x65x86
00499-0100	600	50	1 ½"	50	0.30	15	2.5	125	21	620	790	445	320	8	65x65x86
21071-0100	650	50	1 ½"	50	0.33	17	2.5	200	24	680	825	487	362	8	70x70x89
28479-0100	680	50	1 ½"	50	0.36	18	2.5	210	26	715	865	475	350	8	70x70x89
00500-0100	750	63	2"	50	0.44	22	2.5	290	30	785	890	565	335	2	80x80x93
08133-0100	900	63	2"	50	0.64	32	2.5	500	48	935	1020	670	400	2	96x96x110
00501	900	75	2 ½"	50	0.64	32	2.5	500	51	935	1020	665	395	2	96x96x110

