



## THE HEATER FOR BIGGER POOLS

### RE/I

#### 1 2 POWER LEVELS

The RE/I heater is ideal for pools up to 990 m<sup>3</sup>\*. 2 power levels can be manually set depending on energy saving requirements.



#### 2 MAXIMUM TOUGHNESS

Made in France, its manufacturing quality ensures maximum toughness (EPDM flanges, Hypalon connectors and titanium resistance).



#### 3 FULL DIGITAL REGULATION

The RE/I is equipped with a digital regulator making it easy to adjust the thermostat, the timer, etc., and keep the pool water at the optimum temperature from season to season.



## FEATURES

<990M<sup>3</sup>

SUITABLE FOR POOLS  
UP TO 990 m<sup>3</sup>\*

Ti<sup>22</sup>  
TITANE  
INSIDE

LONG-LASTING  
Patented titanium resistance  
that ensures  
maximum robustness



EASY INSTALLATION  
Only requires a hydraulic  
connection and electricity

## EQUIPMENT

- Electric control unit with precision thermostat  $\pm 0.5^{\circ}\text{C}$
- Digital display and timer
- Watertightness of electrical resistances with an EPDM collar
- HYPALON encapsulated electric connections
- Flow rate switch
- Power contactors
- Illuminated control switches
- Power modulation (2 manual stages) as standard
- Recommended installation of a by-pass if the filtration pump has a flow rate  $>50\text{m}^3$

## TECHNICAL INFORMATION

MODELS	RE/I 30T	RE/I 36T	RE/I 42T	RE/I 48T	RE/I 60T	RE/I 84T	RE/I 96T	RE/I 120T
Voltage	400V - 3N - 50/60Hz							
Operating power**	12 + 18	12 + 24	18 + 24	24 + 24	24 + 36	36 + 48	48 + 48	60 + 60
Current absorbed (A)***	44	52	61	70	87	122	139	174
Water flow rate ( m <sup>3</sup> /h)	20 to 30				30 to 50			
Hydraulic connection	PVC half-unions, 63, to be glued				2 flanges, DN80, with PVC connector, 90, to be glued			

\* Consult a professional to size your electric heater.

\*\* Operating voltage tolerance of + 6 - 10% Grid power supply.

\*\*\* Manufacturing tolerance of + or - 5%.

Easy to install and to use, Zodiac® electric heaters heat your pool rapidly and keep the water at the desired temperature, for a very competitive purchase price. Compact, stand-alone units, they are fitted to the filtration system, and you only have to start filtration to raise the temperature.

**2** YEARS  
WARRANTY