## MAINTENANCE 3 Algicide

# ctx500 ALGASTOP



# Prevents algae formation and growth

· High bactericide, algaecide and fungicide power.

· Fast-working, long-lasting.



#### **PROPIEDADES**

| Appearance     | Liquid                          |
|----------------|---------------------------------|
| Colour         | Blue                            |
| pH (20°C)      | 5-9                             |
| Density (20°C) | 0,98 - 1,02 gr./cm <sup>3</sup> |

## CARACTERÍSTICAS

Effective fast-acting quaternary ammonium compound, with a powerful bactericidal, fungicidal and algicidal action, intended for the prevention and elimination of algae.

### **MODO DE EMPLEO**

Pour the necessary dose of product into a container with water and distribute this solution evenly over the surface of the pool. It will preferably be done at sunset and without the presence of swimmers in the pool.

**Periodic disinfection of the pool glass:** Before refilling the pool, it is recommended to impregnate the walls and the bottom with a product solution (1 It. Of the product in 10 Its. Of water) thus forming a protective film of action disinfectant.

**Disinfection of the pool environment:** The surfaces that are part of the pool environment can become slippery and can be a vehicle for transmitting diseases. To avoid these inconveniences, we recommend applying a product solution (5 liters of the product in 10 liters of water) daily by means of a sprayer or watering can.

After one hour these surfaces should be rinsed with plenty of water.





### DOSIFICACIÓN

Initial Treatment: Add 2 litres of product per 100 m3 of water.

The Initial treatment should be repeated whenever the water does not appear transparent.

Tratamiento de mantenimiento: Add 0,5L for every 100m3 of water once a week.

These doses are the ones suggested and can be modified according to the own characteristics of every swimming pool, climate, etc.

