

ASTER TC - 5018



FEATURES

- ✓ Filters manufactured by spraying up on layers of polyester resin and fiber glass.
- ✓ Excellent finish.
- ✓ Color: RAL 5018.
- ✓ Transparent top lid with screws.
- ✓ Maximum temperature: 50°C.
- ✓ Maxim pressure 2.5 bars.
- ✓ ¼" air and water drain.
- ✓ Fitted with 1" arm collectors and easy-to-remove cone diffuser.

CARACTERÍSTICAS

- ✓ Filtros fabricados con proyección simultánea de poliéster y fibra de vidrio.
- ✓ Excelente acabado.
- ✓ Color: RAL 5018.
- ✓ Tapa superior transparente con tornillos.
- ✓ Temperatura máxima: 50°C.
- ✓ Máxima presión 2.5 bar.
- ✓ Purga de aire y agua de ¼".
- ✓ Equipado con brazos colectores de 1" y un cono difusor roscado de fácil manipulación

FILTER DETAILS



- Cone diffuser
- Cono difusor



- Arm collectors of 1"
- Brazos colectores de 1"



- Transparent top lid with screws
- Tapa superior transparente con tornillos

TECHNICAL DATA

Code	Model (mm)	Connections (mm/inch)		Filtering velocity (m³/h/m²)	Filtration Area (m²)	Flow (m³/h)	Maximum pressure (bar)	Sand (0.4-0.8mm) (kg)	Net weight (kg)	D (mm)	H (mm)	M (mm)	N (mm)
		mm	inch										
20609FA65	350	50	1 ½"	50	0.096	4.8	2.5	50	15	350	655	420	295
20610FA65	450	50	1 ½"	50	0.16	8	2.5	70	18	450	710	430	305
20611FA65	500	50	1 ½"	50	0.196	10	2.5	85	20	500	855	415	290
20612FA65	600	50	1 ½"	50	0.283	14	2.5	125	25	600	900	455	330
20613FA65	750	63	2"	50	0.442	22	2.5	300	33	750	1035	555	325
21584FA65	900	63	2"	50	0.636	32	2.5	430	50	900	1100	635	365

PACKAGING

Code	Units per pallet	Box dimension (cm)
20609FA65	15	39x39x76
20610FA65	10	52x52x76
20611FA65	8	56x56x85
20612FA65	8	65x65x86
20613FA65	2	80x80x93
21584FA65	2	96x96x110

