

Date of compilation: 18/06/2018

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

Version: 13 (Replaced 12)



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Revised: 09/11/2022

SEC	TION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier: 81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE
	Other means of identification:
	Non-applicable
1.2	Relevant identified uses of the substance or mixture and uses advised against:
	Relevant uses: Neoprene-base contact adhesive. For professional users only.
	Uses advised against: All uses not specified in this section or in section 7.3
1.3	Details of the supplier of the safety data sheet:
	RENOLIT IBERICA SA
	Ctra. del Montnegre, s/n 08470 Sant Celoni - Barcelona - España
	Phone: +34 938484000 - Fax: +34 938675936
	piscinas@renolit.com http://renolit.com/swimmingpool
1.4	Emergency telephone number: +44 1235 239 670
SEC	TION 2: HAZARDS IDENTIFICATION
2.1	Classification of the substance or mixture:
	CLP Regulation (EC) No 1272/2008:
	Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
	Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411
	Eye Irrit. 2: Eye irritation, Category 2, H319
	Flam. Liq. 2: Flammable liquids, Category 2, H225 Skin Irrit. 2: Skin irritation, Category 2, H315
	STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
2.2	Label elements:
	CLP Regulation (EC) No 1272/2008:
	Danger
	Hazard statements:
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Lig. 2: H225 - Highly flammable liguid and vapour.
	Skin Irrit. 2: H315 - Causes skin irritation.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
	Precautionary statements:
	P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children.
	P103: Read label before use. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing.
	P312: Call a POISON CENTER/doctor if you feel unwell.
	P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment. Supplementary information:
	EUH208: Contains Rosin. May produce an allergic reaction.
	UFI: WJT0-HV3V-R31X-6UHT
	- CONTINUED ON NEXT PAGE -
ate of c	compilation: 18/06/2018 Revised: 09/11/2022 Version: 13 (Replaced 12) Page 1/1



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of polymers and resins in solvent

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification	Chemical name/Classification				
CAS: EC:	Non-applicable 926-605-8	Hydrocarbons, C6-C7	, isoalkanes, cyclics, <5% n-hexane 1	Self-classified		
Index: Non-applicable REACH: 01-2119486291-36- XXXX		Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	() () () ()	25 - <50 %	
CAS: EC:	141-78-6 205-500-4	Ethyl acetate 1		ATP CLP00		
Index: REACH	205-500-4 607-022-00-5 : 01-2119475103-46- XXXX	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	() ()	25 - <50 %	
CAS: 25085-50-1 EC: 472-160-3 Index: Non-applicable REACH: 01-0000019790-66- XXXX		4-tert-butylphenol-form	maldehyde copolymer 1	Self-classified		
		Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	È	2,5 - <10 %	
CAS: EC:	123-86-4 204-658-1	N-butyl acetate 1		ATP CLP00		
EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29- XXXX		Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	<u>()</u>	5 - <10 %	
CAS: EC:	8050-09-7 232-475-7	Rosin ¹		ATP CLP00		
Index: 650-015-00-7		Regulation 1272/2008	Skin Sens. 1: H317 - Warning	\$	0,1 - <1 %	
CAS: 50-00-0 EC: 200-001-8		Formaldehyde ²		ATP ATP06		
Index:	200-001-8 605-001-00-5 : 01-2119488953-20- XXXX	Regulation 1272/2008	Acute Tox. 3: H301+H311+H331; Carc. 1B: H350; Muta. 2: H341; Skin Corr. 1B H314; Skin Sens. 1: H317 - Danger		<0,1 %	

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878
² Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Formaldehyde CAS: 50-00-0 EC: 200-001-8	% (w/w) >=25: Skin Corr. 1B - H314 5<= % (w/w) <25: Skin Irrit. 2 - H315 % (w/w) >=25: Eye Dam. 1 - H318 5<= % (w/w) <25: Eye Irrit. 2 - H319 % (w/w) >=0,2: Skin Sens. 1 - H317 % (w/w) >=5: STOT SE 3 - H335

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:**



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 4: FIRST AID MEASURES (continued)

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE **RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE**

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

Reference to other sections: 6.4

See sections 8 and 13

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling: 7.1

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage Minimum Temp.: 5°C Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Ethyl acetate	IOELV (8h)	200 ppm	734 mg/m ³
CAS: 141-78-6 EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m ³
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m ³
Formaldehyde	IOELV (8h)	0,3 ppm	0,37 mg/m ³



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE **RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE**

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
CAS: 50-00-0 EC: 200-001-8	IOELV (STEL)	0,6 ppm	0,74 mg/m ³

DNEL (Workers):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	13964 mg/kg	Non-applicable
EC: 926-605-8	Inhalation	Non-applicable	Non-applicable	5306 mg/m ³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	1468 mg/m ³	1468 mg/m ³	734 mg/m³	734 mg/m ³
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	600 mg/m³	600 mg/m³	300 mg/m ³	300 mg/m ³
Rosin	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 8050-09-7	Dermal	Non-applicable	Non-applicable	2,131 mg/kg	Non-applicable
EC: 232-475-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	10 mg/m ³
Formaldehyde	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	240 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	0,75 mg/m³	9 mg/m³	0,375 mg/m ³

DNEL (General population):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Oral	Non-applicable	Non-applicable	1301 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	1377 mg/kg	Non-applicable
EC: 926-605-8	Inhalation	Non-applicable	Non-applicable	1131 mg/m ³	Non-applicable
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
EC: 205-500-4	Inhalation	734 mg/m ³	734 mg/m ³	367 mg/m ³	367 mg/m ³
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
EC: 204-658-1	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
Rosin	Oral	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
CAS: 8050-09-7	Dermal	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
EC: 232-475-7	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Formaldehyde	Oral	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
CAS: 50-00-0	Dermal	Non-applicable	Non-applicable	102 mg/kg	Non-applicable
EC: 200-001-8	Inhalation	Non-applicable	Non-applicable	3,2 mg/m ³	0,1 mg/m ³
PNEC:	•	-	-	-	•
Identification					
Educia	OTD	650 mm/	Erech water	0	0.4 mag/l

Identification				
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Rosin	STP	1000 mg/L	Fresh water	0,002 mg/L
CAS: 8050-09-7	Soil	0 mg/kg	Marine water	0 mg/L
EC: 232-475-7	Intermittent	0,016 mg/L	Sediment (Fresh water)	0,007 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,001 mg/kg
Formaldehyde	STP	0,19 mg/L	Fresh water	0,44 mg/L
CAS: 50-00-0	Soil	0,2 mg/kg	Marine water	0,44 mg/L
EC: 200-001-8	Intermittent	4,44 mg/L	Sediment (Fresh water)	2,3 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	2,3 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

EC	TION 8: EXPOSURE CONTROLS/PERS	ONAL PROTECT	ION (continued)					
	Emergency measure Sta	andards	Emergency measure	Standards				
		6I Z358-1 I1, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011				
	Environmental exposure controls:							
	In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds:							
	With regard to Directive 2010/75/EU, this produ	uct has the following	characteristics:					
	(11)	% weight						
	V.O.C. density at 25 °C: 647,8	1 kg/m³ (647,81 g/L)						
	Average carbon number: 5,2							
	Average molecular weight: 88,32	g/mol						
	TION 9: PHYSICAL AND CHEMICAL PR							
1	Information on basic physical and chemical							
•	For complete information see the product data							
		Sheet.						
	Appearance:	انستنا						
	Physical state at 20 °C:	Liquid						
	Appearance:	Viscous						
	Colour:							
	Odour:	Solvent						
	Odour threshold:	Non-applic	able ^					
	Volatility:	04.00						
	Boiling point at atmospheric pressure:	81 °C						
	Vapour pressure at 25 °C:	5322 Pa						
	Vapour pressure at 50 °C:	-	Pa (15,9 kPa)					
	Evaporation rate at 25 °C:	Non-applic	adie					
	Product description:	045 0051						
	Density at 25 °C:	845 - 885 k	tg/m ^s					
	Relative density at 25 °C:	0,88						
	Dynamic viscosity at 25 °C:	2800 - 540						
	Kinematic viscosity at 25 °C:	Non-applic						
	Kinematic viscosity at 40 °C:	>20,5 mm ²						
	Concentration:	Non-applic						
	pH:	Non-applic						
	Vapour density at 25 °C:	Non-applic						
	Partition coefficient n-octanol/water 25 °C:	Non-applic						
	Solubility in water at 25 °C:	Non-applic						
	Solubility properties:		n water, soluble in organic	c solvents				
	Decomposition temperature:	Non-applic						
	Melting point/freezing point:	Non-applic	able *					
	*Not relevant due to the nature of the product, not provide	ng information property o	f its hazards.					
		CONTINUED ON NE						



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of	compilation: 18/06/2018 Revised: 09/11/2022	Version: 13 (Replaced 12)
SEC	TION 9: PHYSICAL AND CHEMICAL PROPER	RTIES (continued)
	Flammability:	
	Flash Point:	-1 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	345 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard classe	s:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Non-applicable *
	Surface tension at 25 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing inform	nation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

10.5

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable
Incompatible materials:				

Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid alkalis or strong bas	Acids	Water	Oxidising materials	Combustible materials	Others
······g······g······g·····	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: Formaldehyde (1); Polychloroprene (3); Talc (3); disulfiram (3)
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	Acute toxicity		
Ethyl acetate	LD50 oral	4100 mg/kg	Rat	
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit	
EC: 205-500-4	LC50 inhalation	Non-applicable		
N-butyl acetate	LD50 oral	12789 mg/kg	Rat	
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit	
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat	



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	A	cute toxicity	Genus
Rosin	LD50 oral	4100 mg/kg	Rat
CAS: 8050-09-7	LD50 dermal	Non-applicable	
EC: 232-475-7	LC50 inhalation	Non-applicable	
Formaldehyde	LD50 oral	100 mg/kg	
CAS: 50-00-0	LD50 dermal	300 mg/kg	
EC: 200-001-8	LC50 inhalation	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	LC50	>1 - 10 mg/L (96 h)		Fish
CAS: Non-applicable	EC50	>1 - 10 mg/L (48 h)		Crustacean
EC: 926-605-8	EC50	>1 - 10 mg/L (72 h)		Algae
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
4-tert-butylphenol-formaldehyde copolymer	LC50	0,26 mg/L (96 h)	N/A	Fish
CAS: 25085-50-1	EC50	1,4 mg/L (48 h)	N/A	Crustacean
EC: 472-160-3	EC50	Non-applicable		
N-butyl acetate	LC50	Non-applicable		
CAS: 123-86-4	EC50	Non-applicable		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Rosin	LC50	150 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 8050-09-7	EC50	238 mg/L (48 h)	Daphnia magna	Crustacear
EC: 232-475-7	EC50	185 mg/L (72 h)	Selenastrum capricornutum	Algae
Formaldehyde	LC50	100 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 50-00-0	EC50	42 mg/L (24 h)	Daphnia magna	Crustacear
EC: 200-001-8	EC50	Non-applicable		

Chronic toxicity:

Identification		Concentration	Species	Genus	
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish	
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean	
N-butyl acetate	NOEC	Non-applicable			
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean	
Formaldehyde	NOEC	Non-applicable			
CAS: 50-00-0 EC: 200-001-8	NOEC	6,4 mg/L	Daphnia magna	Crustacean	

12.2 Persistence and degradability:

Substance-specific information:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	De	gradability	Biode	egradability
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %
N-butyl acetate	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 123-86-4	COD	Non-applicable	Period	5 days
EC: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %
Rosin	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 8050-09-7	COD	Non-applicable	Period	28 days
EC: 232-475-7	BOD5/COD	Non-applicable	% Biodegradable	32 %
Formaldehyde	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 50-00-0	COD	Non-applicable	Period	14 days
EC: 200-001-8	BOD5/COD	Non-applicable	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccur	nulation potential
Ethyl acetate	BCF	30
CAS: 141-78-6	Pow Log	0.73
EC: 205-500-4	Potential	Moderate
4-tert-butylphenol-formaldehyde copolymer	BCF	
S: 25085-50-1	Pow Log	4.67
EC: 472-160-3	Potential	
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
Formaldehyde	BCF	3
CAS: 50-00-0	Pow Log	0.35
EC: 200-001-8	Potential	Low

12.4 Mobility in soil:

Identification	Absorp	tion/desorption	Volat	ility
Ethyl acetate	Koc	59	Henry	13,58 Pa⋅m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
N-butyl acetate	Кос	Non-applicable	Henry	Non-applicable
CAS: 123-86-4	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable
Formaldehyde	Кос	Non-applicable	Henry	Non-applicable
CAS: 50-00-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-001-8	Surface tension	1,416E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

Revised: 09/11/2022

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Version: 13 (Replaced 12)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018

Revised: 09/11/2022

Version: 13 (Replaced 12)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

with regard to AL	JR 202	1 and RID 2021:	
	14.1	UN number or ID number:	UN1133
× ×	14.2	UN proper shipping name:	ADHESIVES
	14.3	Transport hazard class(es):	3
		Labels:	3
	14.4	Packing group:	II
	14.5	Environmental hazards:	Yes
	14.6	Special precautions for user	
		Special regulations:	640D
		Tunnel restriction code:	D/E
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of dar	ngerou	s goods by sea:	
With regard to IM	DG 40-	-20:	
	14.1	UN number or ID number:	UN1133
	14.2	UN proper shipping name:	ADHESIVES
W AL	14.3	Transport hazard class(es):	3
		Labels:	3
	14.4	Packing group:	II
	14.5	Marine pollutant:	Yes
	14.6	Special precautions for user	
		Special regulations:	Non-applicable
		EmS Codes:	F-E, S-D
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		Segregation group:	Non-applicable
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable
Transport of dar		Maritime transport in bulk according to IMO instruments:	
Transport of dar With regard to IA	ngerou	Maritime transport in bulk according to IMO instruments: s goods by air:	



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Date of compilation: 18/06/2018	Revised: 09/11/2022	Version: 13 (Replaced 12)
SECTION 14: TRANSPOR	T INFORMATION (continue	d)
14.1 14.2 14.3 14.4 14.5 14.6	UN number or ID number: UN proper shipping name: Transport hazard class(es): Labels: Packing group: Environmental hazards: Special precautions for user	UN1133 ADHESIVES 3 3 II Yes
14.7	Physico-Chemical properties: Maritime transport in bulk according to IMO instruments	see section 9 Non-applicable ::

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Formaldehyde (Product-type 2, 3, 22)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

Shall not be used in:

---ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



81045001-81045002 - RENOLIT ALKORGLUE RUBBER-CHLOROPRENE BASED CONTACT ADHESIVE

Revised: 09/11/2022 Date of compilation: 18/06/2018 Version: 13 (Replaced 12) SECTION 16: OTHER INFORMATION (continued) H225: Highly flammable liquid and vapour. H315: Causes skin irritation. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. H411: Toxic to aquatic life with long lasting effects. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled. Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Carc. 1B: H350 - May cause cancer. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Flam. Liq. 3: H226 - Flammable liquid and vapour. Muta. 2: H341 - Suspected of causing genetic defects. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H336 - May cause drowsiness or dizziness. Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms: ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -