



EFFICIENTLY SMART & VERSATILE

GenSalt OE iQ

1 SMARTLY SIMPLE

Easy-to-use thanks to its **innovative & large user interface** focusing on essential information, while being able to access all settings details via the touch buttons. Anytime & anywhere app control with the **Fluidra Pool® app** thanks to its embedded Bluetooth & Wi-Fi connectivity.




2 COMPACT & VERSATILE

Sturdy and compact design to fit all pool pads. Available either in standard version (salt water chlorinator only) or in **evolutionary version** that already includes the **pH regulation** and can get an **optional ORP regulation** for a complete water treatment.



3 A RELIABLE CHOICE

Easy-to-install patented **Quick Fix cell**, with a long-lasting polarity-reversing electrode that can easily be checked thanks to its translucent cell body. Maximum peace of mind with its **2-year unconditional warranty**⁽¹⁾.




⁽¹⁾ 2 years unconditional (device), 2 years (pH sensor), 1 year (ORP sensor and consumables).

SPECIFICATIONS



CONNECTIVITY

Embedded Bluetooth & Wi-Fi with Fluidra Pool® app control.



BOOST & COVER MODE

Achieve 100% chlorine production over a 24-hour cumulative period, and automatically adjust chlorine production when the pool cover is closed.

STOP

SAFE-SYSTEM

Automatic stop if there is no flow in the cell thanks to the flow switch.



WATER PARAMETERS

Water salinity and temperature readings.



UNCONDITIONAL GUARANTEE

On the control box and the cell, whatever the causes of damage.

FOR WHICH TYPE OF POOLS?

1 ALL TYPES OF SWIMMING POOLS



2 POOLS UP TO 110m³
Temperate climate,
filtration 8 hr/day.



ACCESSORIES INCLUDED IN THE PACK



Cell installation kit



Flow switch kit



Wall mounting kit



Temperature sensor kit

TECHNICAL INFORMATION

MODELS	GenSalt OE iQ 12	GenSalt OE iQ 20	GenSalt OE iQ 25	GenSalt OE iQ pH 12 Evo	GenSalt OE iQ pH 20 Evo	GenSalt OE iQ pH 25 Evo
Chlorine output	12 g/h	20 g/h	25 g/h	12 g/h	20 g/h	25 g/h
Maximum treated pool volume (Temperate up to 28°C, filtration 8h/day)	50 m ³	90 m ³	110 m ³	50 m ³	90 m ³	110 m ³
pH regulation (high quality glass sensor)				Standard, with embedded pH pump		
ORP regulation (high quality gold glass sensor)				Optional ORP kit, code 77387		
Recommended salinity (min-max threshold)	4 g/L (3,5 - 10 g/L)					
Salinity reading	Yes					
Water temperature reading	Yes					
Boost mode	Yes (100% chlorination for 24 hours)					
Cover mode	Reduced chlorination when pool cover is closed (adjustable)					
Flow safety	Yes, mechanical flow switch					
Connectivity & App control	Bluetooth & Wi-Fi, remote control with Fluidra Pool app					
Warranty (power pack & cell)	2 years, unconditional					
Warranty (sensors)	2 years (pH sensor) / 1 year (ORP gold sensor)					

Salt chlorinators are an automatic and efficient disinfection solution. They are easy to use, offer complete water treatment and reduce maintenance.

ASSOCIATED PRODUCTS



ORP Kit (for the evolutive version)



Locking ring wrench



Winterizing cap

2 YEAR
UNCONDITIONAL
WARRANTY