

LUMIPLUS ESSENTIAL PAR56

Niche mounted projector. Compatible with AstralPool's niches.




A E		70870	70870WW	
	Color	White	Warm White	
	Consumption	14,5 W (20 VA)		
	Luminous flux	1.485 lm		
	Temp. Color	5.700 K	3.000 K	

A G		75435	75777	75778
	Color	RGB	RGB RC1100	
	Consumption	22 W (29 VA)		
	Luminous flux	1.100 lm		
	Remote Control	Not included	Included	Not included

Control	Can be controlled by push-button 32458, LumiPlus Range Extender 64633 + RC1100 remote controller 75773 or LumiPlus Connect controller 76290.		Works with remote control 75773.	
---------	----------------------------------------------------------------------------------------------------------------------------------------------	--	----------------------------------	--

VOLTAGE:	12 V AC
FREQUENCY:	50/60 Hz
SERVICE LIFE:	L70-50,000 h
MAX. WATER TEMPERATURE:	40 °C
MAX. INSTALLATION DEPTH:	2 m
MAXIMUM WATER TREATMENT VALUES:	Chlorine: 2 mg/l Bromine: 5 mg/l Salt chlorinator (NaCl): 6 g/l Pool water pH: 7.2 and 7.6
ACCESSORIES & COMPATIBLE NICHES:	Compatible with any PAR56 projector
CABLE:	2.5 m. H07RN-F 2 x 1 mm ²
MATERIALS:	Polyamide



PACKAGING AND PALLETIZATION

Volume/Single box (m ³)	0,015
Weight/Single box (kg)	3,4
Units/Standard box	4
Volume/Standard box (m ³)	0.069
Weight/Standard box (kg)	13,6
Units/Pallet	60
Volume/Pallet (m ³)	2,880
Weight/Pallet (kg)	212,56

