

## TECHNICAL DATA SHEET

### RENOLIT ALKORPLUS MEK SOLVENT - Type 81024000

#### Application:

RENOLIT ALKORPLUS MEK solvent (Methyl ethyl ketone or Butanone) is used to achieve correct viscosity of sealants manufactured with MEK solvent. These products leave the factory with the correct viscosity, but as they are manufactured based on volatile solvents, their viscosity increases over time. To reduce it, add a small amount of MEK to the polyethylene bottle containing the sealant. This product is suitable for 81022 (XTREME®), 81023 (TOUCH), 81020 (VOGUE) and 81024 sealants.

#### Technical Data:

- Base: Methyl ethyl ketone
- Color: Transparent
- Viscosity: Approx. 0,42 mPa·s at 20 °C
- Specific Density: Approx. 0,805 +/- 0,01 g/cm<sup>3</sup>
- Flash Point: < 21°C (Highly flammable liquid and vapors)
- Toxicity: Causes eye and mucous membrane and respiratory irritation.

#### Consumption:

Consumption depends directly on prior sealant conditions, on the characteristics of the work and on environmental conditions.

#### Packaging:

Metallic Cans of 900 g / 1 Liter. Six cans in a box.

#### Shelf Life:

3 years.

#### Caution:

Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Read the label and safety data sheet before use. Keep away from sources of heat, sparks, open flames or hot surfaces. - Do not smoke. Avoid breathing vapours. Immediately flush with plenty of water while keeping eyelids open for at least 15 minutes, GET MEDICAL ATTENTION IMMEDIATELY. Avoid release to the environment.



RENOLIT ALKORPLAN

**Storage:**

Follow the instructions relating to inflammable products, refer to the text on the label and take into consideration the data given on the safety sheet, which is available on request.

**For more information:**

Read MSDS.