



Taylor Water Technologies LLC  
31 Loveton Circle  
Sparks, Maryland 21152  
T. 800.837.8548 | F. 410.771.4291  
**TaylorTechnologies.com**

## Technical Data Sheet

---

### 1. Product

76678 – CTX Pro 6 IN 1

### 2. Instructions for use

#### 01/REMOVE

With dry hands, open cap and remove a test strip.

#### 02/DIP

For best results, use test strip away from skimmers or returns. Dip strip at wrist depth and remove with pads facing up. DO NOT shake off excess water. Hold strip level for 20 SECONDS.

#### 03/READ

Compare to colour chart.

Read in order: FC/Br – pH – TA – TH – CYA

### 3. Measuring range

Free Chlorine (FC) ppm: 0, 1, 2, 3, 5, 10

Bromine (Br) ppm: 0, 2, 4, 6, 10, 20

pH: 6.4, 6.8, 7.2, 7.5, 7.8, 8.4

Total Alkalinity (TA) ppm: 0, 40, 80, 120, 180, 240

Total Hardness (TH) ppm: 0, 100, 150, 300, 800

Cyanuric Acid (CYA) ppm: 0, 30-60, 100, 150, 300

See label for color chart.

### 4. Application

Free chlorine, total chlorine or total bromine, pH total alkalinity, total hardness and cyanuric acid test strips for testing in pool and spa water

### 5. Shelf Life

24 months from manufacturing date

### 6. Contents

50 test strips

### 7. Notes

Test water should be within IDEAL range listed on back of bottle. Keep cap closed after removing a strip to prevent moisture from entering the bottle. TEST TWICE WEEKLY. STORE AT ROOM TEMPERATURE.