

TECHNICAL SPECIFICATIONS ASTRALPOOL UV-C

| Reference | 77304 | 77305 |
|-------------------------------------|--------------------------|--------------------------|
| Description | UV-C 60W SHORT | UV-C 80 W |
| Rec. Flow for 30 mJ/cm ² | 12 m ³ /h | 16 m ³ /h |
| Max. Pressure | 0.25 MPa (2,5 bar) | 0.25 MPa (2,5 bar) |
| Max. Flow | 23 m ³ /h | 23 m ³ /h |
| Diameter Unit ø | 70 mm | 70 mm |
| Length Unit | 75 cm | 100 cm |
| Weight (empty) | 4.1 kg | 5.1 kg |
| Weight (full) | 6.3 kg | 8.2 kg |
| Diameter IN-OUTLET ø | 63 mm / 50 mm / 1 ½" | 63 mm / 50 mm / 1 ½" |
| Housing | Stainless Steel / DUPLEX | Stainless steel / DUPLEX |
| IP rating | IPX5 | IPX5 |
| Electronic Ballast | 230V AC 50/60 Hz | 230V AC 50/60 Hz |
| Maximum Current | 0,57 A | 0,57 A |
| Lamp Wattage | 60 W | 80 W |
| Lifespan Lamp | 9000 h | 9000 h |
| Flow Switch | - | - |
| Water Temperature | 1°C – 40°C | 1°C – 40°C |
| Ambient Temperature | 1°C – 40°C | 1°C – 40°C |



77304



77305

Fluidra Global Distribution S.L.U.

Avda. Alcalde Barnils 69, 08174 Sant Cugat (Barcelona), Spain

Tel. +34 93 713 3718

www.astralpool.com