



AUTONOMOUS AND
SECURED CHLORINE
REGULATION

GenChlor

1 AUTOMATIC CHLORINE DOSAGE

GenChlor continually measures water quality and if necessary, makes **fully automated adjustments in the liquid chlorine dosage, without any settings required.**



2 ACCURATE DOSING

GenChlor injects the precise quantity of chlorine thanks to its unique, adaptive dosing technology, ensuring **optimal disinfection** with a **minimum amount of product.**



3 ANTI-OVERDOSE PROTECTION

Thanks to its exclusive safety system, GenChlor **protects against any risk of chlorine overdosing**, ensuring **optimal bathing quality.**



SPECIFICATIONS



'Boost' function

Increases chlorine dosing for intensive bathing sessions or stormy weather.



Super simple

Easy to configure on the LCD screen.



Automatic dosage adjustment

No setting required.



Compatibility

Ideal combination with the Zodiac® GenpH automatic pH regulator.

FOR WHICH TYPE OF POOLS?

1 FOR IN-GROUND POOLS



2 OUTDOOR POOLS FROM 20 TO 150 M³



STANDARD FEATURES



Redox Sensor



Buffer solution



Plumbing kit



Wall mounting kit

TECHNICAL INFORMATION

Volume of water treated (min - max)	20 - 150 m ³
Dosage	Liquid chlorine
User Interface	1-line, backlit LCD screen
Languages	6 (FR-EN-ES-DE-IT-NL)
Calibration	Semi-automatic, one-step (buffer solution included)
Setpoints	Factory settings: ORP = 650 mV
Safety	Configurable 'OFA' three-level over-dosage safety mechanism (settings from 0 to 6 hours, default 4 hours) Level sensor on correction product tank (on the fume-resistant intake tube)
Sensor position	Vertical
Fixing collar	For DN 50 pipes (factory) or DN 63 (accessory)
Protection rating	IP65
50 Hz power supply	220-240 VAC

AVAILABLE ACCESSORIES



Patented POD kit

For grouping GenChlor and GenpH measurement sensors, if used together. Ensures the most accurate measurement.



Anode earth kit

enabling a more stable chlorine measurement.

Zodiac® pH regulators are stand-alone solutions that provide **automated chlorination**, and maintain an **optimal chlorine level**, whatever the type of disinfection.

2 YEAR
WARRANTY*

*Excluding consumables guaranteed for 1 year (sensor, buffer solutions, peristaltic tube, one-way valve).

RCS Paris 395 068 679 - A better life = une vie meilleure - © Crédits photos : ZODIAC® - ZODIAC® is a registered trademark of Zodiac International, S.A.S.U., used under license