

# PERISTALTIC DOSING PUMP

## Double Pumps \_ Pool Basic Pro



The PoolBasic Display is a high level professional pump suitable for use in Swimming Pool markets.



### TECHNICAL CHARACTERISTICS

- **FLOW RATES**
  - 1,5 l/h; 5 l/h
- **BACK PRESSURE**
  - 1,5 bar
- **POWER SUPPLY**
  - 230±Vac - 50/60 Hz - 7W or 12,5 W with galvanized insulation
- **MATERIALS**
  - **ENCLOSURE:** PP with fiber glass
  - **PUMP HEAD:** PP
  - **TUBES:** Santoprene

### FEATURES

- IP 65 level Protection
- Alphanumeric Display
- Wheel holder mounted on ball bearing, for a longer pump life
- New motors with extended life time
- Snap on transparent cover
- Two roller PTFE body, for a more proportional dosing and an extended lifetime

- **DOSING**
  - proportional mode
- **MOTORS**
  - Brushed DC Motors
- **pH or Redox MEASURE**
  - 0 ÷14 pH measure
  - 0 ÷1000 Redox measure
- **FUNCTIONS**
  - Constant dosing by pH feedback measure

# PERISTALTIC DOSING PUMP

## Double Pumps \_ Pool Basic Pro



### PUMP KEY CODE

1	MODEL							
S	Seko							
2,3		MEASURE						
	PM	Constant dosing pump by Ph + Redox measure feedback						
	XD	Constant dosing pump byPh + Rx + Cd measure feedback						
	XC	Constant dosing pump byPh + Rx + CI measure feedback						
4, 5			VERSION					
	BA	BASIC						
6				TYPE				
	S	STANDARD						
7					PUMP			
	P	PERISTAL.						
8						POWER SUPPLY		
	A	230VAC						
9								FLOWRATE
	0	1,5 LITRI						
	5	5 LITRI						
10,11, 12							Free	
	000	Free						
S	PH	BA	S	P	A	0	000	

### RESUME TABLE

CODE					VALUES			
MODEL	MEASURE	VERSION	TYPE	PUMP	POWER	FLOWRATE	TUBES	INSTALLATION KIT
S	PM	BA	S	P	230VAC	1,5 - 5	Santoprene	INCLUDED
S	XD	BA	S	P	230VAC	1,5 - 5	Santoprene	INCLUDED
S	XC	BA	S	P	230VAC	1,5 - 5	Santoprene	INCLUDED

# PERISTALTIC DOSING PUMP

## Double Pumps \_ Pool Basic Pro



### DIMENSIONS

