

Flexible hose in PVC



- Hose made from flexible PVC, with a rigid spiral, practically undeformable and anti-chock.
- Smooth surface, both in the outside and in the inside
- External diameters specially designed for an easy fit in PVC and PE fittings.
- Suitable for a hermetic and resistant glued at 30 bar pressure maximum.
- Temperature range from -10°C to $+60^{\circ}\text{C}$.
- Great resistance to sewage waters, to a wide range of chemical products and soaps.
- Certificated by the Spanish Normalization Association, AENOR, according to the Quality Norm UNE EN ISO 3994
- Draining, hydro-sanitary conductions, swimming pool cleaning circuits, hydro-massage pools, sewing, air conditioning installations.

CODE	ROLL m	INT. DIAM. mm	EXT. DIAM. mm	WEIGHT g/m	MAX. PRESSURE bar	MINIMUM BURST PRESSURE bar	BENDING RADIUS mm
34586	50	13	16	100	7	22	39
28570	50	16	20	155	7	22	48
28571	50	20	25	240	7	22	60
28572	50	27	32	334	5	16	81
28573	50	35	40	400	5	16	105
28574	50	43	50	685	5	16	129
28575	25	55	63	1.000	5	16	165
34588	25	65	75	1.400	4	12,5	195