







# FloPro™

**A RANGE** OF LONG-LASTING AND EFFICIENT PUMPS.



# 1 BUILT TO LAST

FloPro™ pumps are designed with **corrosion-resistant materials**. The body of the pump is made of very thick glass-reinforced polypropylene, which makes it long-lasting and silent.



# 2 HIGH PERFORMANCE

Equipped with highly energy-efficient asynchronous motors, the range is available in 9 models (from 0.5 to 2.0 HP) to meet the needs of most pools.



### BENEFITS OF THE FIOPro™ PLATFORM



#### Easy to install, even as a replacement

Thanks to the "Easy Retrofit" system, pumps can be installed without changing the piping. So, they are compatible with most existing installations.



#### Easy maintenance


A pre-filter basket that is up to 117% larger means more debris can be captured before the filter needs to be cleaned.




| TECHNICAL INFORMATION      |  |             |             |             |             |             |             |             |             |
|----------------------------|--|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
|                            | FloPro 50M   | FloPro 75M  | FloPro 75T  | FloPro 100M | FloPro 100T | FloPro 150M | FloPro 150T | FloPro 200M | FloPro 200T |
| 50 Hz power supply         | 220-240 VAC  | 220-240 VAC | 380-420 VAC | 220-240 VAC | 380-420 VAC | 220-240 VAC | 380-420 VAC | 220-240 VAC | 380-420 VAC |
| Power in kW (P2)           | 0.37 kW  | 0.55 kW     |             | 0.75 kW     |             | 1.1 kW      |             | 1.5 kW      |             |
| Power in HP (P2)           | 0.5 HP   | 0.75 HP     |             | 1.0 HP      |             | 1.5 HP      |             | 2.0 HP      |             |
| Flow rate at 10 m head     | 10.3 m³/h  | 13.2 m³/h   |             | 15.8 m³/h   |             | 20.8 m³/h   |             | 27.0 m³/h   |             |
| Maximum flow rate          | 16.8 m³/h  | 18.6 m³/h   |             | 22.9 m³/h   |             | 27.4 m³/h   |             | 35.5 m³/h   |             |
| Maximum Manometric<br>head | 17.8 m   | 20.7 m      |             | 21.5 m      |             | 22.3 m      |             | 24.5 m      |             |
| Length (A)                 | 58.3 cm  | 58.3 cm     | 54.3 cm     | 58.3 cm     | 55.3 cm     | 58.3 cm     | 56.3 cm     | 58.3 cm     | 58.3 cm     |
| Motor type                 | Asynchronous motor, class F insulation, stainless steel shaft and bearings |             |             |             |             |             |             |             |             |
| Speed                      | 2,850 RPM  |             |             |             |             |             |             |             |             |
| Usage                      | Fresh water and salt water up to 6 g/L (6,000 ppm)                         |             |             |             |             |             |             |             |             |
| Pre-filter basket volume   | 2.6 L  |             |             |             |             |             |             |             |             |

# **BENEFITS**

- 63/50 mm union connectors provided
- 2 optional pump bases for easy installation
- Compatible with salt water



# PERFORMANCE GRAPHS



# **STANDARD FEATURES**



63/50 mm union tailpieces

# FOR WHICH TYPE OF POOLS?

1 ALL TYPES OF SWIMMING POOL



2 POOLS UP TO 150 M<sup>3</sup>



# **ACCESSORIES**







Thick pump base

3 YEAR WARRANTY

RCS Paris 395 068 679 - © Crédits photos : Zodiac® - Zodiac® is a registered trademark of Zodiac International, S.A.S.U., used under license - www.le-fil.fr - Ref. : WL15620

www.zodiac-poolcare.com

