



VERSATILE SALT TREATMENT

eXPERT

1 EASE OF USE

With its large touchscreen, eXPERT is **fast to set up and start up**. Your pool's status can be checked at-a-glance on the **user-friendly display**.

2 MAXIMUM VERSATILITY

Available in a **wide range of options to treat pool volumes** up to 180 m³, eXPERT guarantees **long-lasting water treatment** thanks to a long-lasting cell.

3 AUTONOMOUS WATER QUALITY MANAGEMENT

eXPERT provides **full water treatment features** with **water balance management** (pH regulation) and **automatic regulation of chlorination** (ORP regulation)*.









CHARACTERISTICS



Large intuitive display Easy pool control with the large touchscreen.



Minimal maintenance Self-cleaning electrodes using polarity reversal.

STOP

Safe system Automatic stop if there is no flow in the cell.



Waterproof

Water-resistant 'IP65-rated' control unit.



Unconditional warranty

On the power pack and the cell, regardless on the how the damage is caused.

WHICH TYPE OF POOLS?

1 ALL POOL TYPES



2 POOLS UP TO 180M³ (TEMPERATE CLIMATE, FILTRATION 8 H/DAY)



eXPERT - 3 SOLUTIONS



1. Chlorinator only



2. Chlorinator + pH regulation In addition to automatically disinfecting the pool, this solution automatically measures and regulates the pH level of the water. If necessary, corrective product is injected.



3. Chlorinator + pH regulation and ORP This solution automatically measures and regulates the water's pH and chlorination (ORP method) for a complete water treatment.

TECHNICAL INFORMATION					
MODELS	eXPERT				
Chlorine production (g/h)	7	12	21	30	40
Volume of water treated (temperate climate, filtration 8 h/day)	30	50	90	140	180
User interface	Backlit touchscreen + LCD				
Operating mode(s)	Normal, Cover Mode, Boost Mode (Adjustable Cover Mode from 0 to 90%, default 10%)				
Connectivity	Can be controlled remotely with the NN smartphone application (if linked to the Connect & Go pool automation system)				
pH regulation	Yes - eXPERT pH models pH dosing pump: 1.5 L/h pH sensor: high quality glass				
pH/ORP regulation	Yes - eXPERT pH/ORP models pH dosing pump: 1.5 L/h pH sensor: high quality glass ORP sensor: high quality glass and special gold tip for salt water				
Reverse polarity	Yes (adjustable)				
Recommended minimum salt levels	4 g/L				
Safety	Water temperature: Value displayed on the screen and indicator light if the water is too cold				
	Salinity: Value displayed on the screen and indicator light if the level is too low or too high				
	Flow in the cell: mechanical flow switch that stops production if there is not enough water				
	pH and ORP value(s) (depending on the model): indicator light(s) if the levels are outside the normal range				
Supply voltage	230 Vac - 50/60 Hz				

Salt chlorinators are an **automatic and efficient disinfection solution.** They are **easy to use,** provide complete water treatment and **reduce maintenance.**



RCS Lyon 395 068 679 - © Crédits photos : ZODIAC® - ZODIAC® is a registered trademark of Zodiac International, S.A.S.U., used under license



www.zodiac.com