

ctx379 MULTIACTION 5 250G



Multi-action chlorine treatment for pool maintenance

- Slow and continuous dissolution.
- Disinfection, anti-algae, flocculant, coagulant, chlorine stabilizer.

TABLET	EFFICACY	ALL, SPECIAL CARTRIDGE FILTERS	DOSAGE
250g	WEEKLY		1 /25m ³

PROPERTIES

Appearance	Solid in tablets (250g)
Colour	White
pH (1%)	2,5 - 3

CHARACTERISTICS

Solid compound in tablets of 250g, especially thought to make that with its only addition to the water in the swimming pool, you manage to eliminate all the bacteria, viruses and microorganisms in general. It prevents the weeds from developing and helps to keep the water clear and transparent.

Product specially formulated for the treatment of swimming pool water with filters of cartridge and diatom since it does not clog the filters. It also has an anti scale effect, reduces the consumption of chemical products to maintain the pH value of the water and acts as a stabilizer of the chlorine it generates.

INSTRUCTIONS FOR USE

Always adjust the pH before adding chlorine to the water, to make it as effective as possible.

Introduce the necessary product of ctx379 Multiaction 5 (special cartridge filters and diatoms) doses inside the skimmers. Connect the filtering equipment after and you will have the product dissolved in the water, because water will be flowing through the skimmers.

It is essential that the entire volume of pool water is recirculated through the scrubber equipment daily. Free residual chlorine should be between 0.5-2 mg./l. Value is easily measured using a chlorine and pH analyzer. This control should be at least 2 times a day.

Recommendations:

To keep pace with fully open skimmers and water in the sump during the filtration process.

It is advisable to introduce the dose of ctx379 Multiaction 5 (special cartridge filters and diatoms) when the tablets inside the skimmers have been reduced to 10% of their original weight.

ctx
pro

The caring formula
ctxprofessional.com

DOSAGE

Initial treatment: Add 15 grs. of ClorShock for m³ of water. Wait for two hours before adjusting the pH level between 7,2 - 7,6 using either ctx 10 pH Minus solid or ctx 20 pH Plus solid.

The initial treatment will have to be repeated whenever you notice a lack of transparency in the water.

Maintenance treatment: Once we have the water pH adjusted, add 1 tablet of product for every 20 m³ water during 7-10 days.

These doses are the ones suggested and can be modified according to the own characteristics of every swimming pool, climate, etc.