

## SALT WATER CHLORINATORS

# pH Link & Dual Link









- + Automatic regulation
- + Accurate & easy reading (high quality glass sensor in a POD)















pH 4 and pH 7 buffer solutions x3



470 mV ORP buffer solutions x3





22 mm hole



Plumbing kit



POD Kit

FOR WHICH POOL?					
Model	pH Link	Dual Link			
Volume of treated water (temperate climate)	160 m³	Depending on the chlorinator's output power			
Dosage	Acid	Acid			

DESCRIPTION						
Model	pH Link	Dual Link				
Standard Model	WW000176	WW000177				
User interface	Device's interface (4-line, backlit LCD screen)					
Calibration	Semi-automatic at 2 points pH 4 and pH 7 & ORP 470 mV (buffer solutions included)					
Setpoints	Factory setting: pH = 7,2 / ORP = 700 mV					
Sensor position	Vertical, on the POD (provided)					
Safety	Overdosing safety, low measures, unplugged sensor, broken sensor (pH Link)					

TECHNICAL SPECIFICATIONS					
Model	pH Link	Dual Link			
Sensor type pH or ORP	Combined sensor, simple-junction and simple-porous, Ø12 mm glass body				
Reading scale	0,0 -12,0 pH	100 - 1000 mV			
leading accuracy	0,1 pH	10 mV			
ensor Tolerances	0-60 °C, water speed ≤ 2 m/s				
aximum counter pressure njection point)	1,5 bar				
Peristaltic pH pump flow	1,2 L/h				
ell size (L x w x h)	30,5 x 18,1 x 11,5 cm				

<sup>\*</sup> Excluding consumable parts that have 1 year warranty (ORP sensor, buffer solution, peristaltic tube, one-way valve)




#### INSTALLATION


- Connect the unit directly to the chlorinator's control unit.
- The distance between the module and the sensor cell is 1,5m (3 m extension cable is optional).
- The POD MUST be installed so that the sensor(s) is/are vertical, to ensure accurate measurement.

pH Link & Dual Link Modules installation diagram:

## Kit POD on line:



## POD Kit in by-pass:



OPTIONAL ACCESSORIES						
Intake pipe	pH 4 and pH 7 buffer solutions (x6 + x6)	470 mV ORP buffer solutions (x6)	Winterizing cap	3m BNC cable extension	Earthing anode	
R0808000	R0824400	R0824500	R0770100	R0635800	R0673800	