

## ctx800 INHIBICAL



**Avoids lime scale build-up caused by the use of liquid chlorine that clogs dosing systems (dosing pumps, tubes, etc.).**

- Prevents corrosion of the metal parts of the pool.

LIQUID	EFFICACY	POOLS WITH LIQUID CHLORINE	DOSAGE
	DAILY		500ml /50l

### PROPERTIES

Appearance	Liquid
Colour	Slightly yellow
Density	1,15 - 1,19 g/cm <sup>3</sup>

### CHARACTERISTICS

Inhibiting and dispersing liquid additive, which prevents and avoids incrustations due to the carbonation of Sodium Hypochlorite (chlorine bleach) that clog and plug dosing systems (dosing pumps, injection fittings, pipes, etc.).

On the other hand, this product has a corrosion inhibiting effect on the metallic parts of the dosing pumps.

### INSTRUCTIONS FOR USE

Add the product directly to the dosing container containing the chlorine bleach, each time the Sodium Hypochlorite is replaced. Once added, stir to homogenize the mixture.

It is not necessary to dilute the product before use.

### DOSAGE

Add 0.5 Lts. of product for each 50 Lts. of Sodium Hypochlorite (chlorine bleach).

These doses are for guidance only and may be modified according to the characteristics of each pool, climate, etc.

**ctx**  
pro

The caring formula

ctxprofessional.com