



2019 Products for GRE



Contents

3 CLEANING

ELECTRICAL CLEANERS p. 4

TORNAX™ RANGE p. 7

- OT 2100 p. 8
- OT 2190 p. 9
- GT 2120 p. 10
- OT 3200 p. 11
- OT 3290 p. 12
- GT 3220 p. 13
- OT 3300 p. 14

CYCLONX™ RANGE p. 15

- RC 4300 p. 16

VORTEX™ RANGE p. 17

- OV 3450 p. 18
- OV 3480 p. 19
- GV 3420 p. 20
- OV 3505 p. 21
- RV 4390 TILE p. 22
- RV 4550 TILE p. 23
- GV 3520 p. 24

HYDRAULIC CLEANERS p. 25

- R3 p. 26
- MX6™ p. 27
- MX8™ p. 28
- Kontiki™2 p. 29
- T3® p. 30
- T5® Duo p. 31

32 WATER TREATMENT

PH REGULATOR p. 33

- pH clever p. 34

SALT WATER CHLORINATOR p. 36

- Gensalt OE p. 37



Cleaning

ELECTRICAL CLEANERS

TORNAX™ RANGE

- OT 2100
- OT 2190
- GT 2120
- OT 3200
- OT 3290
- GT 3220
- OT 3300

CYCLONX™ RANGE

- RC 4300

VORTEX™ RANGE

- OV 3450
- OV 3480
- GV 3420
- OV 3505
- RV 4390 TILE
- RV 4550 TILE
- GV 3520

p. 4

p. 7

- p. 8
- p. 9
- p. 10
- p. 11
- p. 12
- p. 13
- p. 14

p. 15

- p. 16

p. 17

- p. 18
- p. 19
- p. 20
- p. 21
- p. 22
- p. 23
- p. 24

HYDRAULIC CLEANERS

- R3
- MX6™
- MX8™
- Kontiki™2
- T3®
- T5®Duo

p. 25

- p. 26
- p. 27
- p. 28
- p. 29
- p. 30
- p. 31



CLEANING

> 2 TECHNOLOGIES FOR SWIMMING POOL CLEANING

To clean a pool as well as possible, multiple parameters are considered in **the choice of cleaning equipment**: shape and lining of the pool, standard of cleaning, volume to be covered, etc.

High technology Zodiac® cleaners match the different features of a pool, the cleaning time and every budget.

2 types of technologies are currently available:
electric cleaning and hydraulic cleaning.

> ZODIAC® ELECTRIC ROBOTIC CLEANERS: A HIGH-PERFORMANCE, STAND-ALONE SYSTEM

Separate from the filtration system and simply connected to the mains power, Plug&Play is **stand-alone equipment**.

With no action required and **programmable** (cleaning time, area to be covered, etc.), they reach every corner of the pool, climb the walls, clean the water line and collect impurities in their own filter basket.

There are different models for all types of pools.



> ZODIAC® HYDRAULIC ROBOTIC CLEANERS: A SIMPLE AND AFFORDABLE SOLUTION

Hydraulic robotic cleaners can be easily installed in the pool filtration system. In fact, they work on the energy produced by your pump.

Vacuum cleaners capture debris by suction and accumulate it in the pump pre-filter.

More affordable than electric cleaners, hydraulic cleaners are connected to a pool vacuum point or a skimmer and are **particularly suitable for the smallest pools** (with a flat floor or gentle slope and above-ground pools).

To optimise the efficiency of these accessories, it is essential to **ensure they are compatible with the pool lining**, filtration equipment, environment, etc.



> **ELECTRIC ROBOT CLEANERS**

A stand-alone and efficient solution

The electric robots combine **the best of Zodiac® technology.**

Thanks to the embedded cyclone suction, a patented Zodiac® technology, **the cleaning performance is maintained throughout the cleaning cycle.** They even capture the finest debris without filter clogging.

Separate from the filtration system, these Plug&Play devices trap debris in their own filter basket, making them stand-alone.



> **TORNAX, EFFICIENCY PURE & SIMPLE**

The Tornax robotic cleaner guarantees **efficient cleaning** of your pool, completely autonomously, thanks to its smart movement and its rotating brush, which removes all debris before collecting it. Tornax is the **lightest** (5.5 kg) of all the Zodiac® robotic cleaners.

It is feather-light, meaning it is quick, easy and **effortless** to operate. Tornax is designed not only to be easy to use but also easy to maintain, as the filter can be accessed from the top so it can be rinsed without touching the debris.



> **CYCLONX™, CONCENTRATED TECHNOLOGY**

Robotic cleaners in the CyclonX™ PRO range provide optimum cleaning of the pool, thanks to their pre-programmed cycles, among which a **Deep Clean** cycle to clean the pool floor thoroughly. Thanks to their large capacity filter (up to 3.7 L) and their wide suction inlets, all debris is collected. The filter can be easily cleaned using the **Push'n'Go™** function, a patented Zodiac® innovation that helps raise the filter basket handle with the push of a button.



> **VORTEX™, ULTIMATE POWER**

Robotic cleaners from the Vortex™ range are equipped with patented extra-powerful and constant cyclonic suction. Their filter is particularly easy to access and maintain. They also have an extra-large suction capacity, thanks to their 4.7 L filter basket and their wide suction inlet.



CLEANING


> ELECTRIC CLEANERS

A stand-alone and efficient solution

COMPARATIVE TABLE OF RANGES	GT 2120	GT 3220	RC 4300	GV 3420	GV 3520
Warranty	2 years	2 years	2 years	2 years	2 years
Cable length	14 m	16,5 m	18 m	18 m	18 m
Swimming pool dimensions	max 8 x 4 m	max 9 x 4 m	max 12 x 6 m	max 12 x 6 m	max 12 x 6 m
Cyclone suction				•	•
Floor only	•		•	•	•
Floor / walls		•			
Floor / walls / water line			•	•	•
Trolley	optional	optional	optional	•	•
Remote control					•
Rigid filter canister	3 L	3 L	3,7 L	5 L	5 L

STANDARD INSTALLATION

- Place the power pack at least 3.5 m from the edge of the pool.
- Connect the cleaner to the power pack.
- Connect the power pack to a mains socket protected by a 30 mA residual current differential circuit breaker (low voltage operation).
- The user can adjust the cleaning cycle using a control unit.



> CYCLONE SUCTION


EXCLUSIVITE
ZODIAC®
EXCLUSIVITE

PATENTED TECHNOLOGY FOR POWERFUL CLEANING

> HOW DOES IT WORK?

Zodiac® engineers have created the first cyclone suction pool cleaners.

The high-power vortex inside the filter keeps debris in suspension, thereby reducing filter clogging.



Cyclonic suction:
keeps debris in suspension

Inclined motor



Cleans the pool floor
(OT/GT 21)



Cleans floor and walls
(OT/GT 32)



Light for effortless handling



Easy-to-clean filter

TECHNICAL SPECIFICATIONS

	OT 2100	OT 2190	GT 2120	OT 3200	OT 3290	GT 3220
Cleaning areas	Floor only	Floor only	Floor only	Floor / Walls	Floor / Walls	Floor / Walls
Types of pools	8 x 4 m 14m cable	8 x 4 m 14m cable	8 x 4 m 14m cable	9 x 4 m 16,5m cable	9 x 4 m 16,5m cable	9 x 4 m 16,5m cable
	Liner, polyester hull, reinforced PVC, painted concrete, Tiles (dedicated brushes)	Liner, polyester hull, reinforced PVC, painted concrete, Tiles (dedicated brushes)	Liner, polyester hull, reinforced PVC, painted concrete, Tiles (dedicated brushes)	Liner, polyester hull, reinforced PVC, painted concrete, Tiles (dedicated brushes)	Liner, polyester hull, reinforced PVC, painted concrete, Tiles (dedicated brushes)	Liner, polyester hull, reinforced PVC, painted concrete, Tiles (dedicated brushes)
	Rectangular, oval, free shape	Rectangular, oval, free shape	Rectangular, oval, free shape	Rectangular, oval, free shape	Rectangular, oval, free shape	Rectangular, oval, free shape
Filter	3L	3L	3L	3L	3L	3L
	Rigid Filter canister with access over the cleaner	Rigid Filter canister with access over the cleaner	Rigid Filter canister with access over the cleaner	Rigid Filter canister with access over the cleaner	Rigid Filter canister with access over the cleaner	Rigid Filter canister with access over the cleaner
	Opaque window	Opaque window	Opaque window	Transparent window	Transparent window	Transparent window
	Filter canister 100µ	Filter canister 100µ	Filter canister 100µ	Filter canister 100µ	Filter canister 100µ	Filter canister 100µ
Weight (without cable)	5,5 kg	5,5 kg	5,5 kg	5,5 kg	5,5 kg	5,5 kg
Weight (when removing from water)	13 kg	13 kg	13 kg	13 kg	13 kg	13 kg
Length of cleaning cycles	1 cycle / 2h	1 cycle / 2h	1 cycle / 2h	1 cycle / 2h30	1 cycle / 2h30	1 cycle / 2h30
Warranty	2 years	2 years	2 years	2 years	2 years	2 years
Transport cart	No	No	No	No	No	No

*With specific brushes for optimal operation in certain tiled pools.



OT 2100 TORNAX

Pool Cleaners > Electrics > OT 2100 TORNAX

2 YEAR WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor cleaning
- + Lightweight for effortless handling
- + Easy clean filter



REFERENCE

Product reference: WR000094

ACCESSORIES INCLUDED IN THE PACK

		
Control box	Fine Filter canister 100µ	Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 8 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor
Number / Length of cleaning cycles	1 cycle - Floor : 2h
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	14 m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	10 kg
Filtration surface and level	480 cm ² / 100µ
Filtration capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

					
	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.



9 317545 022475



OT 2190 TORNAX

Pool Cleaners > Electrics > OT 2190 TORNAX

2 YEAR WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor cleaning
- + Lightweight for effortless handling
- + Easy clean filter



REFERENCE

Product reference: WR000095

ACCESSORIES INCLUDED IN THE PACK



Control box



Fine Filter canister 100µ



Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 8 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor
Number / Length of cleaning cycles	1 cycle - Floor : 2h
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	14 m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	10 kg
Filtering surface and level	480 cm ² / 100µ
Filtering capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.



9 317545 021966



GT 2120 TORNAX

Pool Cleaners > Electrics > GT 2120 TORNAX

2 YEAR
WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor cleaning
- + Lightweight for effortless handling
- + Easy clean filter



**NEW FOR
2019**

REFERENCE

Product reference: WR000187

ACCESSORIES INCLUDED IN THE PACK

		
Control box	Fine Filter canister 100µ	Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 8 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor
Number / Length of cleaning cycles	1 cycle - Floor : 2h
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Transparent window	No
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	14 m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	10 kg
Filtering surface and level	480 cm ² / 100µ
Filtering capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

					
	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.



9 317545 059051



OT 3200 TORNAX

Pool Cleaners > Electrics > OT 3200 TORNAX

2 YEAR WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor and walls cleaning
- + Lightweight for effortless handling
- + Easy clean filter



REFERENCE

Product reference: WR000096

ACCESSORIES INCLUDED IN THE PACK

		
Control box	Fine Filter canister 100µ	Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 9 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor / walls
Number / Length of cleaning cycles	1 cycle - Floor / walls : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	16,5m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	11 kg
Filtering surface and level	480 cm ² / 100µ
Filtering capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

					
	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.





OT 3290 TORNAX

Pool Cleaners > Electrics > OT 3290 TORNAX

2 YEAR
WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor and walls cleaning
- + Lightweight for effortless handling
- + Easy clean filter



REFERENCE

Product reference: WR000097

ACCESSORIES INCLUDED IN THE PACK

		
Control box	Fine Filter canister 100µ	Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 9 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor / walls
Number / Length of cleaning cycles	1 cycle - Floor / walls : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	16,5m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	11 kg
Filtration surface and level	480 cm ² / 100µ
Filtration capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

					
Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)	
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.



9 317545 021973



GT 3220 TORNAX

Pool Cleaners > Electrics > GT 3220 TORNAX

2 YEAR WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor and walls cleaning
- + Lightweight for effortless handling
- + Easy clean filter



NEW FOR 2019

REFERENCE

Product reference: WR000189

ACCESSORIES INCLUDED IN THE PACK



Control box



Fine Filter canister 100µ



Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 9 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor / walls
Number / Length of cleaning cycles	1 cycle - Floor / walls : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Transparent window	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	16,5m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	11 kg
Filtering surface and level	480 cm ² / 100µ
Filtering capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.



9 317545 059075



OT 3300 TORNAX

Pool Cleaners > Electrics > OT 3300 TORNAX

2 YEAR
WARRANTY

EFFICIENCY, PURE AND SIMPLE

- + Efficient floor and walls cleaning
- + Lightweight for effortless handling
- + Easy clean filter
- + 2 cycles : floor only and floor/walls



REFERENCE PRICE

Product reference: WR000146

ACCESSORIES INCLUDED IN THE PACK

		
Control box	Fine Filter canister 100µ	Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 9 x 4 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Liner, polyester hull, reinforced PVC, painted concrete, Tiles *

DESCRIPTION

Cleaning areas	Floor / walls
Number / Length of cleaning cycles	2 cycles : - Floor : 2h - Floor / parois : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Transparent window	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	36

TECHNICAL SPECIFICATIONS

Number of motors	2
Control box supply	100-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	100 W
Cable length	16,5m
Cleaner size (L x W x h)	37 x 29 x 30 cm
Packaging size (L x W x h)	56 x 37 x 38 cm
Cleaner weight	5,5 kg
Packaging weight	11 kg
Filtering surface and level	480 cm ² / 100µ
Filtering capacity	3 L
Theoretical cleaning width	17 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

					
	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Trolley	Special tile brush (unit)
Reference	R0763100	R0762900	R0763000	R0767600	R0774900

*For optimal cleaner behavior in some tile pools, it might be necessary to use the specific tile brush accessory.





ELECTRIC CLEANERS

> CYCLONX™ PRO

The essentials of Zodiac® technology

PUSH'N'GO™ | Push'n'Go™ system
(easy access to the filter)

Filter basket
and large capacity (3.7 L)

Caterpillar tracks

Filter basket
and large capacity (3.7 L)

Multiple cleaning areas
(floor, sides, water line)

Control unit

Transport cart
(supplied with the cleaner or as an accessory)

COMPARATIVE TABLE OF THE RANGE

	RC 4300
Swimming pool dimensions	10 x 5 m
Cleaning areas	Floor / walls / water line
Pool surface	Liner, reinforced PVC, painted concrete, Tiles: dedicated brushes kit
Cleaning cycles	2
Cleaning time adjustment	No
Full filter indicator	No
Window of the filter	Opaque
Cable length	15 m
Trolley	No



RC 4300 CYCLONX™ PRO

Pool Cleaners > Electrics > RC 4300 CYCLONX™ PRO

2 YEAR
WARRANTY

CONCENTRATED TECHNOLOGY

- + Optimal cleaning for the floor/walls/water line
- + Large suction capacity
- + Filter access at the push of a button



PUSH'N'GO

REFERENCE

Product reference: WR000020

ACCESSORIES INCLUDED IN THE PACK

		
Control box	Fine Filter canister 100µ	Control box base

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 10 x 5 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Liner, reinforced PVC, painted concrete , polyester hull, Tiles : dedicated brushes kit

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	2 cycles : - Floor «Deep Clean» : 1h30 - Floor / walls / water line : 1h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	Tracks
Transmission	Gear transmission
Brushes	Yes
Lift System	No
Transparent window	No
Full filter indicator	No
Remote control	No
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	20

TECHNICAL SPECIFICATIONS


Number of motors	2
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	15 m
Cleaner size (L x W x h)	41 x 42 x 28 cm
Packaging size (L x W x h)	56 x 56 x 38 cm
Cleaner weight	9 kg
Packaging weight	17,1 kg
Filtering surface and level	850 cm ² / 100µ
Filtering capacity	3,7 L
Theoretical cleaning width	22 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

							
Ultra-fine filter canister 60µ	Large debris filter canister 200µ	Fine filter canister 100µ	Protective cover	Trolley	Kit for polyester hull pools (2 brushes)	Kit for slippery surfaces (2 brushes)	
Reference	R0632602	R0632601	R0632600	R0568100	R0639500	R0697600	R0718600



9 317545 014128




ELECTRIC CLEANERS

> VORTEX™ RANGE

Ultimate power

COMMON FEATURES OF THE RANGE

3 filtration levels available



Vortex™ technology:
cyclone suction
powerful and constant

Blade brushes



Filter basket with easy access
and large capacity (5 L)



Extra-wide
suction inlet

COMPARATIVE TABLE OF THE RANGE

	OV 3450	OV 3480	GV 3420	OV 3505	GV 3520
					
Swimming pool dimensions	12 x 6 m	12 x 6 m	12 x 6 m	12 x 6 m	12 x 6 m
Cleaning areas	Floor only, floor / walls / water line	Floor only, floor / walls / water line	Floor only, floor / walls / water line	Floor only, floor / walls / water line	Floor only, floor / walls / water line
Cleaning cycles	2	2	2	2	2
Programmable power pack - 7 days	No	No	No	No	No
Lift System	No	No	No	No	No
Swivel	No	No	No	No	No
Drive wheels	2	2	2	2	2
Remote control	No	No	No	Yes	Yes
Full filter indicator	No	No	No	No	No
Cable length	18 m	18 m	18 m	18 m	18 m
Guarantee	2 years	2 years	2 years	2 years	2 years



OV 3450 VORTEX™

Pool Cleaners > Electrics > OV 3450 VORTEX™

2 YEAR
WARRANTY

ULTIMATE POWER

- + Ultra-powerful & long lasting suction
- + Extra large suction capacity
- + Easy clean filter



REFERENCE

Product reference: WR000072

ACCESSORIES INCLUDED IN THE PACK



Trolley



Control box



Fine Filter canister 100µ

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles*, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	2 cycles : - Floor «Deep Clean» : 1h30 - Floor / walls / water line : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	Yes
Lift System	No
Full filter indicator	No
Remote control	No
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	18m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	19,1 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width	24,5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover	Front wheel tyre (for tiled pools) unit
Reference R0638600	R0636600	R0643700	R0568100	R0636400

*For perfect grip of your cleaner on tiles, replace the original tracks with suction tracks sold as accessories: Track front wheel tile - reference R0636400



9 317545 018003

ZPCE: recommended sales price valid from 01/01/2019 through 31/12/2019



OV 3480 VORTEX™

Pool Cleaners > Electrics > OV 3480 VORTEX™

2 YEAR
WARRANTY

ULTIMATE POWER

- + Ultra-powerful & long lasting suction
- + Extra large suction capacity
- + Easy clean filter



REFERENCE

Product reference: WR000147

ACCESSORIES INCLUDED IN THE PACK



Trolley



Control box



Fine Filter canister 100µ

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles*, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	2 cycles : - Floor «Deep Clean» : 1h30 - Floor / walls / water line : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	Yes
Lift System	No
Full filter indicator	No
Remote control	No
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	18m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	19,1 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width	24,5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover	Front wheel tyre (for tiled pools) unit
Reference	R0638600	R0636600	R0643700	R0568100	R0636400

*For perfect grip of your cleaner on tiles, replace the original tracks with suction tracks sold as accessories: Track front wheel tile - reference R0636400



9 317545 026107



GV 3420 VORTEX™

Pool Cleaners > Electrics > GV 3420 VORTEX™

2 YEAR
WARRANTY

ULTIMATE POWER

- + Ultra-powerful & long lasting suction
- + Extra large suction capacity
- + Easy clean filter







**NEW FOR
2019**



REFERENCE

Product reference: WR000192

ACCESSORIES INCLUDED IN THE PACK

			
Trolley	Control box	Fine Filter canister 100µ	Front wheel tyres for tiled pools

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles*, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	2 cycles : - Floor «Deep Clean» : 1h30 - Floor / walls / water line : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	Yes
Lift System	No
Full filter indicator	No
Remote control	No
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	18m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	19,1 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width	24,5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

			
Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover
Reference R0638600	R0636600	R0643700	R0568100

*For perfect grip of your cleaner on tiles, replace the original tracks with suction tracks provided in-pack





OV 3505 VORTEX™

Pool Cleaners > Electrics > OV 3505 VORTEX™

2 YEAR
WARRANTY

ULTIMATE POWER

- + Ultra-powerful & long lasting suction
- + Extra large suction capacity
- + Easy clean filter



REFERENCE

Product reference: WR000152

ACCESSORIES INCLUDED IN THE PACK



Trolley



Control box



Fine Filter canister 100µ



Kinetic remote control

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles*, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	6 cycles : - Floor «Deep Clean» : 1h, 1h30, 2h - Floor / walls / water line : 2h, 2h30, 3h
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	Yes
Lift System	No
Full filter indicator	No
Remote control	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	18m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	20,1 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width	24,5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover	Front wheel tyre (for tiled pools) unit
Reference	R0638600	R0636600	R0643700	R0568100	R0636400

*For perfect grip of your cleaner on tiles, replace the original tracks with suction tracks sold as accessories: Track front wheel tile - reference R0636400





RV 4390 TILE VORTEX™

Pool Cleaners > Electrics > RV 4390 TILE VORTEX™

3 YEAR
WARRANTY

ULTIMATE POWER

- + Ultra-powerful & long lasting suction
- + Extra large suction capacity
- + Easy clean filter



REFERENCE

Product reference: WR000150

ACCESSORIES INCLUDED IN THE PACK



Trolley



Control box



Fine Filter canister 100µ

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	2 cycles : - Floor «Deep Clean» : 1h30 - Floor / walls / water line : 2h30
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	Yes
Lift System	No
Full filter indicator	No
Remote control	No
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	18m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	22,3 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width	24,5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover
Reference R0638600	R0636600	R0643700	R0568100



9 317545 026114

ZPCE: recommended sales price valid from 01/01/2019 through 31/12/2019



RV 4550 TILE VORTEX™ PRO

Pool Cleaners > Electrics > RV 4550 TILE VORTEX™ PRO

3 YEAR
WARRANTY

ULTIMATE POWER





- + Ultra-powerful & long lasting suction
- + Effortless removal from the water
- + Extra large suction capacity



REFERENCE

Product reference: WR000043

ACCESSORIES INCLUDED IN THE PACK

			
Trolley	Control box	Fine Filter canister 100µ	Kinetic remote control

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 15 x7 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles




DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	6 cycles : - Floor «Deep Clean» : 1h, 1h30, 2h - Floor / walls / water line : 2h, 2h30, 3h
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	Yes
Lift System	Yes
Full filter indicator	Yes
Remote control	Yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Filtration system / access	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length	21m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	22,3 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width	24,5 cm

OPTIONAL ACCESSORIES (NOT INCLUDED)

				
	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover
Reference	R0638600	R0636600	R0643700	R0568100





GV 3520 VORTEX™

Pool Cleaners > Electrics > OV 3505 VORTEX™

2 YEAR WARRANTY

ULTIMATE POWER






- + Ultra-powerful & long lasting suction
- + Extra large suction capacity
- + Easy clean filter



REFERENCE

Product reference: WR000191

ACCESSORIES INCLUDED IN THE PACK

				
Trolley	Control box	Fine Filter canister 100µ	Kinetic remote control	Front wheel tyres for tiled pools

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope, diamond shape
Pool surfaces	Tiles*, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor / walls / water line
Number / Length of cleaning cycles	6 cycles : - Floor «Deep Clean» : 1h, 1h30, 2h - Floor / walls / water line : 2h, 2h30, 3h
Power supply	Autonomous, connected to 230V mains supply before the transformer
Steering	Pre-programmed
Drive system	2 wheel drive
Transmission	Gear transmission
Brushes	yes
Lift System	no
Full filter indicator	no
Remote control	yes
Safety	Deck system, out of water safety, diagnostic, electronic motor protector
Type de filtration / Collecte des débris	Rigid Filter canister with access over the cleaner
Units / pallet	16

TECHNICAL SPECIFICATIONS

Number of motors	3
Control box supply	200-240 VAC ; 50 / 60 Hz
Power supply	30 VDC
Operating power	150 W
Cable length / Hose length	18m
Cleaner size (L x W x h)	43 x 48 x 27 cm
Packaging size (L x W x h)	56 x 56 x 46 cm
Cleaner weight	9,5 kg
Packaging weight	20,1 kg
Filtering surface and level	1180 cm ² / 100µ
Filtering capacity	5 L
Theoretical cleaning width / Dimension d'aspiration	24,5 cm
Pump flow	16 m ³ / h

OPTIONAL ACCESSORIES (NOT INCLUDED)

				
	Ultra-fine filter canister 60µ	Fine filter canister 100µ	Large debris filter canister 200µ	Protective cover
reference	R0638600	R0636600	R0643700	R0568100

*For perfect grip of your cleaner on tiles, replace the original tracks with suction tracks provided in-pack.



9 317545 059099



HYDRAULIC CLEANERS

> HYDRAULIC ROBOT CLEANERS

A simple and affordable solution


COMPARATIVE TABLE OF RANGES

	R3®	MX6™	MX8™ PRO	Kontiki™ 2	T3®	T5® Duo
						
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years
Pool Dimension max.	9 x 5 m	10 x 5 m	12 x 6 m	8 x 4 m	9 x 5 m	12 x 6 m
Number of pipes 1 m - Twist Lock pipe	10	10	12	8	10	12
Displacement	Diaphragm	Mechanical	Mechanical	Diaphragm	Diaphragm	Diaphragm
Pool floors						
Rectangular	•	•	•	•	•	•
Oval	•	•	•	•	•	•
Round	•	•	•	•	•	•
Free shape		•	•			•
Floor only	•			•	•	
Floor and walls		•	•			•
Flat	•	•	•	•	•	•
Gentle slope	•	•	•	•	•	•
Composit slope		•	•			•
Diamond shape			•			
Minimum power required from the filtration pump	1/2 HP	3/4 HP*	3/4 HP*	1/2 HP	1/2 HP	3/4 HP

* 1 HP needed for tile pools

STANDARD INSTALLATION

- The suction cleaner is connected directly to the vacuum point or skimmer. No electrical connection required.
- The ideal hose length for the pool equals the greatest distance that the cleaner can cover in the pool from the connection point (skimmer) to the farthest corner of the pool, plus a 1 metre section.
- For optimal installation, perform a flow test and adjust the flow rate using an adjusting valve.





R3®

Pool Cleaners > Hydraulics > T3®

2 YEAR WARRANTY

- + DiaCyclone Diaphragm: even more powerful suction
- + Finned disc: optimum mobility of the cleaner



ALL TYPE OF LININGS



PRODUCT REFERENCE

Product reference: W70676

ACCESSORIES INCLUDED IN THE PACK

Twist Lock Hoses	Wheel deflector	Flow gauge	Flowkeeper valve (skimmer)

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 9 x 5 m
Pool shapes	Rectangular, oval
All Floors	Flat, gentle slope
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor
Cleaning cycles	Recommended 6h filtering in three 2h sessions
Power supply	Filtering group
Steering	Random
Installation	Suction line or skimmer
Suction system	DiaCyclone Diaphragm
Types of debris handled	Fine and medium
Units / pallet	27

TECHNICAL SPECIFICATIONS

Hose length	10 sections of 1 m
Cleaner size (L x W x h)	41 x 36 x 28 cm
Packaging size (L x W x h)	102,8 x 41,5 x 22,4 cm
Cleaner weight	1,2 kg
Packaging weight	6,8 kg
Filtering capacity	Pool filtering circuit
Cleaned width	30 cm
Displacement speed	6,5 m/min
Minimum required filter pump power	1/2 CV

OPTIONAL ACCESSORIES (NOT INCLUDED)

	6 section of 1m Twist Lock hoses
reference	W78055



9 3478580706761

ZPCE: recommended sales price valid from 01/01/2019 through 31/12/2019



MX6™

Pool Cleaners > Hydraulics > MX6™

2 YEAR
WARRANTY

- + Pre-programmed X-Drive navigation system : methodical cleaning of all areas
- + Turbo aspiration: a powerful turbine and one peripheral propeller
- + Traction using notched tracks: for perfect stability and total movement
- + Equipped with a flow regulator valve: automatically controls excess flow through cleaner for best performance and longevity



REFERENCE

Product reference: W79102

ACCESSORIES INCLUDED IN THE PACK

					
Twist Lock Hoses	In-ground valve cuff	45° Elbow extended	45° Elbow	Flow Regulator Valve (cleaner)	Flowkeeper valve (skimmer)

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 10 x 5 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete


DESCRIPTION

Cleaning areas	Floor and walls
Cleaning cycles	Recommended 6h filtering in three 2h sessions
Power supply	Filtering group
Steering	Random
Installation	Suction line or skimmer
Suction system	Mechanical suction : turbine
Types of debris handled	Fine and medium
Units / pallet	30

TECHNICAL SPECIFICATIONS

Hose length	10 sections of 1 m
Cleaner size (L x W x h)	31 x 19 x 22 cm
Packaging size (L x W x h)	102 x 23 x 37 cm
Cleaner weight	2,5 kg
Packaging weight	8,2 kg
Filtering capacity	Pool filtering circuit
Cleaned width	25 cm
Displacement speed	8 m/min
Minimum required filter pump power	3/4 HP (1 HP for Tile pools)

OPTIONAL ACCESSORIES (NOT INCLUDED)

	
	6 section of 1m Twist Lock hoses
Reference	W78055





MX8™

Pool Cleaners > Hydraulics > MX8™

2 YEAR
WARRANTY

- + Pre-programmed X-Drive navigation system : methodical cleaning of all areas
- + Turbo aspiration: a powerful turbine and two peripheral propellers
- + Traction using notched tracks: for perfect stability and total movement
- + Equipped with a flow regulator valve: automatically controls excess flow through cleaner for best performance and longevity



REFERENCE

Product reference: W70668

ACCESSORIES INCLUDED IN THE PACK

Twist Lock Hoses	In-ground valve cuff	45° Elbow extended	45° Elbow	Flow Regulator Valve (cleaner)	Flowkeeper valve (skimmer)

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor and walls
Cleaning cycles	Recommended 6h filtering in three 2h sessions
Power supply	Filtering group
Steering	Random
Installation	Suction line or skimmer
Suction system	Mechanical suction : turbine
Types of debris handled	Fine and medium
Units / pallet	30

TECHNICAL SPECIFICATIONS

Hose length	12 sections of 1 m
Cleaner size (L x W x h)	41 x 19 x 22 cm
Packaging size (L x W x h)	102 x 23 x 37 cm
Cleaner weight	3,2 kg
Packaging weight	9,5 kg
Filtering capacity	Pool filtering circuit
Cleaned width	36cm
Displacement speed	8 m/min
Minimum required filter pump power	3/4 HP (1 HP for Tile pools)

OPTIONAL ACCESSORIES (NOT INCLUDED)

	6 section of 1m Twist Lock hoses
Reference	W78055



ZPCE: recommended sales price valid from 01/01/2019 through 31/12/2019



KONTIKI™ 2

Pool Cleaners > Hydraulics > KONTIKI™ 2

2 YEAR WARRANTY

- + Diaphragm: membrane technology
- + Finned disc: optimum mobility of the cleaner



REFERENCE PRICE

Product reference: W70478

ACCESSORIES INCLUDED IN THE PACK



Adaptors (x2)



Hose deflectors (x2)

FOR WHICH TYPE OF POOLS?

Types of pools	Private above-ground pools with rigid walls, maximum 8 x 4 m
Pool shapes	Rectangular, oval
All Floors	Flat, gentle slope
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete



DESCRIPTION

Cleaning areas	Floor
Cleaning cycles	Recommended 6h filtering in three 2h sessions
Power supply	Filtering group
Steering	Random
Installation	Suction line or skimmer
Suction system	Diaphragm
Types of debris handled	Fine and medium
Units / pallet	24

TECHNICAL SPECIFICATIONS

Hose length	8 sections of 1 m
Cleaner size (L x W x h)	48 x 20 x 40 cm
Packaging size (L x W x h)	101 x 31,5 x 33 cm
Cleaner weight	1,3 kg
Packaging weight	5,5 kg
Filtering capacity	Pool filtering circuit
Cleaned width	40 cm
Displacement speed	6 m/min
Minimum required filter pump power	1/2 HP

OPTIONAL ACCESSORIES (NOT INCLUDED)

		
	6 sections of 1 m	Flow gauge
Reference	W69100	W70335P



3 478580 704781





- + DiaCyclone Diaphragm: even more powerful suction
- + Finned disc: optimum mobility of the cleaner



REFERENCE PRICE

Product reference: W70674

ACCESSORIES INCLUDED IN THE PACK

			
Twist Lock Hoses	Wheel deflector	Flow gauge	Flowkeeper valve (skimmer)

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 9 x 5 m
Pool shapes	Rectangular, oval
All Floors	Flat, gentle slope
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete


DESCRIPTION

Cleaning areas	Floor
Cleaning cycles	Recommended 6h filtering in three 2h sessions
Power supply	Filtering group
Steering	Random
Installation	Suction line or skimmer
Suction system	DiaCyclone Diaphragm
Types of debris handled	Fine and medium
Units / pallet	27

TECHNICAL SPECIFICATIONS

Hose length	10 sections of 1 m
Cleaner size (L x W x h)	41 x 36 x 28 cm
Packaging size (L x W x h)	102,8 x 41,5 x 22,4 cm
Cleaner weight	1,2 kg
Packaging weight	6,8 kg
Filtering capacity	Pool filtering circuit
Cleaned width	30 cm
Displacement speed	6,5 m/min
Minimum required filter pump power	1/2 HP

OPTIONAL ACCESSORIES (NOT INCLUDED)

	
	6 section of 1m Twist Lock hoses
Reference	W78055





T5[®]Duo

Pool Cleaners > Hydraulics > T5[®]Duo

2 YEAR
WARRANTY

- + DiaCyclone Diaphragm: even more powerful suction
- + Flexible Duo Traction Control disc in 2 parts: optimum grip



ALL TYPES OF SWIMMING POOLS



ALL TYPE OF LININGS



REFERENCE PRICE

Product reference: W78046

ACCESSORIES INCLUDED IN THE PACK



Twist Lock Hoses



Wheel deflector



Flow gauge



Flowkeeper valve (skimmer)

FOR WHICH TYPE OF POOLS?

Types of pools	Private in-ground pools and above-ground pools with rigid walls, maximum 12 x 6 m
Pool shapes	Rectangular, oval, free shape
All Floors	Flat, gentle slope, composite slope
Pool surfaces	Tiles, liner, polyester hull, reinforced PVC, painted concrete

DESCRIPTION

Cleaning areas	Floor and walls
Cleaning cycles	Recommended 6h filtering in three 2h sessions
Power supply	Filtering group
Steering	Random
Installation	Suction line or skimmer
Suction system	DiaCyclone Diaphragm
Types of debris handled	Fine and medium
Units / pallet	24

TECHNICAL SPECIFICATIONS

Hose length	12 sections of 1 m
Cleaner size (L x W x h)	44 x 43 x 22 cm
Packaging size (L x W x h)	99 x 45,5 x 29,5 cm
Cleaner weight	1,4 kg
Packaging weight	8,4 kg
Filtering capacity	Pool filtering circuit
Cleaned width	44 cm
Displacement speed	6 m/min
Minimum required filter pump power	3/4 HP

OPTIONAL ACCESSORIES (NOT INCLUDED)



6 section of 1m Twist Lock hoses

Reference

W78055



3 478580 780464



Water treatment

PH REGULATOR

- pH clever

p. 33

p. 34

SALT WATER CHLORINATOR

- Gensalt OE

p. 36


p. 37



> pH REGULATION SYSTEM

For perfect water balance

pH clever incorporates proportional dosing technology to **maintain an ideal pH automatically** for the comfort of bathers. For optimal water balance, pH clever includes a function to adjust injection cycles depending on the total alkalinity (TAC) of the water. **A choice of 3 settings is available:**




> SAFE, AUTO-ADAPTIVE OPERATION

Depending on the value measured by the sensor, Zodiac® pH regulation systems automatically adjust the pH of the swimming pool up or down, using a peristaltic dosing pump.

The dosing time depends on **the difference between the pH of the swimming pool and the ideal pH (set point value)**. The water balance in the swimming pool is maintained at the desired value without taking any action.

Zodiac® pH regulation systems are equipped **with an exclusive overdosing safety device** (called 'OFA') to prevent excessive injection. The safety device is adjustable and operates in 3 steps to determine whether or not it is necessary to inject correcting product.

EXCLUSIVE AUTO-ADAPTIVE DOSING




> FOR GREATER COMFORT

For the comfort of bathers, the pH of the swimming pool must be kept between 7.0 and 7.6:

- Below this, the water is aggressive.
- Above this, larger doses of disinfectant are needed to maintain healthy water and combat the growth of algae.
- The ideal pH for the swimming pool water is also the average pH of the human body, and more especially the blood, which is between 7.35 and 7.45.

pH SCALE



DID YOU KNOW?

The pH must be controlled and adjusted, whatever the disinfection system used. As a result, pH Expert can be used in all types of pools.

pH clever

Water treatment > Automatical regulators > pH clever

- + Automatic dosage of pH
- + Accurate dosing
- + Anti-overdose protection



2 YEAR WARRANTY

pH clever

PRODUCT REFERENCE

Standard model

WW000031

ACCESSORIES INCLUDED IN THE PACK



pH Sensor



Buffer solutions kit



Plumbing kit



Wall mounting kit



Suction Pipe

FOR WHICH POOL?

Maximum volume of treated water

150 m³

Dosage

Acid or alkaline

DESCRIPTION

User Interface

1-line, backlit LCD screen

Languages

6 (FR-EN-ES-DE-IT-NL)

Calibration

Semi-automatic in 1 or 2 steps (Buffer solutions kit included)

Setpoints

Factory setting: pH = 7,4

Sensor position

Vertical

Safety

Configurable 'OFA' three-level over-feed alarm (settings from 0 to 6 h, default 4 h)
Level sensor on intake pipe (equipped with anti-fumes cap)

TECHNICAL SPECIFICATIONS

Sensor type (pH)

Combined sensor, simple-junction and simple-porous, Ø12 mm epoxy body

Reading scale

0,0 - 14,0 pH

Reading accuracy

0,1 pH

Sensor Tolerances

0-60 °C, water speed ≤ 2 m/s

Maximum counter pressure (injection point)

1,5 bar

Peristaltic pH pump flow

1,5 L/h

Fixing collar**

For 50 mm pipes (standard) or 63 mm (accessory)

Protection index

IP65

Size (l x h x p)

19,5 x 23,6 x 8,5 cm

Power supply

220-240 VAC / 50-60 Hz

* Excluding consumable parts that have 1 year warranty (buffer solutions, peristaltic tube, one-way valve)

** Not needed if the "POD Kit" option is used.




9 317545017099


INSTALLATION

- The sensor must be placed more than 30 cm before or after any elbow fittings (otherwise, use the Pod Kit)
- The sensor must be installed vertically (maximum tolerance: 45°) Its cable (BNC type) is 5 m long.
- It is recommended to ground the pool water, so as to avoid parasitic currents.

pH clever installation diagram:



PH VALUE IS ESSENTIAL TO MAINTAIN CHLORINE EFFECTIVENESS:



OPTIONAL ACCESSORIES (NOT INCLUDED)

				
	POD Kit	63mm saddle clamp	pH 4 and pH 7 buffer solutions (x6 + x6)	Earthing anode
reference	R0534900	W013011	R0824400	R0673800



WATER TREATMENT

> SALT WATER CHLORINATOR

Automatic, easy and efficient disinfection

Simple to install and use, salt water chlorinators provide complete treatment with reduced maintenance.


> HOW DOES IT WORK?

The principle of salt electrolysis is simple. The swimming pool water is very slightly saline (from 2 to 4 g/L, meaning from 9 to 18 times less than sea water). By an electrolysis reaction across the cell of the system, chloride ions - from the salt dissolved in the water - are converted to chlorine gas, a powerful disinfectant that dissolves in the water instantaneously. **The resulting active chlorine (HOCl) destroys all the micro-organisms in the cell and provides an adequate level of free chlorine in the pool.** The active chlorine, which is removed by combining with organic matter and under the effect of UV rays in sunlight, is continuously renewed by the cell without action by the user.

For optimum efficiency of the chlorinator, **the pH of the swimming pool must be kept between 7.0 and 7.6.**

All Zodiac® chlorinators have cells with **high quality, long-lasting titanium electrodes**, ensuring peace of mind for the user.

CYCLIC REACTION OF SALT ELECTROLYSIS



REFERENCE POINT

Zodiac® control units and salt chlorinator cells will be repaired or exchanged during the guarantee period, whatever the causes of damage.



Gensalt OE

Water treatment > Salt water chlorinators > Gensalt OE

- + Long lasting
- + Suitable for all installations
- + Easy to install



2 YEAR WARRANTY

INCONDITIONNELLE GARANTIE INCONDITIONNELLE

Gensalt OE 17

Gensalt OE 25

PRODUCT REFERENCE

Standard model	WW000095	WW000096
----------------	----------	----------

ACCESSORIES INCLUDED IN THE PACK



Installation Kit

FOR WHICH POOL?

Volume of treated water (temperate climate, Filtration 8h/day)	70 m ³	110 m ³
Nominal output Amps	18 g/h	25 g/h
Ampérage de sortie nominal	3,6 A	5,0 A

DESCRIPTION

User Interface	Leds
Operating modes	normal
Timer	Controlled by filtration timer
Polarity reversal	Yes : 5 h
Required salt level - minimum	4 g/L - 3,0 g/L minimum
Safety	Low salt' indicator light: Reduced production to protect the electrode 'no flow' indicator light: Production is interrupted as long as conditions are not ideal
Cell position	Horizontal or vertical
Plumbing compatibility	DN50 mm, DN63 mm, 1 1/2" (48 mm)

TECHNICAL SPECIFICATIONS


Working life of cells*	7 500 h (titanium plates, SC6 ruthenium coating)	
Electric power	100 W	140 W
Minimum flow rate (needed to purge air from the cell)	5 m ³ / h	
Maximum flow rate (limited by pressure drops in the pipe)	18 m ³ /h (Bypass mandatory over this level)	
Maximum authorised cell pressure	2,75 bar (KPa)	
Maximum water temperature	40 °C	
Minimum water temperature	5 °C	
Length of the cell cable	1,8 m	
Protection index	IPX5	
Cell size (L x w x h)	16,5 x 22,5 x 12,5 cm	
Control box size (L x w x h)	28,5 x 40,5 x 12,5 cm	
Power supply	220-240 VAC / 50 Hz (mains power cable with moulded plug)	

* Under good operating conditions.



INSTALLATION

- Le coffret étant IPX5, il peut être installé n'importe où, y compris dans le volume 1 (cf. norme NF C15-100).
- La distance coffret de commande - cellule est de 1,5 m.
- Le coffret de commande doit être OBLIGATOIREMENT Controlled by filtration timer (alimentation électrique coupée quand la pompe de filtration s'éteint).

GenSalt OE installation diagram:



OPTIONAL ACCESSORIES (NOT INCLUDED)

		
	Locking ring wrench	Winterizing cap
reference	R0769900	R0770100



www.zodiac.com

Parc d'Activités du Chêne
2 rue Edison
69500 Bron
France

Tél. : +33 (0)820 60 99 98
Fax : +33 (0)276 34 18 80