



SIMPLE AND  
LONG-LASTING

**Ei<sup>2</sup>**

### **1** LONG-LASTING

One of the **longest-lasting** chlorinators in its category (up to 7,500 hours) thanks to its **high quality titanium** electrode.

**Ti<sup>22</sup>**  
**TITANIUM  
INSIDE**

### **2** SUITABLE FOR ALL INSTALLATIONS

The compact cell and watertight IPX5 casing allow the Ei<sup>2</sup> to be installed anywhere, **in confined spaces and even in humid environments.**

  
**EASY  
INSTALLATION**

### **3** FAST INSTALLATION

Ei<sup>2</sup> can be installed in **just 10 minutes** in any environment, thanks to its **patented Quick Fix system.**




## SPECIFICATIONS



### NO MAINTENANCE

Self-cleaning electrodes via reverse polarity.



### SHUTTER MODE

Automatic reduction of chlorine production when the pool's roller shutters are closed (adjustable to 0% or 20%).

## STOP

### SAFE-SYSTEM

Automatic stop if there is no flow in the cell.



### WATERPROOF

The "IPX5" waterproof control unit can be installed in all types of machine rooms.

UNCONDITIONAL  
GUARANTEE  
UNCONDITIONAL

### UNCONDITIONAL GUARANTEE

On the control box and the cell, whatever the causes of damage.

## FOR WHICH TYPE OF POOLS?

**1** ALL TYPES OF SWIMMING POOLS



**2** POOLS UP TO 90M<sup>3</sup>  
(TEMPERATE CLIMATE,  
FILTRATION 8 HR/DAY)



## STANDARD FEATURES



Cell installation kit  
for 50-mm and 63-mm hoses

## TECHNICAL INFORMATION

MODELS	Ei <sup>2</sup> 12	Ei <sup>2</sup> 20	Ei <sup>2</sup> 25
Volume of water treated (temperate climate, filtration 8hr/day)	50 m <sup>3</sup>	90 m <sup>3</sup>	110 m <sup>3</sup>
Nominal chlorine production	12 g/h	20 g/h	25 g/h
Power rating	70 W	110 W	140 W
User interface	LEDS		
Operating mode	Normal, Shutter mode (0-20%)		
Clock/Timer	Linked to the filtration		
Reverse polarity	Yes: 5 hr		
Recommended salt level - minimum	4 g/L - 3.0 g/L minimum (*)		
Safety	'Low salt' indicator light: reduced production to protect the electrode 'No flow' indicator light: production is interrupted until optimal conditions return		
Cell position	Horizontal or vertical		
Compatible pipework	DN50, DN63, 1/2" (48 mm)		
Protection rating	IPX5		
50 Hz power supply	220-240 VAC (mains power cable with moulded plug)		

## AVAILABLE ACCESSORIES



Locking ring wrench



Winterizing cap

Salt chlorinators are an **automatic and efficient** disinfection solution.  
**They are easy to use**, offer complete water treatment and **reduce maintenance**.

**2** YEAR  
UNCONDITIONAL  
WARRANTY