



PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/01/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Gear oil

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
3100 Sanders Road
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : 800 424 9300 (United States); 00 1 703 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin sensitisation, Category H317 1 May cause an allergic skin reaction.

Full text of H-statements: see section 16

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US) :



GHS07

Signal word (GHS US) : Warning
Hazard statements (GHS US) : May cause an allergic skin reaction.
Precautionary statements (GHS US) : Avoid breathing mist, spray, vapors
Contaminated work clothing must not be allowed out of the workplace.
Wear personal protective equipment as required.
If on skin: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Dispose of contents/container to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

2.3. Other hazards

Other hazards which do not result in classification : Avoid prolonged or repeated contact with used fluid.

2.4. Unknown acute toxicity (GHS US)

37.19 % of the mixture consists of ingredient (s) of unknown toxicity. (Oral, Dermal) 31.24 % of the mixture consists of ingredient (s) of unknown toxicity. (Inhalation Gas, Vapor Dust)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	% by wt	GHS-US classification
Mineral oil	(CAS-No.) 8012-95-1	3 – 7	Not classified
Amines, C12-14-tert-alkyl	(CAS-No.) 68955-53-3	0.1 – 1	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.
- Symptoms/effects after skin contact : Contact during a long period may cause light irritation.
- Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/effects after ingestion : Ingestion is likely to be harmful or have adverse effects.

4.3. Indication of any immediate medical attention and special treatment needed

Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to cause aspiration.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Alcohol-resistant foam. Carbon dioxide. Dry chemical.
- Unsuitable extinguishing media : Do not use a heavy water stream. Will float and can be reignited on water surface.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable. Promotes combustion.
- Explosion hazard : Not applicable.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Fight fire with normal precautions from a reasonable distance. Under fire conditions, hazardous fumes will be present.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray.

6.1.1. For non-emergency personnel

- Protective equipment : Use appropriate personal protection equipment (PPE).
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product. Plug the leak, cut off the supply. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Store in a dry place. Store in a well-ventilated place. Keep cool. Keep container closed when not in use. Protect from sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not store near food, foodstuffs, drugs or potable water supplies.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip		
ACGIH	ACGIH OEL TWA	5 mg/m ³ Chemical name: Oil mist, mineral
ACGIH	ACGIH OEL STEL	10 mg/m ³ Chemical name: Oil mist, mineral
OSHA	OSHA PEL TWA [1]	5 mg/m ³ Chemical name: Oil mist, mineral
OSHA	Remark (OSHA)	Skin notation
Mineral oil (8012-95-1)		
ACGIH	ACGIH OEL TWA	5 mg/m ³ (Inhalable fraction)
OSHA	OSHA PEL TWA [1]	5 mg/m ³
Amines, C12-14-tert-alkyl (68955-53-3)		
Not applicable		

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Protective goggles. Gloves.

Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration
	Neoprene rubber (HNBR), Nitrile rubber (NBR)			

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Amber Brown
Odor	: petroleum-like odor
Odor threshold	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 223 °C (433 °F) [Method used: Cleveland Open Cup]
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific Gravity	: 0.87
Density	: 0.87 kg/l (7.24 lbs/gal)
Solubility	: Water: Negligible
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 105.6 cSt @ 40 °C (100 °F)
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: Not applicable.
Oxidizing properties	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Mineral oil (8012-95-1)	
LD50 oral rat	> 5000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)

Amines, C12-14-tert-alkyl (68955-53-3)	
LD50 oral rat	300 mg/kg
LD50 dermal rat	1120 mg/kg
ATE US (oral)	300 mg/kg bodyweight
ATE US (dermal)	1120 mg/kg bodyweight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : ON CONTINUOUS EXPOSURE/CONTACT: May cause respiratory irritation.
Symptoms/effects after skin contact : Contact during a long period may cause light irritation.
Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion : Ingestion is likely to be harmful or have adverse effects.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.

12.2. Persistence and degradability

Mineral oil (8012-95-1)	
Persistence and degradability	Contains non readily biodegradable component(s).

12.3. Bioaccumulative potential

Mineral oil (8012-95-1)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the ozone layer : No known effect on the ozone layer
Effect on global warming : No additional information available

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Refer to current TDG Canada for further Canadian regulations

Not regulated

Transport by sea

In accordance with IMDG / IMO

Not regulated

Air transport

In accordance with IATA / ICAO

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

EPA TSCA Regulatory Flag

Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed

Mineral oil (8012-95-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Amines, C12-14-tert-alkyl (68955-53-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

WHMIS Classification

This SDS has been prepared according to the criteria of the Hazardous Products Regulations (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR. Applicable GHS information is listed in section 2.2 of this SDS.

Mineral oil (8012-95-1)

Listed on the Canadian DSL (Domestic Substances List)

Amines, C12-14-tert-alkyl (68955-53-3)

Listed on the Canadian DSL (Domestic Substances List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substance(s) known to the state of California to cause cancer, developmental toxicity and/or reproductive toxicity

PEAK 75W-90 GL-5 Full Synthetic Gear Lubricant with Limited Slip

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Mineral oil (8012-95-1)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List


SECTION 16: Other information

Revision date : 11/01/2021

Full text of H-statements:

H301	Toxic if swallowed.
H312	Harmful in contact with skin.
H317	May cause an allergic skin reaction.

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.