


## Q-HELIPAD APPROACH LIGHT (FATO)

## TECHNICAL DETAILS



Application:	Helipad/Heliport
Classification:	Safe Area
Light Source:	LED, steady burning
Light Colour:	White, 6000K
Light Intensity:	100 cd
Vertical Beam Profile:	as per CAP437/ ICAO
Colour chromaticity:	as per CAP437/ ICAO
Enclosure:	Aluminium, Powder coated RAL5015 / Polycarbonate
Mounting:	Frangible, 4 xM8
Input Voltage:	1) 100-240 VAC, 50-60 Hz 2) 24 VAC
External Earthing:	up to 4mm <sup>2</sup> / AWG 12
Ambient Temp:	-25°C to + 60°C
In Compliance With:	CAP437
Cable glands included:	2 x M25x1.5
Cable stops included:	1 x M25x1.5
Cable Outer Dimension:	12 - 19mm
Consumption:	10 Watt
Life expectancy:	100.000+ hours
Warranty:	2 Years
IP index:	IP 67
Weight:	4.2 Kg
Dimensions:	185x185x150 mm(LxWxH)
Packaging dimension:	200x200x200 mm (LxWxH)

## DESCRIPTION

The Q-Helipad Approach Light (FATO) is an ICAO compliance 100 cd approach light for all Helipad and Heliport facilities. The Q-Helipad Approach Light is available in several configurations such as 100-240 VAC and 24 VDC.


## CERTIFICATES



## ORDER CODE

**Q22FR03** – Q-Helipad Approach Light (FATO)

- 11** Input power: 100-240 VAC
- 12** Input power: 24 VDC



## MAIN DIMENSIONS

Find the main dimensions and mounting dimensions in the image below

