

# AXON EQ

## L- 862S(L) Stop Bar

### LED Elevated, Unidirectional



#### Compliance with Standards (current version)

**FAA** AC 150/5345-46 and FAA Engineering Brief No. 67, ETL certified

CE

#### Uses

##### FAA

- L - 862S(L) Stop Bar

#### Features and Benefits

##### Efficiency

- AXON EQ features ILCMS remote and onboard environmental sensors for the LINC 360 system, enabling high data capacity and radio degradation resistance. This results in top-notch communication platform for control, status, and health/usage monitoring.
- AXON EQ can be upgraded with plug-in modules and configured via LINC 360 or CORTEX CLOUD for additional features.
- AXON EQ version available with optional Cellular monitoring module.
- Infra Red for EFVS / NVG compatibility. Highly configurable to suit operational requirement.
- LED is PWM-modulated at 400 Hz to optimize performance and eliminate human flicker perception, regardless of brightness levels.
- Lights are fully dimmable and conform to FAA EB 67D and ICAO Annex 14 dimming curve
- Dedicated aiming device allows easy leveling and azimuth aiming of the light.
- Three screws allow for 4° leveling adjustment of the fixture after installation.

##### Sustainability

- Independent Product Carbon Footprint calculation to support in product lifecycle analysis.
- Modular housing maximizes parts commonality and enables midlife upgrades for enhanced functionality instead of requiring a new product.
- Options for either glass or UV-resistant polycarbonate outer lens.
- A single fixture family covers all elevated approach, runway and stop bar applications.

- IP68 & IP69K rated enclosure designed for harsh environments; all fastenings are stainless steel.
- This product is a direct replacement for ADB Safegate LED elevated fixtures, thanks to its mechanical and photometric backwards compatibility.
- Finishing: Stainless steel hardware, aluminum body, phosphated aviation yellow electrostatic polyester powder coating.
- Based on the LED manufacturer's ratings & calculations, we guarantee a LED life expectancy L70 higher than 50,000 operation hours.
- Aerodynamic and lightweight weight designed to withstand heaviest jet blast.

##### Safety

- Identifiable daytime recognition, with large surface area coloured optical module surround.
- Modular mechanical design consolidates and strengthens product components for faster, easier maintenance and reconfiguration.
- SMART Arctic kit with option of heater output down to 4.1A.
- Failed-LED Detection as required by Engineering Brief 67D.
- The product meets the lightning protection criteria of ANSI/IEEE C62.41-1991 and FAA Eng. Brief 67's Location Category C2 requirements, which outlines a 1.2/50 - 8/20  $\mu$ s combination wave, peaking at 10,000 V and 5,000 A.

##### Power Supply

- AXON EQ with integrated ILCMS with OFDM technology for use with LINC 360 system
- AXON EQ Optional Cellular monitoring, future upgradable and feature configurable



## ANNEX

### Elevated Stop Bar Fixtures Without Arctic Kit (Heater)

| Fixture type           | Fixture load | Isolation transformer |      | CCR load |
|------------------------|--------------|-----------------------|------|----------|
|                        |              | Wattage               | Load |          |
| FAA Stop Bar L-862S(L) | 11 VA        |                       |      |          |

### Additional Overhead VA per Function

| Fixture type     | Additional fixture VA        |
|------------------|------------------------------|
| SMART Arctic Kit | 5 VA                         |
| Infra Red        | 1.5 VA                       |
| Cellular Module  | 5 VA (4G/5G wireless module) |

For more information about the product, including manuals and certifications, please see the Product Center on the ADB SAFEGATE website: [www.adbsafegate.com](http://www.adbsafegate.com).