

Q-FLUSHMOUNT TLOF PERIMETER LIGHT (GREEN)



TECHNICAL DETAILS

Application:	Helipad/Heliport
Classification:	Safe Area
Light Source:	LED, steady burning
Light Colour:	Green, 530nm
Light Intensity:	30 cd International Civil Aviation Organization (ICAO), Heliports Annex 14, Volume 2, Fourth edition, 2013
Vertical Beam Profile:	as per ICAO Figure 5-11, Illustration 6
Colour chromaticity:	as per ICAO Figure A1-1b
Enclosure:	Aluminium, Powder coated RAL5015
Mounting:	Flushmount, 4x M6
Input Voltage:	1) 100-240 VAC, 50-60 Hz 2) 24 VDC
External Earthing:	up to 4mm ² / AWG 12
Ambient Temp:	-25°C to + 60°C
In Compliance With:	ICAO, Annex 14 vol 2
Cable glands included:	2 x M25x1.5
Cable Outer Dimensions:	12 - 16mm
Cable type:	H07RN-F 3x2,5mm ²
Consumption:	8 Watt
Life expectancy:	100.000+ hours
Warranty:	2 Years
IP index:	IP 67
Weight:	2 Kg
Dimensions:	200x200x122 mm (LxWxH)
Packaging dimension:	205x205x215mm (LxWxH)

DESCRIPTION


The Q-Flushmount TLOF Perimeter Light is an ICAO compliance 30 cd Perimeter light for all Helipad and Heliport facilities where flush installation is preferred. The Q-Flushmount TLOF Perimeter Light is available in several configurations such as 100-240 VAC and 24 VDC.

CERTIFICATES



ORDER CODE

Q10FM03 – Q-Flushmount TLOF Perimeter Light (green)



- 11** Input power: 100-240 VAC
- 12** Input power: 24 VDC

MAIN DIMENSIONS

Find the main dimensions and mounting dimensions in the image below

