

Q-FLUSHMOUNT APPROACH (WHITE)

TECHNICAL DETAILS



Application:	Helipad/Heliport
Classification:	Safe Area
Light Source:	LED, steady burning
Light Colour:	White, 6000K
Light Intensity:	100cd International Civil Aviation Organization (ICAO), Heliports Annex 14, Volume 2, Fourth edition, 2013 as per ICAO Figure 5-11, Illustration 5
Vertical Beam Profile:	as per ICAO Figure A1-1b
Colour chromaticity:	Aluminium, Powder coated RAL5015
Enclosure:	Flushmount, 4x M6
Mounting:	1) 100-240 VAC, 50-60 Hz
Input Voltage:	2) 24 VDC
External Earthing:	up to 4mm ² / AWG 12
Ambient Temp:	-25°C to + 60°C
In Compliance With:	ICAO, Annex 14 vol 2
Cable glands included:	2 x M25x1.5
Cable Outer Dimensions:	12 - 16mm
Cable type:	H07RN-F 3x2,5mm ²
Consumption:	8 Watt
Life expectancy:	100.000+ hours
Warranty:	2 Years
IP index:	IP 67
Weight:	2 Kg
Dimensions:	200x200x122 mm (LxWxH)
Packaging dimension:	205x205x215mm (LxWxH)

DESCRIPTION


The Q-Flushmount Helipad Approach Light is an ICAO compliance 100 cd FATO light for all Helipad and Heliport facilities where flush installation is preferred. The Q-Flushmount FATO Light is available in several configurations such as 100-240 VAC and 24 VDC.

CERTIFICATES



ORDER CODE

Q22FM03 – Q-Flushmount FATO Light (White)



- 11 Input power: 100-240 VAC
- 12 Input power: 24 VDC

MAIN DIMENSIONS

Find the main dimensions and mounting dimensions in the image below

