

VOLUKLER



OIL & GAS

Oil and petroleum/Petrol pumps



APPLICATIONS

For equipment of petrol pumps: regular, super and unleaded petrol, biofuel, diesel fuel.

ADVANTAGES

- Good resistance to ageing and abrasion from repeated dragging over oily floors.
- Complies with European standard.
- Can be supplied ready fitted and tested with end fittings.

COMPLEMENTARY INFORMATION

2 standard colors available.

Type BK = Black

Type GR = Green

Blue or red cover upon request.

TECHNICAL DESCRIPTION

Inner tube	petrol resistant NBR, black, smooth.
Reinforcement	synthetic textilebraided
Cover	oil and weather resistant NBR/PVC, black or green, smooth.
Working temperature	-30°C => +55°C.
Electrical Properties	conductive tube, $R < 10^6 \Omega / \text{lg}$.

STANDARD/APPROVAL

EN 1360:2013 type 1.

ID 21mm: also available as VOLUKLER VR ASSEMBLY with

EN

French directive TMD (carriage of dangerous goods in France).

TMD

TRELLEBORG - VOLUKLER - EN 1360:2013 - TYPE 1 - ND - 16 BAR - Ω - quarter/year - batch number - Made in France



16-19-25mm



21 mm - Addition of EN 13483:2013 Type 1 marking



16 mm

**OIL & GAS****VOLUKLER**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	TYPE	ARTICLE NUMBER
16.0	25.0	16	48	80	0.40	40.0	BK	5513438
16.0	25.0	16	48	80	0.37	40.0	GR	5513451
16.0	25.0	16	48	80	0.40	80.0	BK	5513439
16.0	25.0	16	48	80	0.37	80.0	GR	5513452
16.0	25.0	16	48	80	0.40	120.0	BK	5513440
19.0	31.0	16	48	100	0.63	40.0	BK	5513442
19.0	31.0	16	48	100	0.63	80.0	BK	5513443
19.0	31.0	16	48	100	0.63	120.0	BK	5513444
21.0	31.0	16	48	75	0.55	40.0	BK	5513466
21.0	31.0	16	48	75	0.55	80.0	BK	5513467
25.0	37.0	16	48	140	0.75	40.0	BK	5513446
25.0	37.0	16	48	140	0.75	80.0	BK	5513447

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

