

PROJECTOR 120



CONSTRUCTION & INFRASTRUCTURE



Spraying

APPLICATIONS

For spraying of wet mortar, mixed concrete and other wet products. Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

ADVANTAGES

- High working pressure.
- Light weight, flexible and easy to handle.
- Abrasion resistant tube.
- Non-staining white cover avoids traces on walls and floors.

COMPLEMENTARY INFORMATION

13.3m lengths available on request, min. order is three pieces and by multiple of three.

Other wall thickness and/or bursting pressure on request.

2 standard colors available.

Type BK = Black

Type WH = White

TECHNICAL DESCRIPTION


Inner tube	wear resistant NR, black, smooth.
Reinforcement	synthetic textile
Cover	wear and weather resistant SBR, black, fabric impression.
Working temperature	-30°C => +70°C.
Electrical Properties	antistatic tube.
Special Properties	abrasion resistance of tube <40mm3 according to ISO 4649.





**CONSTRUCTION &
INFRASTRUCTURE**

PROJECTOR 120



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	TYPE	ARTICLE NUMBER
25.0	39.0	40	120	200	0.85	40.0	BK	5513551
25.0	39.0	40	120	200	0.85	40.0	WH	59006807
30.0	44.0	40	120	240	1.00	40.0	BK	5513552
32.0	48.0	40	120	260	1.22	40.0	BK	5513553
35.0	49.0	40	120	280	1.12	40.0	BK	5513554
35.0	49.0	40	120	280	1.13	40.0	WH	59006808
38.0	54.0	40	120	300	1.45	40.0	BK	5513564
40.0	55.0	40	120	310	1.53	40.0	BK	59006802
50.0	68.0	40	120	410	2.01	20.0	BK	59006804
50.0	68.0	40	120	410	2.22	20.0	WH	59006809
50.0	68.0	40	120	410	2.01	40.0	BK	5513557
50.0	68.0	40	120	410	2.22	40.0	WH	59006810
60.0	80.0	40	120	480	2.66	40.0	BK	5513558
63.0	83.0	40	120	500	2.77	40.0	BK	5513559
65.0	85.0	40	120	520	2.84	20.0	BK	59006805
90.0	114.0	40	120	720	4.45	20.0	BK	59006806
102.0	130.0	40	120	800	5.67	40.0	BK	5513563

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

