

SUPERVAST



OIL & GAS

Steam



APPLICATIONS

For heavy duty industrial cleaning and circulation of saturated and superheated steam in heating systems in applications where the hose is exposed to oil.
Used in the petrochemical, building, shipyard and chemical industry.

ADVANTAGES

- Oil resistant cover.
- Multipurpose hose.
- Highly flexible.
- Very high temperature resistance.
- Chemical resistant.
- Durable and safe performance.
- Fulfills international standards.

TECHNICAL DESCRIPTION

Inner tube	EPDM, black, smooth.
Reinforcement	steelbraided
Cover	CSM, red, fabric impression.
Working temperature	Water: -40°C to +120°C, WP=60bar. Saturated steam: +210°C/18bar. Superheated steam: +230°C/18bar
Electrical Properties	conductive tube, $R < 10^6 \Omega / \text{lg}$.

STANDARD/APPROVAL

ISO 6134:2017 type 2 class B.

ISO





OIL & GAS

SUPERVAST



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	33.0	18	180	190	0.77	20.0	5015531
19.0	33.0	18	180	190	0.77	30.0	5015570
19.0	33.0	18	180	190	0.77	40.0	5015532
25.0	40.0	18	180	250	1.06	20.0	5015534

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

