

HYDRO'K



GENERAL INDUSTRY

Multipurpose oil



APPLICATIONS

A versatile hose for industrial use.
For diesel oil, mineral oil and grease with aromatic content $\leq 50\%$.
Return hose in hydraulic system and for farming equipment.
Sea water (engine cooling) and aqueous solution.
An allround hose for oil, water, compressed air, grease, etc.

ADVANTAGES

A multi-purpose hose to minimize inventory.
Ozone, abrasion and oil splash resistant cover.

COMPLEMENTARY INFORMATION

Length 50m: packed in carton.


TECHNICAL DESCRIPTION

Inner tube	oil resistant NBR/PVC, black, smooth.
Reinforcement	synthetic textile
Cover	oil and weather resistant NBR/SBR, black, smooth.
Working temperature	-25°C => +100°C.



TRELLEBORG

HYDRO'K ID Ø WP 16 bar - Made in France





GENERAL INDUSTRY

HYDRO'K



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
5.0	11.5	16	48	30	0.12	20.0	0060722
5.0	11.5	16	48	30	0.12	40.0	0060723
5.0	11.5	16	48	30	0.12	80.0	0060724
5.0	11.5	16	48	30	0.12	120.0	0060725
6.0	13.0	16	48	35	0.15	20.0	0060727
6.0	13.0	16	48	35	0.15	40.0	0060728
6.0	13.0	16	48	35	0.15	80.0	0060729
6.0	13.0	16	48	35	0.15	120.0	0060730
8.0	15.0	16	48	40	0.18	20.0	0060732
8.0	15.0	16	48	40	0.18	40.0	0060733
8.0	15.0	16	48	40	0.18	80.0	0060734
8.0	15.0	16	48	40	0.18	120.0	0060735
10.0	17.0	16	48	45	0.22	20.0	0060737
10.0	17.0	16	48	45	0.22	40.0	0060738
10.0	17.0	16	48	45	0.22	50.0	0060703
10.0	17.0	16	48	45	0.22	80.0	0060739
10.0	17.0	16	48	45	0.22	120.0	0060740
13.0	20.5	16	48	50	0.27	20.0	0060742
13.0	20.5	16	48	50	0.27	40.0	0060743
13.0	20.5	16	48	50	0.27	50.0	0060704
13.0	20.5	16	48	50	0.27	80.0	0060744
13.0	20.5	16	48	50	0.27	120.0	0060745
15.0	23.0	16	48	55	0.32	20.0	0060746
15.0	23.0	16	48	55	0.32	40.0	0060747
15.0	23.0	16	48	55	0.32	80.0	0060748
15.0	23.0	16	48	55	0.32	120.0	0060749
16.0	24.0	16	48	60	0.34	20.0	0060844
16.0	24.0	16	48	60	0.34	40.0	0060845
16.0	24.0	16	48	60	0.34	80.0	0060846
19.0	27.4	16	48	65	0.42	20.0	0060750
19.0	27.4	16	48	65	0.42	40.0	0060751
19.0	27.4	16	48	65	0.42	80.0	0060753
25.0	35.0	16	48	80	0.68	20.0	0060755
25.0	35.0	16	48	80	0.68	40.0	0060756
25.0	35.0	16	48	80	0.68	80.0	0060757

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

