

RED WATER



GENERAL INDUSTRY

Air and water



APPLICATIONS

Water discharge under pressure on industrial or urban sites.

ADVANTAGES


- Sturdy hose.
- Good resistance to abrasion thanks to wall thickness.

TECHNICAL DESCRIPTION

| | |
|---------------------|--|
| Inner tube | SBR for ID≤25mm, EPDM for ID>25mm, black, smooth. |
| Reinforcement | synthetic textile |
| Cover | SBR, red, smooth for ID≤25mm, fabric impression for ID>25mm. |
| Working temperature | -25°C => +70°C. |

TRELLEBORG

RED WATER





GENERAL INDUSTRY

RED WATER



| ID (MM) | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | BENDING RADIUS (MM) | WEIGHT (KG/M) | LENGTH (M) | ARTICLE NUMBER |
|---------|---------|------------------------|-------------------------|---------------------|---------------|------------|----------------|
| 13.0 | 21.0 | 10 | 30 | 78 | 0.36 | 40.0 | 5503031 |
| 16.0 | 24.0 | 10 | 30 | 96 | 0.43 | 20.0 | 5503404 |
| 16.0 | 24.0 | 10 | 30 | 96 | 0.43 | 40.0 | 5503040 |
| 19.0 | 28.0 | 10 | 30 | 115 | 0.57 | 20.0 | 5503405 |
| 19.0 | 28.0 | 10 | 30 | 115 | 0.57 | 40.0 | 5503032 |
| 25.0 | 35.0 | 10 | 30 | 150 | 0.80 | 40.0 | 5503033 |
| 32.0 | 43.0 | 10 | 30 | 200 | 0.90 | 40.0 | 5503034 |
| 38.0 | 50.0 | 10 | 30 | 210 | 1.00 | 40.0 | 5503035 |
| 50.0 | 65.0 | 10 | 30 | 400 | 1.60 | 40.0 | 5503036 |

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

