

RED WATER



GENERAL INDUSTRY

Air and water



APPLICATIONS

Water discharge under pressure on industrial or urban sites.

ADVANTAGES

Sturdy hose.


Good resistance to abrasion thanks to wall thickness.

TECHNICAL DESCRIPTION

Inner tube	SBR for ID≤25mm, EPDM for ID>25mm, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, red, smooth for ID≤25mm, fabric impression for ID>25mm.
Temperature range	-25°C => +70°C

TRELLEBORG

RED WATER





GENERAL INDUSTRY

RED WATER



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	21.0	10	30	78	0.36	40	5503031
16.0	24.0	10	30	96	0.43	20	5503404
16.0	24.0	10	30	96	0.43	40	5503040
19.0	28.0	10	30	115	0.57	20	5503405
19.0	28.0	10	30	115	0.57	40	5503032
25.0	35.0	10	30	150	0.80	20	5503406
25.0	35.0	10	30	150	0.80	40	5503033
32.0	43.0	10	30	200	0.90	40	5503034
38.0	50.0	10	30	210	1.00	40	5503035
50.0	65.0	10	30	400	1.60	40	5503036

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

