

# OIL 10 D



## OIL & GAS

Oil and petroleum/Discharge applications



### APPLICATIONS

Delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%.  
Limited use for biofuels. Consult us.

### TECHNICAL DESCRIPTION


Inner tube	synthetic NBR rubber, black, smooth.
Reinforcement	synthetic textile
Cover	synthetic NBR/SBR rubber, black, fabric impression.
Temperature range	-30°C => +80°C
Electrical Properties	conductive tube, $R < 10^6 \Omega/m$ .

**OIL 10 D**



**TRELLEBORG**

**OIL 10 D**





OIL & GAS

OIL 10 D



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
16.0	26.0	10	30	130	0.45	40	5514101
19.0	31.0	10	30	160	0.60	40	5514102
25.0	37.0	10	30	200	0.74	40	5514103
30.0	41.0	10	30	300	0.78	40	5514104
32.0	44.0	10	30	320	0.90	20	5514105
32.0	44.0	10	30	320	0.90	40	5514106
35.0	46.0	10	30	350	0.89	40	5514107
38.0	51.0	10	30	380	1.17	20	5514108
38.0	51.0	10	30	380	1.17	40	5514109
40.0	54.0	10	30	400	1.34	40	5514110
45.0	59.0	10	30	450	1.48	40	5514111
51.0	65.0	10	30	510	1.65	20	5514112
51.0	65.0	10	30	510	1.65	40	5514113
60.0	74.0	10	30	600	1.80	40	5514114
63.0	75.0	10	30	630	1.66	40	5514115
75.0	90.0	10	30	700	2.44	40	5514116
80.0	95.0	10	30	760	2.58	40	5514117
90.0	105.0	10	30	800	2.88	40	5514118

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

